

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST

Revision date: 22.11.2023

Product code: 03346

Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST

UFI: V989-Q08A-500W-5DA2

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Skin Corr. 1B; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

nitric acid

Signal word: Danger

Pictograms:



###### Hazard statements

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 2 of 11

**Precautionary statements**

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

**Special labelling of certain mixtures**

- EUH071 Corrosive to the respiratory tract.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7697-37-2	nitric acid			5 - < 10 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!

**After inhalation**

- Provide fresh air.
- If breathing is irregular or stopped, administer artificial respiration.
- Call a physician immediately.

**After contact with skin**

- Wash immediately with: Water
- Take off immediately all contaminated clothing and wash it before reuse.
- Call a physician immediately.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST

Revision date: 22.11.2023

Product code: 03346

Page 3 of 11

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage  
Causes burns.  
Cough  
Dyspnoea  
Risk of serious damage to eyes.  
Vomiting  
Methaemoglobinaemia

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids  
Hazardous combustion products  
In case of fire may be liberated:  
Nitrogen oxides (NO<sub>x</sub>)

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.  
Do not inhale explosion and combustion gases.  
Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Corrosive to metals.

##### For non-emergency personnel

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST

Revision date: 22.11.2023

Product code: 03346

Page 4 of 11

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### **7.1. Precautions for safe handling**

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Material, oxygen-rich, Oxidising

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations.

Keep in a cool place.

#### Further information on storage conditions

Unsuitable container/equipment material: Metal, Light metal

### **7.3. Specific end use(s)**

Laboratory chemicals

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST

Revision date: 22.11.2023

Product code: 03346

Page 5 of 11

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

### 8.2. Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Face protection shield  
goggles.

##### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L  
Recommended material: NBR (Nitrile rubber) 0,11mm  
Wearing time with permanent contact: >480min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L  
Recommended material: NBR (Nitrile rubber) 0,11mm  
Wearing time with occasional contact (splashes): >480min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 6 of 11

Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	X
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	<1
Viscosity / kinematic:	No data available
Water solubility:	very soluble
Solubility in other solvents not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,0345 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties No data available	

**Other safety characteristics**

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

**Further Information**

Corrosive to metals.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Corrosive to metals.  
Oxidising agent, strong

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 7 of 11

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Danger of explosion:

Acetone, Alcohol, Aniline, Substance, organic, Benzene, Aniline, Amines, Hydrocarbons, halogenated, Diethyl ether, Hydrazine, Dioxane, Acetic acid, Acetic anhydride, Ethanol, Fluorine, Formaldehyde, Rubber articles, Hydrocarbons, Copper, Powdered metals, Methanol, Phosphorus trichloride, Hydrogen phosphides, Gasoline, Reducing agent, titanium, Toluene, Hydrogen peroxide, tin, Xylene, Dichloromethane, carbon black, Potassium chlorate, permanganates, e.g. potassium permanganate

Ignition hazard:

Amines, Ammonia (NH<sub>3</sub>), Combustible substance, aldehydes, Hydrogen iodide (HI), White/yellow phosphor, Hydrogen sulphide (H<sub>2</sub>S), Alkali metals, Alkaline earth metal

Violent reaction with:

Nitriles, antimony, arsenic, boron, Alkali (lye), , Formic acid, sulphuric acid, sulphuric acid, sulphuric acid, selenium

**10.4. Conditions to avoid**

Heat

**10.5. Incompatible materials**

Cellulose, Metal

Keep away from: Metal.

Keep away from combustible material.

The product develops hydrogen in an aqueous solution in contact with metals. / Nitrogen oxides (NO<sub>x</sub>)

**10.6. Hazardous decomposition products**

In case of fire may be liberated:

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

Causes serious eye damage.

Corrosive to the respiratory tract.

Risk of serious damage to eyes.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 8 of 11

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

There are no data available on the mixture itself.

**Further information**

Irritant — skin irritation and eye damage

Causes burns.

Cough

Dyspnoea

Risk of serious damage to eyes.

Vomiting

Methaemoglobinaemia

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC	> 419 mg/l	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50	> 1000 mg/l ( )	3 h	Activated sludge	Study report (2008) OECD Guideline 209

**12.2. Persistence and degradability**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 9 of 11

The methods for determining the biological degradability are not applicable to inorganic substances.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not empty into drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Do not mix with other wastes.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2031
<b>14.2. UN proper shipping name:</b>	NITRIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2031
<b>14.2. UN proper shipping name:</b>	NITRIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 10 of 11

<b>14.1. UN number or ID number:</b>	UN 2031
<b>14.2. UN proper shipping name:</b>	NITRIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 2031
<b>14.2. UN proper shipping name:</b>	NITRIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	A212
Limited quantity Passenger:	Forbidden
Passenger LQ:	Forbidden
Excepted quantity:	E0
IATA-packing instructions - Passenger:	Forbidden
IATA-max. quantity - Passenger:	Forbidden
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Oxidising substances. strongly corrosive.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,12.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**AAS standard bismuth 1.000 g Bi/I Bi(NO<sub>3</sub>)<sub>3</sub> \* 5 H<sub>2</sub>O in nitric acid 1 mol/l traceable to NIST**

Revision date: 22.11.2023

Product code: 03346

Page 11 of 11

**Abbreviations and acronyms**

- Ox. Liq: Oxidising liquid
- Met. Corr: Substance or mixture corrosive to metals
- Acute Tox: Acute toxicity
- Skin Corr: Skin corrosion
- Eye Dam: Eye damage
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

**Relevant H and EUH statements (number and full text)**

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- EUH071 Corrosive to the respiratory tract.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*