

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

UFI: 7GD9-H02S-6005-K3V7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0 Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

sodium hydroxide

Signal word: Danger

Pictograms:



Hazard statements

H290 May be corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 2 of 11

H314 Causes severe skin burns and eye damage.

Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1310-73-2	sodium hydroxide			5 - < 10 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1310-73-2	215-185-5	sodium hydroxide	5 - < 10 %
	Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 3 of 11

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation
Dyspnoea
Cough
Circulatory collapse
Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 4 of 11

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe vapour/aerosol.

Read label before use.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide adequate ventilation as well as local exhaust at critical locations.

Unsuitable container/equipment material:

Metal

Aluminium

Tin

Zinc

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl4 in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 5 of 11

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
1310-73-2	sodium hydroxide		
Worker DNEL, long-term	inhalation	local	1 mg/m ³
Consumer DNEL, long-term	inhalation	local	1 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		>13
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
not determined		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		No data available
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

Corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 7 of 11

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Metal, Light metal (Formation of: Hydrogen)
Phenols
Combustible substance
Alkaline earth metal (Metal powder)
Acids, Nitriles

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Aluminium, Brass, Glass
Tin, Zinc, Aluminium
plastic

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 8 of 11

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

Skin corrosion/irritation

Dyspnoea

Cough

Circulatory collapse

Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
1310-73-2	sodium hydroxide						
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia sp.	Ecotoxicology and Environmental Safety,4	other: acute 48-h immobilization test ac

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

not applicable

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

Further information

Do not allow to enter into surface water or drains.

Harmful effect due to pH shift.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 9 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Do not empty into drains.
Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Classification code: C5
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Classification code: C5
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-A, S-B
Segregation group: alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Special Provisions: A3 A803

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 10 of 11

Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		851
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		855
IATA-max. quantity - Cargo:		30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Skin Corr: Skin corrosion

Eye Dam: Eye damage

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicon standard 1.000g Si/L SiCl₄ in sodium hydroxide 2 mol/l for AAS - traceable to NIST

Revision date: 17.03.2025

Product code: 03395

Page 11 of 11

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)