

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sulfuric acid 90.3 % for testing white vaseline according to DAB

UFI: XJSG-50EK-S00U-NP72

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

sulphuric acid

Signal word: Danger

Pictograms:



Hazard statements

H290 May be corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 2 of 11

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 IF exposed or concerned:
 P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	Classification (Regulation (EC) No 1272/2008)	REACH No
7664-93-9	sulphuric acid	90 - < 95 %
	231-639-5	016-020-00-8
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318	01-2119458838-20

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7664-93-9	231-639-5	sulphuric acid	90 - < 95 %
		oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 3 of 11

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.
Causes burns.
Irritant
Cough
Dyspnoea
Vomiting
Gastric perforation
Nausea
Abdominal pain

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Avoid contact with skin, eyes and clothes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 4 of 11

6.3. Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff.
- Use personal protection equipment. Use extractor hood (laboratory).
- Provide adequate ventilation.
- Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

- No special fire protection measures are necessary.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed.
- Unsuitable container/equipment material: Metal

Further information on storage conditions

- Corrosive to metals.
- The product develops hydrogen in an aqueous solution in contact with metals.

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 5 of 11

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³
Worker DNEL, acute		inhalation	local	0,1 mg/m ³

PNEC values

CAS No	Substance	Value
7664-93-9	sulphuric acid	
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,002 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		8,8 mg/l

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:
goggles
Face protection shield

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®
Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 6 of 11

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		<1
Viscosity / kinematic:		No data available
Water solubility:		very soluble (Heat)
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,814 g/cm ³
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 7 of 11

Solid: No data available
 Gas: No data available
 Oxidizing properties
 No data available

Other safety characteristics

Evaporation rate: No data available
 Solvent separation test: No data available
 Solvent content: No data available
 Solid content: No data available
 Sublimation point: No data available
 Softening point: No data available
 Pour point: No data available
 No data available:
 Viscosity / dynamic: No data available
 Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.
 Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with:
 Water, Alkali metals, Ammonia
 aldehydes, Alkaline earth metal, Acids
 Alkali (lye), Metal,
 Phosphorus oxides, Combustible substance
 Solvent, Aniline, permanganates, e.g. potassium permanganate
 Peroxides, Amines, Carbide
 peroxides, for example hydrogen peroxide , Nitriles

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal
 The product develops hydrogen in an aqueous solution in contact with metals.
 Cellulose

10.6. Hazardous decomposition products

In case of fire may be liberated:
 SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 8 of 11

Acute toxicity

Based on available data, the classification criteria are not met.
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).
Irritation to respiratory tract (Cough, Dyspnoea)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 2140 mg/kg	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser

Irritation and corrosivity

Causes severe skin burns and eye damage.
Causes serious eye damage.
Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

Risk of serious damage to eyes.
Causes burns.
Irritant
Cough
Dyspnoea
Vomiting
Gastric perforation
Nausea
Abdominal pain

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 9 of 11

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC 0,025 mg/l	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not mix with other wastes.
Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: SULPHURIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 10 of 11

Classification code: C1
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 80
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8
 Classification code: C1
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8
 Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: SULPHURIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y840
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 851
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 855
 IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid 90.3 % for testing white vaseline according to DAB

Revision date: 12.02.2024

Product code: 05702

Page 11 of 11

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals
Skin Corr: Skin corrosion
Eye Dam: Eye damage
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)