

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

UFI: 5JAH-D036-E00U-M8KU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290
Skin Corr. 1A; H314
Eye Dam. 1; H318
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

EDTA Na 2
sodium hydroxide

Signal word: Danger

Pictograms:



Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 2 of 14

Hazard statements

- H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H373 May cause damage to organs (Respiratory tract, lung) through prolonged or repeated exposure if inhaled.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
6381-92-6	EDTA Na 2			15 - < 20 %
	205-358-3		01-2119486775-20	
	Acute Tox. 4, STOT RE 2; H332 H373			
1310-73-2	sodium hydroxide			10 - < 15 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			
7647-14-5	sodium chloride			5 - < 10 %
	231-598-3		01-2119485491-33	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
6381-92-6	205-358-3	EDTA Na 2	15 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 2800 mg/kg	
1310-73-2	215-185-5	sodium hydroxide	10 - < 15 %
		Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	
7647-14-5	231-598-3	sodium chloride	5 - < 10 %
		dermal: LD50 = > 10000 mg/kg; oral: LD50 = 3550 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 3 of 14

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

corrosive

Irritant

Dyspnoea

Cough

Circulatory collapse

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 4 of 14

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 5 of 14

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material:

Metal, Aluminium, Zinc, tin

Hints on joint storage

national regulations

Further information on storage conditions

Store in a dry place.

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 6 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
6381-92-6	EDTA Na 2			
Worker DNEL, long-term		inhalation	local	1,5 mg/m ³
Worker DNEL, acute		inhalation	local	3 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,6 mg/m ³
Consumer DNEL, acute		inhalation	local	1,2 mg/m ³
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
1310-73-2	sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³
7647-14-5	sodium chloride			
Consumer DNEL, long-term		dermal	systemic	126,65 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	126,65 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	126,65 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	126,65 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2068,62 mg/m ³
Worker DNEL, acute		inhalation	systemic	2068,62 mg/m ³
Worker DNEL, acute		dermal	systemic	295,52 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	443,28 mg/m ³
Consumer DNEL, acute		inhalation	systemic	443,28 mg/m ³
Worker DNEL, long-term		dermal	systemic	295,52 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
6381-92-6	EDTA Na 2		
		Freshwater	2,2 mg/l
		Freshwater (intermittent releases)	1,2 mg/l
		Marine water	0,22 mg/l
		Micro-organisms in sewage treatment plants (STP)	43 mg/l
7647-14-5	sodium chloride		
		Freshwater	5 mg/l
		Micro-organisms in sewage treatment plants (STP)	500 mg/l
		Soil	4,86 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 7 of 14

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 8 of 14

pH-Value:	12,4
Viscosity / kinematic:	No data available
Water solubility:	completely miscible
Solubility in other solvents	not determined
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density (at 20 °C):	1,2543 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	not applicable
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	Not oxidising.

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	0
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

metals, Light metal (Formation of: Hydrogen)
Combustible substance, Phenols
Acid, Nitriles, Alkaline earth metal (Metal powder)

10.4. Conditions to avoid

No data available

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 9 of 14

10.5. Incompatible materials

Aluminium, Brass
metals (including their alloys), Zinc
Tin, Light metal
Glass, plastics
Material, containing silicate

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).
Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
6381-92-6	EDTA Na 2				
	oral	LD50 2800 mg/kg	Rat	Study report (1973)	BASF-TEST: In principle, the methods des
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
7647-14-5	sodium chloride				
	oral	LD50 3550 mg/kg	Rat	Study report	The study methodology followed appeared
	dermal	LD50 > 10000 mg/kg	Rabbit	Study report	The study methology followed appeared to

Irritation and corrosivity

Causes severe skin burns and eye damage.
Causes serious eye damage.
Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (EDTA Na 2)

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 10 of 14

Aspiration hazard

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

corrosive

Irritant

Dyspnoea

Cough

Circulatory collapse

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
6381-92-6	EDTA Na 2					
	Acute fish toxicity	LC50 41 mg/l	96 h	Lepomis macrochirus	Bull. Environm. Contam. Toxicol. 24: 543	The static water acute toxicity tests fo
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2001)	OECD Guideline 201
	Acute crustacea toxicity	EC50 140 mg/l	48 h	Daphnia magna	Study report (1989)	other: DIN 38412, part 11
	Fish toxicity	NOEC >= 25,7 mg/l	35 d	Danio rerio	Study report (2001)	OECD Guideline 210
	Crustacea toxicity	NOEC 25 mg/l	21 d	Daphnia magna	Study report (1998)	other: EEC Guideline XI/681/86, Draft 4:
1310-73-2	sodium hydroxide					
	Acute crustacea toxicity	EC50 40,4 mg/l	48 h	Ceriodaphnia sp.	Ecotoxicology and Environmental Safety,4	other: acute 48-h immobilization test ac
7647-14-5	sodium chloride					
	Acute fish toxicity	LC50 5840 mg/l	96 h	Lepomis macrochirus	Study report (1985)	other: ASTM E729
	Acute crustacea toxicity	EC50 4136 mg/l	48 h	Daphnia magna	J. fish. Res. Bd. Canada, 29: 1691-1700.	OECD Guideline 202
	Fish toxicity	NOEC 252 mg/l	33 d	Pimephales promelas	Study report (1985)	OECD Guideline 210
	Crustacea toxicity	NOEC 314 mg/l	21 d	Daphnia pulex	Memorandum of agreement No. 5429, Kentuc	OECD Guideline 211

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
6381-92-6	EDTA Na 2	-4,3

BCF

CAS No	Chemical name	BCF	Species	Source
6381-92-6	EDTA Na 2	ca. 1,8	Lepomis macrochirus	Proc. 3rd. Ann. Symp

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 12 of 14

Further information

Do not allow to enter into surface water or drains.
Harmful effect due to pH shift.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Do not allow to enter into surface water or drains.
Do not mix with other wastes.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 13 of 14

14.4. Packing group:	II	
Hazard label:	8	
Special Provisions:	A3 A803	
Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		851
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		855
IATA-max. quantity - Cargo:		30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Abbreviations and acronyms

Met. Corr: Corrosive to metals

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Eye Dam: Eye damage

STOT RE: Specific target organ toxicity - repeated exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

Reaktionslösung zur Ammoniummessung geeignet für Wasserhärten > 30 °dH

Revision date: 18.01.2024

Product code: 05900

Page 14 of 14

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H373	May cause damage to organs (Respiratory tract, lung) through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)