

according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

UFI: SMDH-H0NQ-S00Q-GFKD

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephoneFor Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,number:Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



#### **Hazard statements**

H290 May be corrosive to metals.

# **Precautionary statements**

P234 Keep only in original packaging.

P390 Absorb spillage to prevent material damage.



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 2 of 10

P406

Store in a corrosion-resistant container with a resistant inner liner.

#### 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Chemical characterization**

Mixtures in aqueous solution

#### Relevant ingredients

CAS No	Chemical name				
	EC No Index No REACH No				
	Classification (Regulation (EC) No 1272/2008)				
7664-93-9	sulphuric acid				
	231-639-5 016-020-00-8 01-2119458838-20				
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318				

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
7664-93-9	231-639-5	sulphuric acid	1 - < 5 %
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### **General information**

No data available

#### After inhalation

Provide fresh air.

# After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

Irritant

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 3 of 10

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

## Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Sulphur oxides

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 4 of 10

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use.

#### Advice on protection against fire and explosion

Usual measures for fire prevention.

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

### Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal, Light metal

The product develops hydrogen in an aqueous solution in contact with metals.

# Further information on storage conditions

Keep container tightly closed.

# 7.3. Specific end use(s)

Laboratory chemicals

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7664-93-9	sulphuric acid					
Worker DNEL, long-term		inhalation	local	0,05 mg/m³		
Worker DNEL, acute		inhalation	local	0,1 mg/m³		



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 5 of 10

#### **PNEC values**

CAS No	Substance			
Environmental	Environmental compartment			
7664-93-9	-93-9 sulphuric acid			
Freshwater		0,003 mg/l		
Marine water		0 mg/l		
Freshwater sediment (		0,002 mg/kg		
Marine sediment		0,002 mg/kg		
Micro-organisms in sewage treatment plants (STP)				

### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

Wear eye/face protection.

## **Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

# **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 6 of 10

Colour: colourless
Odour: odourless
Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

No data available

boiling range:

Flammability: No data available Lower explosion limits: No data available Upper explosion limits: No data available Flash point: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: <1 No data available Viscosity / kinematic:

Viscosity / kinematic:

Water solubility:

No data available

completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

1,0301 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

#### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

Oxidizing

## Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

No data available

No data available

No data available

Solid content:

0

Sublimation point:

Softening point:

No data available

No data available

Pour point:

No data available

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information
Corrosive to metals.

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Corrosive to metals.



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 7 of 10

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Meta

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

#### **Further information**

No data available

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
7664-93-9	sulphuric acid					
	oral	LD50 mg/kg	2140		1969 Sep-Oct; 30(5):	The study was performed as part of a ser

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 8 of 10

#### Additional information on tests

There are no data available on the preparation/mixture itself.

#### **Practical experience**

There are no data available on the preparation/mixture itself.

#### 11.2. Information on other hazards

#### Other information

There are no data available on the preparation/mixture itself.

#### **Further information**

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
7664-93-9	sulphuric acid						
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Discharge into the environment must be avoided.

#### **Further information**

Do not empty into drains.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

## Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 9 of 10

to the industry and process.

# **SECTION 14: Transport information**

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 8 Classification code: C1 **Special Provisions:** 274 Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 80 Tunnel restriction code: Ε

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C1Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

**14.2. UN proper shipping name:** CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223, 274Limited quantity:5 LExcepted quantity:E1EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

### 14.5. Environmental hazards



according to Regulation (EC) No 1907/2006

# Sulfuric acid approx. 0.5 mol/l for photometric determination of silicic acid according to DIN 38405

Revision date: 23.11.2023 Product code: 05924 Page 10 of 10

ENVIRONMENTALLY HAZARDOUS: No

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Information according to Directive

Not subject to 2012/18/EU (SEVESO III)

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

#### **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,12.

#### Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Skin Corr: Skin corrosion Eye Dam: Eye damage

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data

#### Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)