

according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Acetone > 99% pure

REACH Registration Number: 01-2119471330-49-XXXX

CAS No: 67-64-1 Index No: 606-001-00-8 EC No: 200-662-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 2 of 12

Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P240 Ground and bond container and receiving equipment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: C3H6O

Molecular weight: 58,08 g/mol

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|---------|--|----------|----------|----------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 67-64-1 | acetone | | | |
| | 200-662-2 606-001-00-8 01-2119471330-49-XXXX | | | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

| opoomo con | o: =::::::0, ::: :ao | toro una / ri = | | |
|------------|--|---------------------------|----------|--|
| CAS No | EC No | Chemical name | Quantity | |
| | Specific Conc. | Limits, M-factors and ATE | | |
| 67-64-1 | 200-662-2 | acetone | 100 % | |
| | dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg | | | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 3 of 12

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Anaesthetic state

Vomiting, Headache, Dizziness

Gastrointestinal complaints, Corneal opacity.

Has degreasing effect on the skin.

Repeated exposure may cause skin dryness or cracking.

May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2).

Foam.

Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Beware of reignition.

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Additional information

Danger of bursting container.

Use water spray jet to protect personnel and to cool endangered containers.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 4 of 12

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Keep away from food, drink and animal feedingstuffs.

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 5 of 12

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

storage temperature: +5°C - +30°C

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

Protect against: Light

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|---------|-----------|-----|-------|---------|-----------|--------|
| 67-64-1 | Acetone | 500 | 1210 | | TWA (8 h) | |

Biological limit values

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|---------|-----------|-----------|---------|---------------|---------------|
| 67-64-1 | Acetone | Acetone | 50 mg/L | Urine | End of shift |

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|---------------|----------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| 67-64-1 | acetone | | | |
| Worker DNEL, | long-term | inhalation | systemic | 1210 mg/m³ |
| Worker DNEL, | acute | inhalation | local | 2420 mg/m³ |
| Worker DNEL, | long-term | dermal | systemic | 186 mg/kg bw/day |
| Consumer DNE | EL, long-term | inhalation | systemic | 200 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 62 mg/kg bw/day |
| Consumer DNE | EL, long-term | oral | systemic | 62 mg/kg bw/day |



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 6 of 12

PNEC values

| CAS No | Substance | |
|--|----------------|------------|
| Environment | al compartment | Value |
| 67-64-1 | acetone | |
| Freshwater | | 10,6 mg/l |
| Freshwater (intermittent releases) | | 21 mg/l |
| Marine water | | 1,06 mg/l |
| Freshwater sediment | | 30,4 mg/kg |
| Marine sediment | | 3,04 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 100 mg/l |
| Soil | | 29,5 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butvl caoutchouc (butvl rubber) 0.3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: AX



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 7 of 12

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: fruity

Melting point/freezing point: -95,4 °C
Boiling point or initial boiling point and 56,2 °C

boiling range:

Flammability: not applicable Lower explosion limits: 2.15 vol. % Upper explosion limits: 13 vol. % <-20 °C Flash point: 465 °C Auto-ignition temperature: Decomposition temperature: No data available pH-Value (at 20 °C): 5-6 (395 g/l) Viscosity / kinematic: No data available Water solubility: very soluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: log Pow: -0,23 Vapour pressure: 240 hPa

(at 20 °C)

Vapour pressure:No data availableDensity:0,79 g/cm³Bulk density:No data availableRelative vapour density:No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

100
Solid content:

No data available
No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 8 of 12

Viscosity / dynamic:

0,32 mPa·s

(at 20 °C) Flow time:

No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

10.2. Chemical stability

Protect against:

Light

Air

10.3. Possibility of hazardous reactions

Ignition hazard:

Fluorine, Oxidising agent, strong; chromium trioxide

Reducing agent, strong; Nitric acid

Danger of explosion:

Chloroform, peroxides, for example hydrogen peroxide

Exothermic reaction with:

Bromine, Alkali metals

Hydrogen halide, Sulphur dichloride

10.4. Conditions to avoid

Heat

Light

Air

10.5. Incompatible materials

Rubber articles

Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 9 of 12

| CAS No | Chemical name | | | | | |
|---------|----------------|---------------|--------|---------|--|--|
| | Exposure route | Dose | | Species | Source | Method |
| 67-64-1 | acetone | | | | | |
| | oral | LD50 mg/kg | 5800 | Rat | J Toxicol Environ Health 15: 609-621 (19 | Undiluted acetone applied to female rats |
| | dermal | LD50 mg/kg | > 7426 | Rabbit | Toxicol Appl Pharmacol 7: 559-565. (1965 | other: Code of federal regulations: 21 C |

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Has degreasing effect on the skin.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

No data available

Further information

Irritant, Dizziness, Anaesthetic state

Vomiting, Headache, Dizziness

Gastrointestinal complaints, Corneal opacity.

Has degreasing effect on the skin.

Repeated exposure may cause skin dryness or cracking.

May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 10 of 12

| CAS No | Chemical name | | | | | | |
|---------|--------------------------|------------------|-------|-----------|--|--|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 67-64-1 | acetone | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 8120 | 96 h | Pimephales promelas | Publication (1984) | OECD Guideline 203 |
| | Acute crustacea toxicity | EC50 mg/l | 8800 | 48 h | Daphnia pulex | Publication (1978) | The toxicity of acetone towards daphnids |
| | Crustacea toxicity | NOEC mg/l | 2212 | 28 d | Daphnia magna | Arch Environm Contam Toxicol 12: 305-310 | Study conducted comparable to OECD 211 w |
| | Acute bacteria toxicity | EC50 mg/l () | 61150 | | activated sludge of a predominantly domestic sewag | Water Res 26: 887-892 (1992) | ISO 8192 |

12.2. Persistence and degradability

91 %; 28 d

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|---------------|---------|
| 67-64-1 | acetone | -0,23 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|---------|---------------|-----|---------|----------------------|
| 67-64-1 | acetone | 3 | | Unpublished calculat |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

| | Acetone > 99% pure | |
|---------------------------|---------------------|---------------|
| Revision date: 04.03.2025 | Product code: 07020 | Page 11 of 12 |

Land transport (ADR/RID)

| 14.1. UN number or ID number: | UN 1090 |
|----------------------------------|---------|
| 14.2. UN proper shipping name: | ACETONE |
| 14.3 Transport hazard class(es): | 3 |

П 14.4. Packing group: 3 Hazard label: Classification code: F1 Limited quantity: 1 L Excepted quantity: E2 Transport category: 2 Hazard No: 33 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 109014.2. UN proper shipping name:ACETONE

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1090
14.2. UN proper shipping name: ACETONE

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1090 **14.2. UN proper shipping name:** ACETONE

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information



according to Regulation (EC) No 1907/2006

Acetone > 99% pure

Revision date: 04.03.2025 Product code: 07020 Page 12 of 12

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

Additional information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12,15.

Abbreviations and acronyms

Flam. Liq: Flammable liquid Eve Irrit: Eve irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.