

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.

Revision date: 14.12.2021

Product code: 07045

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.

REACH Registration Number: 01-2119471310-51-XXXX  
CAS No: 108-88-3  
Index No: 601-021-00-3  
EC No: 203-625-9

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals  
Industrial uses: Uses of substances as such or in preparations at industrial sites  
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
Telefax: 0203/5194-290  
e-mail: info@berndkraft.de  
Contact person: Abteilung Produktsicherheit  
Telephone: 0203/5194-107/117  
e-mail: produktsicherheit@berndkraft.de  
Internet: www.berndkraft.de  
Responsible Department: Abteilung Produktsicherheit

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

No data available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Repr. 2; H361d  
Skin Irrit. 2; H315  
STOT SE 3; H336  
STOT RE 2; H373  
Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Signal word: Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.

Revision date: 14.12.2021

Product code: 07045

Page 2 of 13

#### Pictograms:



#### Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P314	Get medical advice/attention if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

#### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

#### Chemical characterization

Hydrocarbons, aromatic

Sum formula:	C <sub>7</sub> H <sub>8</sub>
Molecular weight:	92,14 g/mol

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			100 %
	203-625-9	601-021-00-3	01-2119471310-51-XXXX	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	100 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 3 of 13

**General information**

No data available

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant, Headache  
Dizziness, Dizziness  
Vomiting, Inebriation  
Spasms, Circulatory collapse  
Respiratory complaints, Dyspnoea  
Unconsciousness

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Foam.  
Extinguishing powder  
Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Beware of reignition.  
Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide (CO<sub>2</sub>), Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 4 of 13

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up**

**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 5 of 13

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.  
Draw up and observe skin protection programme.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.  
Store in a place accessible by authorized persons only.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.

**Further information on storage conditions**

Keep cool. Protect from sunlight.  
storage temperature: +5°C - +30°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 6 of 13

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
108-88-3	toluene		
Worker DNEL, long-term	inhalation	systemic	192 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	384 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	192 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	384 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	226 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	226 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
108-88-3	toluene	
Freshwater	0,68 mg/l	
Freshwater (intermittent releases)	0,68 mg/l	
Marine water	0,68 mg/l	
Freshwater sediment	16,39 mg/kg	
Marine sediment	16,39 mg/kg	
Micro-organisms in sewage treatment plants (STP)	13,61 mg/l	
Soil	2,89 mg/kg	

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 7 of 13

By short-term hand contact  
Trade name/designation: KCL 890 Vitoject®  
Suitable material: FKM (fluoro rubber) 0,7 mm  
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation  
Filtering device with filter or ventilator filtering device of type: A

**Environmental exposure controls**

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: clear  
Odour: like: Hydrocarbons, aromatic  
Odour threshold: No data available

**Changes in the physical state**

Melting point/freezing point: -95 °C  
Boiling point or initial boiling point and boiling range: 110,6 °C  
Sublimation point: No data available  
Softening point: No data available  
Pour point: No data available  
:  
Flash point: 4,4 °C

**Flammability**

Solid/liquid: No data available  
Gas: No data available

**Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits: 1,1 vol. %  
Upper explosion limits: 7,1 vol. %  
Auto-ignition temperature: 480 °C

**Self-ignition temperature**

Solid: No data available  
Gas: No data available

Decomposition temperature: No data available

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 8 of 13

pH-Value:	No data available
Viscosity / dynamic: (at 20 °C)	0,6 mPa·s
Viscosity / kinematic: (at 20 °C)	0,7 mm <sup>2</sup> /s
Flow time:	No data available
Water solubility: (at 20 °C)	0,52 g/L
<b>Solubility in other solvents</b>	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 2,65
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	29,3 hPa
Vapour pressure: (at 50 °C)	123 hPa
Density:	0,87 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Sustaining combustion:	Sustaining combustion
Oxidizing properties	
No data available	

**Other safety characteristics**

Solvent separation test:	No data available
Solvent content:	100,00 %
Solid content:	0
Evaporation rate:	No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent  
Nitric acid  
Acetic acid  
Strong acid  
silver



**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 9 of 13

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles  
Rubber articles

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

**Acute toxicity**

Based on available data, the classification criteria are not met.  
Irritation to respiratory tract

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

**Irritation and corrosivity**

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.  
Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (toluene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (toluene)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (toluene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 10 of 13

**Practical experience**

No data available

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Further information**

Irritant, Headache  
Dizziness, Dizziness  
Vomiting, Inebriation  
Spasms, Circulatory collapse  
Respiratory complaints, Dyspnoea  
Unconsciousness

**SECTION 12: Ecological information**

**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003

**12.2. Persistence and degradability**

69 - 81 %; 5 d; aerob  
APHA NO. 219  
(ECHA)

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 11 of 13

**BCF**

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

**12.4. Mobility in soil**

log Koc: 2,15 (MSDS)

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.  
No data available

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.  
No data available

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.  
Avoid release to the environment.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not mix with other wastes.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1294
<b>14.2. UN proper shipping name:</b>	TOLUENE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1294
<b>14.2. UN proper shipping name:</b>	TOLUENE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L

**Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.**

Revision date: 14.12.2021

Product code: 07045

Page 12 of 13

Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1294  
**14.2. UN proper shipping name:** TOLUENE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1294  
**14.2. UN proper shipping name:** TOLUENE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 40, Entry 48

2010/75/EU (VOC): 100 % (870 g/l)  
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,7,8,9,10,11,12,13,14,15.

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene > 99.7 % for analysis, ACS, Reag. Ph. Eur.

Revision date: 14.12.2021

Product code: 07045

Page 13 of 13

H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.