

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Petroleum benzine 30/40 °C pure

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

**1.4. Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

**Further Information**

This product is a mixture. REACH Registration Number see section 3.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No 1272/2008**

Flam. Liq. 1; H224

Asp. Tox. 1; H304

STOT SE 3; H336

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

**Regulation (EC) No 1272/2008**

**Hazard components for labelling**

pentane

isopentane

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H224

Extremely flammable liquid and vapour.

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 2 of 12

H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P403+P235 Store in a well-ventilated place. Keep cool.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
109-66-0	pentane			75 - < 80 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
78-78-4	isopentane			25 - < 30 %
	201-142-8	601-006-00-1	01-2119475602-38	
	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H224 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
109-66-0	203-692-4	pentane	75 - < 80 %
	inhalation: LC50 = > 25,3 mg/l (vapours); oral: LD50 = > 5000 mg/kg		
78-78-4	201-142-8	isopentane	25 - < 30 %
	inhalation: LC50 = > 25,3 mg/l (vapours); oral: LD50 = > 2000 mg/kg		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

No data available

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 3 of 12

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant  
Vapours may cause drowsiness and dizziness.  
Gastrointestinal complaints

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>)  
Foam  
Extinguishing powder  
Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.  
Beware of reignition.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 4 of 12

**For non-emergency personnel**

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

- Do not allow to enter into surface water or drains.
- The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
- Danger of explosion

**6.3. Methods and material for containment and cleaning up**

**For containment**

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

- Avoid exposure - obtain special instructions before use.
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Provide adequate ventilation. Do not breathe vapour.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

**Further information on handling**

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 5 of 12

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Further information on storage conditions**

Keep container tightly closed and dry.

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
78-78-4	iso-Pentane	1000	-		TWA (8 h)	
109-66-0	n-Pentane	1000	-		TWA (8 h)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
109-66-0	pentane			
	Worker DNEL, long-term	inhalation	systemic	3000 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	432 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	643 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	214 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	214 mg/kg bw/day
78-78-4	isopentane			
	Worker DNEL, long-term	inhalation	systemic	3000 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	432 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	643 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	214 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	214 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
109-66-0	pentane	
	Freshwater	0,23 mg/l
	Freshwater (intermittent releases)	0,88 mg/l
	Marine water	0,23 mg/l
	Freshwater sediment	1,2 mg/kg
	Marine sediment	1,2 mg/kg
	Micro-organisms in sewage treatment plants (STP)	3,6 mg/l
	Soil	0,55 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 6 of 12

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

- goggles
- Face protection umbrella

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

- Trade name/designation: KCL 890 Vitoject®
- Suitable material: FKM (fluoro rubber) 0,7 mm
- Wearing time with permanent contact: > 480 min

By short-term hand contact

- Trade name/designation: KCL 730 Camatril® Velours
- Suitable material: NBR (Nitrile rubber) 0,4 mm
- Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

- Take off immediately all contaminated clothing and wash it before reuse.
- Wear fire resistant or flame retardant clothing.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Draw up and observe skin protection programme.

**Respiratory protection**

- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Filtering device with filter or ventilator filtering device of type: AX

**Environmental exposure controls**

- Do not allow to enter into surface water or drains.
- Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
- Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Gasoline

**Changes in the physical state**

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	30-40 °C
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
:	No data available
Flash point:	-56 °C

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 7 of 12

**Flammability**

Solid/liquid: No data available  
Gas: No data available

**Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits: 1,3 vol. %  
Upper explosion limits: 7,8 vol. %  
Auto-ignition temperature: 245 °C

**Self-ignition temperature**

Solid: No data available  
Gas: No data available

Decomposition temperature: No data available

pH-Value: No data available

Viscosity / dynamic: No data available

Viscosity / kinematic: No data available

Flow time: No data available

Water solubility: No data available

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: No data available

Vapour pressure: No data available

Density: 0,628 g/cm<sup>3</sup>

Bulk density: No data available

Relative vapour density: No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Sustaining combustion: Sustaining combustion

Oxidizing properties

No data available

**Other safety characteristics**

Solvent separation test: No data available

Solvent content: 100%

Solid content: No data available

Evaporation rate: No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 8 of 12

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles  
Rubber articles

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
109-66-0	pentane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 423
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat	Secondary source (1993)	OECD Guideline 403
78-78-4	isopentane				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat	Secondary source (1993)	OECD Guideline 403

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (pentane; isopentane)  
Organs affected: central nervous system

**STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available



**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 9 of 12

**11.2. Information on other hazards**

**Other information**

Avoid exposure - obtain special instructions before use.

**Further information**

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
109-66-0	pentane					
	Acute fish toxicity	LC50 mg/l	4,26	96 h	Oncorhynchus mykiss	Study report (1997) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	20,33	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 mg/l	48,11	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Fish toxicity	NOEC mg/l	6,165	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	10,76	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
78-78-4	isopentane					
	Acute fish toxicity	LC50 mg/l	4,26	96 h	Oncorhynchus mykiss	Study report OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	25,12	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 mg/l	59,44	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Fish toxicity	NOEC mg/l	7,618	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	13,29	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009) The aquatic toxicity was estimated by a

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
109-66-0	pentane	3,45
78-78-4	isopentane	4

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 10 of 12

**BCF**

CAS No	Chemical name	BCF	Species	Source
109-66-0	pentane	171	Pimephales promelas	QSAR in Environmenta
78-78-4	isopentane	171	Pimephales promelas	QSAR in Environmenta

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

Avoid release to the environment.

**Further information**

No data available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1265
<b>14.2. UN proper shipping name:</b>	PENTANES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Classification code:	F1
Limited quantity:	0
Excepted quantity:	E3
Transport category:	1
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1265
<b>14.2. UN proper shipping name:</b>	Pentanes
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Classification code:	F1
Limited quantity:	0
Excepted quantity:	E3

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 11 of 12

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1265
<b>14.2. UN proper shipping name:</b>	PENTANES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Special Provisions:	-
Limited quantity:	0
Excepted quantity:	E3
EmS:	F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1265
<b>14.2. UN proper shipping name:</b>	PENTANES liquid
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Limited quantity Passenger:	Forbidden
Passenger LQ:	Forbidden
Excepted quantity:	E3
IATA-packing instructions - Passenger:	351
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	361
IATA-max. quantity - Cargo:	30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	pentane

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):	
Entry 3, Entry 40	
Information according to 2012/18/EU (SEVESO III):	P5a FLAMMABLE LIQUIDS
Additional information:	E2

**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,9,14.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petroleum benzine 30/40 °C pure**

Revision date: 16.03.2021

Product code: 07142

Page 12 of 12

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 1; H224	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*