

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

n-Hexane > 95 % pure

Substance name: n-hexane

REACH Registration Number: 01-2119480412-44-XXXX

CAS No: 110-54-3 Index No: 601-037-00-0 EC No: 203-777-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

<u>1.4. Emergency telephone</u> For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Repr. 2; H361f Skin Irrit. 2; H315 STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008 Signal word: Danger



according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 2 of 12

Pictograms:









Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361f Suspected of damaging fertility.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs (central nervous system) through prolonged or repeated

exposure if inhaled.

H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment.

P273 Avoid release to the environment.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P314 Get medical advice/attention if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: CH3(CH2)4CH3
Molecular weight: 86,18 g/mol

Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	EC No Index No REACH No			
	Classification (Regulation	Classification (Regulation (EC) No 1272/2008)			
110-54-3	n-hexane	n-hexane			
	203-777-6	601-037-00-0	01-2119480412-44-XXXX		
		Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
110-54-3	203-777-6	n-hexane	100 %	
	inhalation: LC50 = 73860 mg/l (vapours); dermal: LD50 = > 2000 mg/kg STOT RE 2; H373: >= 5 - 100			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Vapours may cause drowsiness and dizziness.

Narcotic effects

Gastrointestinal complaints

Corneal opacity.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 4 of 12

Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour.



according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 5 of 12

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed and dry. Keep cool. Protect from sunlight. storage temperature +5°C - +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
110-54-3	n-Hexane	20	72		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
110-54-3	Hexane	2,5-Hexanedion	0.4 mg/L		End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance					
DNEL type	DNEL type		Effect	Value		
110-54-3	n-hexane					
Worker DNEL,	long-term	inhalation	systemic	75 mg/m³		
Worker DNEL,	long-term	dermal	systemic	11 mg/kg bw/day		
Consumer DNE	EL, long-term	inhalation	systemic	16 mg/m³		
Consumer DNE	EL, long-term	dermal	systemic	5,3 mg/kg bw/day		
Consumer DNE	EL, long-term	oral	systemic	4 mg/kg bw/day		

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 6 of 12

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Colour:

Odour:

Uiquid

colourless

like: Gasoline

No data available



Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 7 of 12

-94,3 °C Melting point/freezing point: Boiling point or initial boiling point and 69 °C

boiling range:

Flammability: No data available Lower explosion limits: 1 vol. % Upper explosion limits: 8.1 vol. % -22 °C Flash point: 240 °C

Auto-ignition temperature: Decomposition temperature: No data available pH-Value: No data available

Viscosity / kinematic: 0.5 mm²/s

(at 20 °C)

Water solubility: 0.0095 q/l

(at 20 °C)

Solubility in other solvents No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: log Pow: 4.11 Dispersion stability: No data available Vapour pressure: 160 hPa

(at 20 °C)

Vapour pressure: No data available 0,66 g/cm3 Density: Relative density: No data available No data available Bulk density: Relative vapour density: No data available Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available Gas: No data available

Oxidizing properties No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: 100% Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point: No data available No data available Viscosity / dynamic:

0,326 mPa·s

(at 20 °C)

Flow time: No data available

Further Information

No data available



according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 8 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

NOx

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

May cause respiratory irritation.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Resorption (dermal)

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
110-54-3	n-hexane	n-hexane						
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)			
	inhalation (4 h) vapour	LC50 mg/l	73860	Rat	Industrial Medicine, Vol. 39, No. 5, May	OECD Guideline 403		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility. (n-hexane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 9 of 12

STOT-single exposure

May cause drowsiness or dizziness. (n-hexane) Organs affected: central nervous system

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (n-hexane)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Avoid exposure - obtain special instructions before use.

Further information

Irritant

Vapours may cause drowsiness and dizziness.

Narcotic effects

Gastrointestinal complaints

Corneal opacity.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
110-54-3	n-hexane						
	Acute algae toxicity	ErC50 mg/l	9,285	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 mg/l	21,85	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC	2,8 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	4,888	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

log Pow: 4,11



Revision date: 17.04.2025

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure Product code: 07151 Page 10 of 12

Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
110-54-3	n-hexane	4

BCF

CAS No	Chemical name	BCF	Species	Source
110-54-3	n-hexane	501,187	Pimephales promelas	QSAR in Environmenta

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

UN 1208

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1. UN number or ID number:

Land transport (ADR/RID)

14.2. UN proper shipping name:	HEXANES
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1208
14.2. UN proper shipping name:	HEXANES
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure					
Revision date: 17.04.2025	Product code: 07151	Page 11 of 12			
Classification code:	F1				
Limited quantity:	1 L				
Excepted quantity:	E2				
Marine transport (IMDG)					
14.1. UN number or ID number:	UN 1208				
14.2. UN proper shipping name:	HEXANES				
14.3. Transport hazard class(es):	3				
14.4. Packing group:	II				
Hazard label:	3				
Marine pollutant:	P				
Special Provisions:	-				
Limited quantity:	1 L				
Excepted quantity:	E2				
EmS:	F-E, S-D				
Air transport (ICAO-TI/IATA-DGR)					
14.1. UN number or ID number:	UN 1208				
14.2. UN proper shipping name:	HEXANES				
14.3. Transport hazard class(es):	3				
14.4. Packing group:	II				
Hazard label:	3				
Limited quantity Passenger:	1 L				
Passenger LQ:	Y341				
Excepted quantity:	E2				
IATA-packing instructions - Passenger:	353				
IATA-max. quantity - Passenger:	5 L				
IATA-packing instructions - Cargo:	364				
IATA-max. quantity - Cargo:	60 L				
14.5. Environmental hazards					
ENVIRONMENTALLY HAZARDOUS:	Yes				
Danger releasing substance:	n-hexane				

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

E2 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,8,11,15.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Hexane > 95 % pure

Revision date: 17.04.2025 Product code: 07151 Page 12 of 12

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

H373 May cause damage to organs (central nervous system) through prolonged or repeated

exposure if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.