

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TAN-solvent mixture for determination of the neutralization number

UFI:

RV25-41SE-V00A-CYKY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
<u>1.4. Emergency telephone</u> number:	Exposure, or Accident Call CHEMTR	ous Goods] Incidents Spill, Leak, Fire, REC Day or Night Within USA and Canada: anada: +1 703-741-5970 (collect calls

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene

propan-2-ol; isopropyl alcohol; isopropanol Signal word: Danger



TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Pictograms:

Product code: 13032

Page 2 of 13



Hazard statements

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.

Precautionary statements

	actorially oraconnorm	
P2	10	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P2	260	Do not breathe mist/vapours/spray.
P2	80	Wear protective gloves/protective clothing/eye protection/face protection.
P3	01+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P3	31	Do NOT induce vomiting.
P4	03+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (Regulation			
108-88-3	toluene			50 - < 55 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Ski H361d H315 H336 H373			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			45 - < 50 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	EC No Chemical name			
	Specific Conc.	Limits, M-factors and ATE			
108-88-3	203-625-9	toluene	50 - < 55 %		
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg				

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures



TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 3 of 13

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage, Headache Dizziness, Dizziness Vomiting, Inebriation Spasms, Circulatory collapse Respiratory complaints, Dyspnoea Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide Vapours are heavier than air, spread along floors and form explosive mixtures with air. Beware of reignition. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely.



an analyti**chem** brand

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 4 of 13

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 5 of 13

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Draw up and observe skin protection programme.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L		Prior to last shift of workweek
67-63-0	2-Propanol	Acetone	40 mg/L		End of shift at end of workweek



according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 6 of 13

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
108-88-3	toluene					
Worker DNEL,	, long-term	inhalation	systemic	192 mg/m³		
Worker DNEL,	, acute	inhalation	systemic	384 mg/m³		
Worker DNEL,	, long-term	inhalation	local	192 mg/m³		
Worker DNEL,	, acute	inhalation	local	384 mg/m ³		
Worker DNEL,	, long-term	dermal	systemic	384 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	56,5 mg/m³		
Consumer DN	EL, acute	inhalation	systemic	226 mg/m ³		
Consumer DN	EL, long-term	inhalation	local	56,5 mg/m³		
Consumer DN	EL, acute	inhalation	local	226 mg/m ³		
Consumer DN	EL, long-term	dermal	systemic	226 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	8,13 mg/kg bw/day		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
Worker DNEL,	, long-term	inhalation	systemic	500 mg/m³		
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	89 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	319 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	26 mg/kg bw/day		

PNEC values

CAS No	Substance				
Environment	Environmental compartment				
108-88-3	toluene				
Freshwater		0,68 mg/l			
Freshwater (intermittent releases)	0,68 mg/l			
Marine water	r	0,68 mg/l			
Freshwater s	sediment	16,39 mg/kg			
Marine sedin	nent	16,39 mg/kg			
Micro-organia	13,61 mg/l				
Soil		2,89 mg/kg			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
Freshwater		140,9 mg/l			
Freshwater (intermittent releases)	140,9 mg/l			
Marine water	ſ	140,9 mg/l			
Freshwater s	sediment	552 mg/kg			
Marine sedin	nent	552 mg/kg			
Secondary p	160 mg/kg				
Micro-organisms in sewage treatment plants (STP)					
Soil	Soil 28 mg/l				

8.2. Exposure controls





an analyti**chem** brand

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 7 of 13

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 480 min

By short-term hand contact Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	Liquid colourless characteristic No data available	
Melting point/freezing point: Boiling point or initial boiling point and boiling range:		No data available 82 °C
Flammability: Lower explosion limits: Upper explosion limits:		No data available No data available No data available



N-solvent mixture for determination of the neutralization numb

TAN-solvent mixture	for determination of the neutralization number	
Revision date: 13.03.2024	Product code: 13032	Page 8 of 13
Flash point:	4 °C	
Auto-ignition temperature:	No data available	
Decomposition temperature:	No data available	
pH-Value:	No data available	
Viscosity / kinematic:	No data available	
Water solubility:	No data available	
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:	No data available	
Vapour pressure:	No data available	
Vapour pressure:	No data available	
Density:	0,8269 g/cm³	
Bulk density:	No data available	
Relative vapour density:	No data available	
9.2. Other information		
Information with regard to physical hazard cla	asses	
Explosive properties		
Vapours are heavier than air, spread along	floors and form explosive mixtures with air.	
Sustaining combustion:	Sustaining combustion	
Self-ignition temperature		
Solid:	No data available	
Gas:	No data available	
Oxidizing properties		
No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point:	No data available	
	No data available	
Viscosity / dynamic:	No data available	
Flow time:	No data available	
Further Information		
No data available		
CECTION 40. Ctability and reactivity		

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent Nitric acid Acetic acid Strong acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 9 of 13

10.5. Incompatible materials

Plastic articles Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Exposure route Dose Species				Method	
108-88-3	toluene						
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1	
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o	
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene; propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 10 of 13

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant — skin irritation and eye damage, Headache Dizziness, Dizziness Vomiting, Inebriation Spasms, Circulatory collapse Respiratory complaints, Dyspnoea Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
108-88-3	toluene							
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other	
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACh Registration Dossier	Method: other	
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th	
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other	
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol							
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
BCF		

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).



TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 11 of 13

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol;		
	isopropanol)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	ll		
Hazard label:	3		
Classification code:	F1		
Special Provisions:	274 601 640D		
Limited quantity:	1 L		
Excepted quantity:	E2		
Transport category:	2		
Hazard No:	33		
Tunnel restriction code:	D/E		
Inland waterways transport (ADN)			
14.1. UN number or ID number:	UN 1993		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol;		
	isopropanol)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
Classification code:	F1		
Special Provisions:	274 601 640D		
Limited quantity:	1 L		
Excepted quantity:	E2		



TAN-solvent mixture for determination of the neutralization number

TAN-solvent mixture for determination of the neutralization number				
Revision date: 13.03.2024	Product code: 13032	Page 12 of 13		
Marine transport (IMDG)				
14.1. UN number or ID number:	UN 1993			
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)			
14.3. Transport hazard class(es):	3			
14.4. Packing group:	II			
Hazard label:	3			
Special Provisions:	274			
Limited quantity:	1 L			
Excepted quantity:	E2			
EmS:	F-E, S-E			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	UN 1993			
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)			
14.3. Transport hazard class(es):	3			
14.4. Packing group:	II			
Hazard label:	3			
Special Provisions:	A3			
Limited quantity Passenger:	1 L			
Passenger LQ:	Y341			
Excepted quantity:	E2			
IATA-packing instructions - Passenger:	353			
IATA-max. quantity - Passenger:	5 L			
IATA-packing instructions - Cargo:	364			
IATA-max. quantity - Cargo:	60 L			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture			
EU regulatory information				
Restrictions on use (REACH, annex XVII):				
Entry 3, Entry 40, Entry 48				
Information according to Directive	P5c FLAMMABLE LIQUIDS			
2012/18/EU (SEVESO III):	F3C FLAMIMABLE LIQUIDS			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve			
	work protection guideline' (94/33/EC). Observe employment restriction	15		
	under the Maternity Protection Directive (92/85/EEC) for expectant or			
	nursing mothers. Observe employment restrictions for women of			
Water hazard class (D):	child-bearing age. 3 - highly hazardous to water			
	5 - mymy nazaruous to water			
SECTION 16: Other information				

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.



according to Regulation (EC) No 1907/2006

TAN-solvent mixture for determination of the neutralization number

Revision date: 13.03.2024

Product code: 13032

Page 13 of 13

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)