

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

UFI: 6P27-J1R8-D00N-MS5E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Asp. Tox. 1; H304
Skin Corr. 1B; H314
Eye Dam. 1; H318
Repr. 2; H361d
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

toluene
acetic acid
acetone

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 2 of 15

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
108-88-3	toluene			55 - < 60 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
64-19-7	acetic acid			30 - < 35 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A; H226 H314			
67-64-1	acetone			5 - < 10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-88-3	203-625-9	toluene	55 - < 60 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
64-19-7	200-580-7	acetic acid	30 - < 35 %
		inhalation: LC50 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	
67-64-1	200-662-2	acetone	5 - < 10 %
		dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, corrosive

Headache, Dizziness

Dizziness, Vomiting

Inebriation, Spasms

Circulatory collapse, Respiratory complaints

Dyspnoea, Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.

Extinguishing powder

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 4 of 15

Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Beware of reignition.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 5 of 15

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- Draw up and observe skin protection programme.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Store in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

- national regulations

Further information on storage conditions

- Keep cool. Protect from sunlight.

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 6 of 15

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	WEL
		20	50		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
108-88-3	toluene			
	Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
	Worker DNEL, acute	inhalation	systemic	384 mg/m ³
	Worker DNEL, long-term	inhalation	local	192 mg/m ³
	Worker DNEL, acute	inhalation	local	384 mg/m ³
	Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
	Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
	Consumer DNEL, acute	inhalation	local	226 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
64-19-7	acetic acid			
	Worker DNEL, long-term	inhalation	local	25 mg/m ³
	Worker DNEL, acute	inhalation	local	25 mg/m ³
	Consumer DNEL, long-term	inhalation	local	25 mg/m ³
	Consumer DNEL, acute	inhalation	local	25 mg/m ³
67-64-1	acetone			
	Worker DNEL, long-term	inhalation	systemic	1210 mg/m ³
	Worker DNEL, acute	inhalation	local	2420 mg/m ³
	Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	200 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 7 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		Value
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg
67-64-1	acetone	
Freshwater		10,6 mg/l
Freshwater (intermittent releases)		21 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 8 of 15

By short-term hand contact
Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wear fire resistant or flame retardant clothing.
Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Hydrocarbons, aromatic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		55 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		11 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
	No data available	
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,9152 g/cm ³
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 9 of 15

Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Nitric acid

Acetic acid

Strong acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 10 of 15

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 33,15 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 mg/kg 5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg > 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
64-19-7	acetic acid				
	oral	LD50 mg/kg 3310	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194)	The sodium salt of acetic acid was admin
	inhalation (4 h) vapour	LC50 11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403
67-64-1	acetone				
	oral	LD50 mg/kg 5800	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 mg/kg > 7426	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 11 of 15

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant, corrosive

Headache, Dizziness

Dizziness, Vomiting

Inebriation, Spasms

Circulatory collapse, Respiratory complaints

Dyspnoea, Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 12 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l > 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 mg/l 11,5	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l 1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l > 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l 0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
64-19-7	acetic acid					
	Acute fish toxicity	LC50 mg/l > 1000	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 mg/l > 1000	72 h	Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 mg/l > 1000	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l 8120	96 h	Pimephales promelas	Publication (1984)	OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l 8800	48 h	Daphnia pulex	Publication (1978)	The toxicity of acetone towards daphnids
	Crustacea toxicity	NOEC mg/l 2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310	Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	EC50 mg/l () 61150	0,5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992)	ISO 8192

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-19-7	acetic acid	-0,17
67-64-1	acetone	-0,23

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 13 of 15

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch
67-64-1	acetone	3		Unpublished calculat

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.
Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (toluene, acetic acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (toluene, acetic acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 14 of 15

Hazard label: 3+8
Classification code: FC
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (toluene, acetic acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (toluene, acetic acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8
Special Provisions: A3
Limited quantity Passenger: 0.5 L
Passenger LQ: Y340
Excepted quantity: E2
IATA-packing instructions - Passenger: 352
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 363
IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Safety Data Sheet

according to UK REACH Regulation

Acetic acid / toluene / acetone mixture mixed 3 : 6 : 1 volumetrically suitable for determination of

Revision date: 13.03.2024

Product code: 13752

Page 15 of 15

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Abbreviations and acronyms

Flam. Liq: Flammable liquids
 Asp. Tox: Aspiration hazard
 Skin Corr: Skin corrosion
 Skin Irrit: Skin irritation
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 Repr: Reproductive toxicity
 STOT SE: Specific target organ toxicity - single exposure
 STOT RE: Specific target organ toxicity - repeated exposure
 Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)