

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 1 of 15

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Macro etching solution according to Fry suitable for the visualization of lines of action of the for

UFI: D7X7-Y10X-100K-087C

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

This product is a mixture. REACH Registration Number see section 3.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Flam. Liq. 3; H226

Skin Irrit. 2; H315

Eye Dam. 1; H318

STOT SE 3; H335

Aquatic Acute 1; H400

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

Hydrochloric acid

Kupfer-II-chlorid-2-hydrat

Signal word: Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 2 of 15

#### Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixtures in aqueous solution

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol			15 - < 20 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7647-01-0	Hydrochloric acid			15 - < 20 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Skin Corr. 1B, STOT SE 3; H314 H335			
10125-13-0	Kupfer-II-chlorid-2-hydrat			1 - < 5 %
			01-2119970306-36	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H315 H318 H400 H411			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 3 of 15

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	15 - < 20 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7647-01-0	231-595-7	Hydrochloric acid	15 - < 20 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
10125-13-0		Kupfer-II-chlorid-2-hydrat	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 584 mg/kg Aquatic Acute 1; H400: M=10	

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

No data available

##### After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

##### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

##### After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 4 of 15

Hydrogen chloride (HCl)  
Metal oxide smoke, toxic  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.  
Corrosive to metals.

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion  
Do not allow uncontrolled discharge of product into the environment. Danger of explosion

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 5 of 15

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

##### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

##### **Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations.

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material:

Metal.

##### **Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.  
national regulations

##### **Further information on storage conditions**

Keep cool. Protect from sunlight.

#### **7.3. Specific end use(s)**

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 6 of 15

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, long-term		inhalation	systemic	950 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
7647-01-0	Hydrochloric acid			
Worker DNEL, long-term		inhalation	local	8 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	15 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	8 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	15 mg/m <sup>3</sup>

#### PNEC values

CAS No	Substance	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
10125-13-0	Kupfer-II-chlorid-2-hydrat	
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater sediment		87 mg/kg
Marine sediment		676 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,23 mg/l
Soil		65 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 7 of 15

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 30 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	green
Odour:	like: Alcohol
Odour threshold:	No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 8 of 15

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	38 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	not determined
pH-Value:	0
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,0782 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

###### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

###### Sustaining combustion:

Sustaining combustion

###### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

###### Oxidizing properties

Not oxidising.

##### Other safety characteristics

###### Evaporation rate:

not determined

###### Solvent separation test:

No data available

###### Solid content:

not determined

###### Sublimation point:

No data available

###### Softening point:

No data available

###### Pour point:

No data available

###### Viscosity / dynamic:

No data available

###### Flow time:

No data available

##### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Corrosive to metals. Flammable.

In case of warming: Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.



**Macro etching solution according to Fry suitable for the visualization of lines of action of the  
for**

Revision date: 02.01.2025

Product code: 14061

Page 9 of 15

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Heat

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Keep away from: Metal.

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 mg/kg	10470	Rat	Study report (1976) OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980) OECD Guideline 403
10125-13-0	Kupfer-II-chlorid-2-hydrat				
	oral	LD50 mg/kg	584	Rat	Publication (1991) The test material was administered to gr
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2003) OECD Guideline 402

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Hydrochloric acid)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 10 of 15

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### Practical experience

There are no data available on the mixture itself.

#### 11.2. Information on other hazards

##### Other information

There are no data available on the mixture itself.

##### Further information

There are no data available on the mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

**Macro etching solution according to Fry suitable for the visualization of lines of action of the  
for**

Revision date: 02.01.2025

Product code: 14061

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50 862 mg/l	96 h	Leuciscus idus		
10125-13-0	Kupfer-II-chlorid-2-hydrat					
	Acute fish toxicity	LC50 0,193 mg/l	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard
	Acute algae toxicity	ErC50 0,152 mg/l	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,007 mg/l	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t
	Fish toxicity	NOEC 0,123 mg/l	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de
	Algae toxicity	NOEC 0,0102 mg/l	19 d	other aquatic plant: giant kelp Macrocystis pyrife	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199)	Tests were conducted to determine the ef
	Crustacea toxicity	NOEC 0,033 mg/l	14 d	Penaeus mergulensis and Penaeus monodon	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

## BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi
10125-13-0	Kupfer-II-chlorid-2-hydrat	0,02 - 20	Crangon crangon	Symp. Biologica. Hun

**Macro etching solution according to Fry suitable for the visualization of lines of action of the  
for**

Revision date: 02.01.2025

Product code: 14061

Page 12 of 15

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid, Copper chloride)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid, Copper chloride)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 13 of 15

#### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid, Copper chloride)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid, Copper chloride)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	A3
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Copper chloride

#### 14.6. Special precautions for user

Warning: Combustible liquid. strongly corrosive.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

Additional information: P5c

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 14 of 15

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1,9,12,15.

### Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals  
 Flam. Liq: Flammable liquid  
 Acute Tox: Acute toxicity  
 Skin Corr: Skin corrosion  
 Skin Irrit: Skin irritation  
 Eye Dam: Eye damage  
 Eye Irrit: Eye irritation  
 STOT SE: Specific target organ toxicity - single exposure  
 Aquatic Acute: Acute aquatic hazard  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H290 May be corrosive to metals.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Macro etching solution according to Fry suitable for the visualization of lines of action of the for

Revision date: 02.01.2025

Product code: 14061

Page 15 of 15

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*