

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

REACH Registration Number: 01-2119433307-44-XXXX  
CAS No: 67-56-1  
Index No: 603-001-00-X  
EC No: 200-659-6

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit  
Telefax: 0203/5194-290  
Telephone: 0203/5194-107/117

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

No data available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Acute Tox. 3; H331  
Acute Tox. 3; H311  
Acute Tox. 3; H301  
STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 2 of 13

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
H370 Causes damage to organs (eyes, central nervous system).

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.  
P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Sum formula: CH<sub>3</sub>OH  
Molecular weight: 32,04 g/mol

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			100 %
	200-659-6	603-001-00-X	01-2119433307-44-XXXX	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H301 H370			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-56-1	200-659-6	methanol	100 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 3 of 13

Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

#### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Consult an ophthalmologist.

#### After ingestion

Provide fresh air.  
Call a physician immediately.  
Notes for the doctor : Methanol

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness  
Dizziness, Anaesthetic state  
Agitation, Spasms  
Inebriation, Vomiting  
Headache, Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquids  
Highly flammable.  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide, Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Beware of reignition.  
Heating causes rise in pressure with risk of bursting.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.  
Wear full chemical protective clothing.  
In case of fire and/or explosion do not breathe fumes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 4 of 13

#### For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

- Do not allow uncontrolled discharge of product into the environment. Danger of explosion
- Do not allow to enter into surface water or drains.
- The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
- Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

- Avoid exposure - obtain special instructions before use.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

- Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
- Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

- Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H2O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 5 of 13

a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

storage temperature: +5°C - +30°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

**DNEL/DMEL values**

CAS No	Substance	DNEL type	Exposure route	Effect	Value
67-56-1	methanol	Consumer DNEL, acute	inhalation	systemic	50 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	systemic	260 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	local	260 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>
		Worker DNEL, long-term	dermal	systemic	40 mg/kg bw/day
		Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	50 mg/m <sup>3</sup>
		Consumer DNEL, long-term	inhalation	local	50 mg/m <sup>3</sup>
		Consumer DNEL, acute	inhalation	local	50 mg/m <sup>3</sup>
		Consumer DNEL, long-term	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	8 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 6 of 13

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 898 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 7 of 13

Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation  
Filtering device with filter or ventilator filtering device of type: AX

#### Environmental exposure controls

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-98 °C
Boiling point or initial boiling point and boiling range:	64,7 °C
Flammability:	not applicable
Lower explosion limits:	5,5 vol. %
Upper explosion limits:	44 vol. %
Flash point:	9,7 °C
Auto-ignition temperature:	420 °C
Decomposition temperature:	not determined
pH-Value:	No data available
Viscosity / kinematic:	No data available
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	log Pow: -0,77
Vapour pressure: (at 20 °C)	128 hPa
Vapour pressure: (at 50 °C)	546,6 hPa
Density:	0,792 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

Vapours can form explosive mixtures with air.

##### Sustaining combustion:

Sustaining combustion

##### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

##### Oxidizing properties

not determined

#### Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 8 of 13

Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic: (at 20 °C)	0,597 mPa·s
Flow time:	No data available

#### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.  
Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent, Nitrogen oxides (NO<sub>x</sub>), Potassium chlorate, peroxides, for example hydrogen peroxide, Nitric acid, sulphuric acid, Acid halogen, Acetic anhydride, Maleic anhydride, Reducing agent, Acid, Bromine, Chlorine, Chloroform, Fluorine, Alkali metals, Alkaline earth metal;

### 10.4. Conditions to avoid

Vapours can form explosive mixtures with air.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Plastic articles  
Zinc

### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

#### Acute toxicity

Toxic if swallowed.  
Toxic in contact with skin.  
Toxic if inhaled.  
Irritation to respiratory tract



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 mg/kg 6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE mg/kg 300			
	inhalation (4 h) vapour	LC50 mg/l 128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.  
Has degreasing effect on the skin.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Causes damage to organs. (methanol)  
eyes, central nervous system

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

Irritation to respiratory tract  
Repeated exposure may cause skin dryness or cracking.  
Causes damage to organs.  
Organs affected:  
Liver and kidney damage  
eyes  
heart

**Further information**

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache,  
Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H2O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 10 of 13

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

**12.2. Persistence and degradability**

99 %; 30 d  
OECD 301D  
Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 11 of 13

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste.  
Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1230
<b>14.2. UN proper shipping name:</b>	METHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	279
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	336
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1230
<b>14.2. UN proper shipping name:</b>	METHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	279 802
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1230
<b>14.2. UN proper shipping name:</b>	METHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Special Provisions:	279
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1230
<b>14.2. UN proper shipping name:</b>	METHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Special Provisions:	A113
Limited quantity Passenger:	1 L

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm**

Revision date: 22.05.2023

Product code: 14730

Page 12 of 13

Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		352
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. Toxic.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69

Information according to 2012/18/EU (SEVESO III): 22 Methanol (67-56-1)

Additional information: H2, P5c

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,11,12,15.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

STOT SE: Specific target organ toxicity - single exposure

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol dried > 99.8 % for analysis suitable for Karl Fischer titration H<sub>2</sub>O < 50 ppm

Revision date: 22.05.2023

Product code: 14730

Page 13 of 13

H331	Toxic if inhaled.
H370	Causes damage to organs (eyes, central nervous system).
H370	Causes damage to organs.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.