



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 1 of 14

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Potassium hydroxide 2 mol/I - 2 N solution in methanol

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTF	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls

### Further Information

This product is a mixture. REACH Registration Number see section 3.

accepted)

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### Regulation (EC) No 1272/2008

### Hazard components for labelling

methanol potassium hydroxide

potassium nyuloxide

Signal word: Danger



	Potassium hydroxide 2 mol/l - 2 N solution in methanol	
Revision date: 04.08.2023	Product code: 15895	Page 2 of 14
Pictograms:		
Hazard statements		
H225	Highly flammable liquid and vapour.	
H290	May be corrosive to metals.	
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.	
H314	Causes severe skin burns and eye damage.	
H370	Causes damage to organs.	
Precautionary statemen	Its	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P240	Ground and bond container and receiving equipment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.	

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

### Hazardous components

CAS No	Chemical name					
	EC No	Index No REACH No				
	Classification (Regulation (EC) No 1272/2008)					
67-56-1	methanol	methanol				
	200-659-6	603-001-00-X	01-2119433307-44			
	Flam. Liq. 2, Acute Tox. 3, A	Acute Tox. 3, Acute Tox. 3, STOT	SE 1; H225 H331 H311 H301 H370			
1310-58-3	potassium hydroxide			10 - < 15 %		
	215-181-3	019-002-00-8	01-2119487136-33			
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A; H290 H302 H314					

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Cond	Specific Conc. Limits, M-factors and ATE				
67-56-1	200-659-6	200-659-6 methanol				
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10					
1310-58-3	215-181-3	potassium hydroxide	10 - < 15 %			
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2					



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 3 of 14

### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### General information

First aider: Pay attention to self-protection!

### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

#### After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

#### After ingestion

Provide fresh air. Do not allow a neutralisation agent to be drunk. Call a physician immediately. Notes for the doctor : Methanol

### 4.2. Most important symptoms and effects, both acute and delayed

corrosive, Irritant, Dizziness, Dizziness Anaesthetic state, Agitation, Spasms Inebriation, Vomiting, Headache Impairment of vision, Dyspnoea, Cough Repeated exposure may cause skin dryness or cracking. Risk of serious damage to eyes. Circulatory collapse, Corneal opacity.

# 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor : Methanol

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2) Foam Extinguishing powder

# Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Beware of reignition.



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 4 of 14

Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Keep away from sources of ignition - No smoking. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Take action to prevent static discharges. Corrosive to metals.

### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

# For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

# 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13





according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 5 of 14

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

Avoid exposure - obtain special instructions before use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

# 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material: Aluminium, tin, zinc

### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

### Further information on storage conditions

Keep cool. Protect from sunlight.

storage temperature +15°C - +25°C

# 7.3. Specific end use(s)

Laboratory chemicals

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### **Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

#### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 6 of 14

### **DNEL/DMEL** values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
67-56-1	methanol		·				
Consumer DN	IEL, acute	inhalation	systemic	50 mg/m³			
Worker DNEL	, long-term	inhalation	systemic	260 mg/m³			
Worker DNEL	, acute	inhalation	systemic	260 mg/m³			
Worker DNEL	, long-term	inhalation	local	260 mg/m³			
Worker DNEL	, acute	inhalation	local	260 mg/m³			
Worker DNEL	, long-term	dermal	systemic	40 mg/kg bw/day			
Worker DNEL	, acute	dermal	systemic	40 mg/kg bw/day			
Consumer DN	IEL, long-term	inhalation	systemic	50 mg/m³			
Consumer DN	IEL, long-term	inhalation	local	50 mg/m³			
Consumer DN	IEL, acute	inhalation	local	50 mg/m³			
Consumer DN	IEL, long-term	dermal	systemic	8 mg/kg bw/day			
Consumer DN	IEL, acute	dermal	systemic	8 mg/kg bw/day			
Consumer DN	IEL, long-term	oral	systemic	8 mg/kg bw/day			
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day			
1310-58-3	potassium hydroxide						
Worker DNEL	, long-term	inhalation	local	1 mg/m³			
Consumer DN	IEL, long-term	inhalation	local	1 mg/m³			

# **PNEC** values

CAS No	Substance				
Environmen	tal compartment	Value			
67-56-1	methanol				
Freshwater	20,8 mg/l				
Freshwater (intermittent releases) 1					
Marine water		2,08 mg/l			
Freshwater sediment		77 mg/kg			
Marine sedi	ment	7,7 mg/kg			
Micro-organ	100 mg/l				
Soil	100 mg/kg				

# 8.2. Exposure controls

# Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

goggles

### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 7 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Recommended glove articles KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme.

# Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

# Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid colourless	
Odour:	like: Methanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		~64 °C
boiling range:		
Flammability:		not applicable
Lower explosion limits:		5,5 vol. %
Upper explosion limits:		44 vol. %
Flash point:		~11 °C
Auto-ignition temperature:		455 °C
Decomposition temperature:		not determined
pH-Value:		alkaline



#### Potassium hydroxide 2 mol/l - 2 N solution in methanol Product code: 15895 Revision date: 04.08.2023 Page 8 of 14 Viscosity / kinematic: not determined Soluble in: Water Water solubility: Solubility in other solvents not determined No data available Dissolution rate: Partition coefficient n-octanol/water: not determined Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: 0.9397 g/cm<sup>3</sup> Relative density: No data available No data available Bulk density: Relative vapour density: not determined Particle characteristics: No data available 9.2. Other information Information with regard to physical hazard classes Explosive properties Vapours can form explosive mixtures with air. Sustaining combustion: Sustaining combustion Self-ignition temperature Solid: not applicable Gas: not applicable Oxidizing properties not determined Other safety characteristics Evaporation rate: not determined Solvent separation test: not determined Solvent content: No data available Solid content: not determined Sublimation point: No data available No data available Softening point: Pour point: No data available No data available: No data available Viscosity / dynamic: not determined Flow time: **Further Information** May be corrosive to metals.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Highly flammable. Vapours can form explosive mixtures with air. May be corrosive to metals.

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent, Hydrogen peroxide, Acid halides Reducing agent, Acid, Alkaline earth metal, Alkali metals

### 10.4. Conditions to avoid

Vapours can form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 9 of 14

# 10.5. Incompatible materials

Plastic articles Glass metals (including their alloys)

### 10.6. Hazardous decomposition products

#### SECTION 5: Firefighting measures

Further information

No data available

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

#### Acute toxicity

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

#### ATEmix calculated

ATE (oral) 115,4 mg/kg; ATE (dermal) 354,4 mg/kg; ATE (inhalation vapour) 3,540 mg/l; ATE (inhalation dust/mist) 0,5910 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-56-1	methanol							
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t		
	dermal	ATE mg/kg	300					
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co		
	inhalation dust/mist	ATE	0,5 mg/l					
1310-58-3	potassium hydroxide	potassium hydroxide						
	oral	LD50 mg/kg	333	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425		

### Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage. Corneal opacity.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Causes damage to organs. (methanol) eyes Liver and kidney damage

STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 10 of 14

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

There are no data available on the mixture itself.

### Specific effects in experiment on an animal

There are no data available on the mixture itself.

### Additional information on tests

There are no data available on the mixture itself.

### Practical experience

There are no data available on the mixture itself.

# 11.2. Information on other hazards

#### Endocrine disrupting properties

There are no data available on the mixture itself.

#### Other information

corrosive, Irritant, Dizziness, Dizziness Anaesthetic state, Agitation, Spasms Inebriation, Vomiting, Headache Impairment of vision, Dyspnoea, Cough Repeated exposure may cause skin dryness or cracking. Risk of serious damage to eyes. Circulatory collapse, Corneal opacity.

### **Further information**

Do not empty into drains. Discharge into the environment must be avoided.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
67-56-1	methanol							
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975	
	Acute algae toxicity	ErC50 22000 mg/l	ca.		Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11	
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR	
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi	

# 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 11 of 14

### Partition coefficient n-octanol/water

CAS No	No Chemical name					
67-56-1	6-1 methanol					
BCF					•	
CAS No	Chemical name	BCF	Species	Source		
67-56-1	methanol	1	Cyprinus carpio	Comparativ	e Biochemi	

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

### **Further information**

Do not allow to enter into surface water or drains. Avoid release to the environment.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not allow to enter into surface water or drains.

# Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

# **SECTION 14: Transport information**

Land transport (ADR/RID)	
<u>14.1. UN number or ID number:</u>	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol,
	potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	368
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 3286



Potassium hydroxide 2 mol/l - 2 N solution in methanol   Revision date: 04.08.2023 Product code: 15895 Page 12 of 14			
		1 age 12 01 14	
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:			
Hazard label:	3+6.1+8		
Classification code:	FTC		
Special Provisions:	274 802		
Limited quantity:	1 L		
Excepted quantity:	E2		
Marine transport (IMDG)			
14.1. UN number or ID number:	UN 3286		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3+6.1/8		
Special Provisions:	274		
Limited quantity:			
Excepted quantity:	E2		
EmS:	F-E, S-C		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 3286		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)		
14.3. Transport hazard class(es):	3 		
<u>14.4. Packing group:</u> Hazard label:	3+6.1 8		
Limited quantity Passenger:	0.5 L		
Passenger LQ:	Y340		
Excepted quantity:	E2		
IATA-packing instructions - Passenger:	352		
IATA-max. quantity - Passenger:	1 L		
IATA-packing instructions - Cargo:	363		
IATA-max. quantity - Cargo:	5 L		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user			
Warning: Combustible liquid. Toxic.			
14.7. Maritime transport in bulk according to not applicable	o IMO instruments		
SECTION 15: Regulatory information			
	ations/legislation specific for the substance or mixture		
EU regulatory information			
Restrictions on use (REACH, annex XVII):			
Entry 3, Entry 40, Entry 69, Entry 75			
Information according to 2012/18/EU	H2 ACUTE TOXIC		
(SEVESO III):			
Additional information:	P5c		
National regulatory information			



according to Regulation (EC) No 1907/2006

Potassium hydroxide 2 mol/I - 2 N solution in methanol			
Revision date: 04.08.2023	Product code: 15895	Page 13 of 14	
Employment restrictions:	Observe restrictions to employment for juveniles acco work protection guideline' (94/33/EC). Observe employ under the Maternity Protection Directive (92/85/EEC) f nursing mothers.	yment restrictions	
Water hazard class (D):	2 - obviously hazardous to water		
Skin resorption/Sensitization:	Permeates easily through outer skin and causes poiso	oning.	

# **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 3,8,9,12.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Met. Corr: Substance or mixture corrosive to metals Flam. Lig: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eve Dam: Eve damage STOT SE: Specific target organ toxicity - single exposure

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

# Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs.

# Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 2 mol/l - 2 N solution in methanol

Revision date: 04.08.2023

Product code: 15895

Page 14 of 14

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)