

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Acute Tox. 4; H302
Acute Tox. 4; H312
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Repr. 2; H361d
STOT SE 1; H370
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene
2,2,4-trimethylpentane
methanol
2,4,4-trimethylpentene

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 2 of 17

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P310	Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			45 - < 50 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
540-84-1	2,2,4-trimethylpentane			20 - < 25 %
	208-759-1	601-009-00-8	01-2119457965-22	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			
67-56-1	methanol			10 - < 15 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
25167-70-8	2,4,4-trimethylpentene			10 - < 15 %
	246-690-9	601-087-00-3		
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1; H225 H336 H304			
64-17-5	ethanol			1 - < 5 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-88-3	203-625-9	toluene	45 - < 50 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
540-84-1	208-759-1	2,2,4-trimethylpentane	20 - < 25 %
		inhalation: LC50 = > 33,52 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
67-56-1	200-659-6	methanol	10 - < 15 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
25167-70-8	246-690-9	2,4,4-trimethylpentene	10 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
64-17-5	200-578-6	ethanol	1 - < 5 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 4 of 17

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Headache
Dizziness, Dizziness
Vomiting, Inebriation
Spasms, Circulatory collapse
Respiratory complaints, Dyspnoea
Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.
Extinguishing powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Beware of reignition.
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 5 of 17

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Draw up and observe skin protection programme.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 6 of 17

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
Store in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
108-88-3	toluene			
Worker DNEL, long-term		inhalation	systemic	192 mg/m ³
Worker DNEL, acute		inhalation	systemic	384 mg/m ³
Worker DNEL, long-term		inhalation	local	192 mg/m ³
Worker DNEL, acute		inhalation	local	384 mg/m ³
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m ³
Consumer DNEL, acute		inhalation	systemic	226 mg/m ³
Consumer DNEL, long-term		inhalation	local	56,5 mg/m ³
Consumer DNEL, acute		inhalation	local	226 mg/m ³
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,13 mg/kg bw/day
540-84-1	2,2,4-trimethylpentane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
25167-70-8	2,4,4-trimethylpentene			
Worker DNEL, long-term		inhalation	systemic	14,7 mg/m ³
Worker DNEL, long-term		dermal	systemic	2,1 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	4,4 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,2 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2,5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 8 of 17

64-17-5	ethanol		
Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment			Value
108-88-3	toluene		
Freshwater			0,68 mg/l
Freshwater (intermittent releases)			0,68 mg/l
Marine water			0,68 mg/l
Freshwater sediment			16,39 mg/kg
Marine sediment			16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)			13,61 mg/l
Soil			2,89 mg/kg
67-56-1	methanol		
Freshwater			20,8 mg/l
Freshwater (intermittent releases)			1540 mg/l
Marine water			2,08 mg/l
Freshwater sediment			77 mg/kg
Marine sediment			7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)			100 mg/l
Soil			100 mg/kg
25167-70-8	2,4,4-trimethylpentene		
Freshwater			0,015 mg/l
Freshwater (intermittent releases)			0,015 mg/l
Marine water			0,015 mg/l
Freshwater sediment			0,9 mg/kg
Marine sediment			0,9 mg/kg
Micro-organisms in sewage treatment plants (STP)			0,233 mg/l
Soil			0,43 mg/kg
64-17-5	ethanol		
Freshwater			0,96 mg/l
Freshwater (intermittent releases)			2,75 mg/l
Marine water			0,79 mg/l
Freshwater sediment			3,6 mg/kg
Marine sediment			2,9 mg/kg
Secondary poisoning			380 mg/kg
Micro-organisms in sewage treatment plants (STP)			580 mg/l
Soil			0,63 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 9 of 17

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Hydrocarbons, aromatic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		~64 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		-12 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 10 of 17

Water solubility:	No data available
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,7864 g/cm ³
Bulk density:	No data available
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Nitric acid

Acetic acid

Strong acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 11 of 17

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if swallowed.
Harmful in contact with skin.
Harmful if inhaled.

ATEmix calculated

ATE (oral) 666,2 mg/kg; ATE (dermal) 1998,7 mg/kg; ATE (inhalation vapour) 19,99 mg/l; ATE (inhalation dust/mist) 3,331 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
540-84-1	2,2,4-trimethylpentane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 33,52 mg/l	Rat	Study report (1982)	OECD Guideline 403
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
25167-70-8	2,4,4-trimethylpentene				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 402
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 12 of 17

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

May cause drowsiness or dizziness. (toluene; 2,2,4-trimethylpentane)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
540-84-1	2,2,4-trimethylpentane					
	Acute fish toxicity	LC50 0,11 mg/l	96 h	Oncorhynchus mykiss	SIDS Initial Assessment Report For SIAM	OECD Guideline 203
	Acute algae toxicity	ErC50 2,943 mg/l	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 0,4 mg/l	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC 0,82 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
25167-70-8	2,4,4-trimethylpentene					

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 14 of 17

	Acute algae toxicity	ErC50 mg/l	0,73	72 h	Pseudokirchneriella subcapitata	Study report (1996)	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	0,16	21 d	Daphnia magna	Study report (2009)	OECD Guideline 211
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 mg/l	ca. 22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
540-84-1	2,2,4-trimethylpentane	4,08
67-56-1	methanol	-0,77
25167-70-8	2,4,4-trimethylpentene	4,9 - 5
64-17-5	ethanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
540-84-1	2,2,4-trimethylpentane	231	calculated	Other company data (
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi
25167-70-8	2,4,4-trimethylpentene	925	no data	QSAR calculation (20
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 15 of 17

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	336
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 16 of 17

14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	2,2,4-trimethylpentane

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 69, Entry 75

Information according to 2012/18/EU (SEVESO III): H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Additional information: P5c, E2

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 2 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 02.03.2023

Product code: 16175

Page 17 of 17

H302	Harmful if swallowed.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)