

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Acute Tox. 4; H302
Acute Tox. 4; H312
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Repr. 2; H361d
STOT SE 1; H370
STOT SE 3; H336
STOT RE 2; H373
Aquatic Acute 1; H400
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195


Page 2 of 16

Hazard components for labelling

2,2,4-trimethylpentane
toluene
methanol

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P310	Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
540-84-1	2,2,4-trimethylpentane	45 - < 50 %
	208-759-1	601-009-00-8
	01-2119457965-22	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410	
108-88-3	toluene	35 - < 40 %
	203-625-9	601-021-00-3
	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412	
67-56-1	methanol	15 - < 20 %
	200-659-6	603-001-00-X
	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
540-84-1	208-759-1	2,2,4-trimethylpentane	45 - < 50 %
		inhalation: LC50 = > 33,52 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
108-88-3	203-625-9	toluene	35 - < 40 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
67-56-1	200-659-6	methanol	15 - < 20 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.

Extinguishing powder

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 4 of 16

Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Beware of reignition.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 5 of 16

Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
Draw up and observe skin protection programme.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
Store in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
540-84-1	2,2,4-trimethylpentane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
108-88-3	toluene			
Worker DNEL, long-term		inhalation	systemic	192 mg/m ³
Worker DNEL, acute		inhalation	systemic	384 mg/m ³
Worker DNEL, long-term		inhalation	local	192 mg/m ³
Worker DNEL, acute		inhalation	local	384 mg/m ³
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m ³
Consumer DNEL, acute		inhalation	systemic	226 mg/m ³
Consumer DNEL, long-term		inhalation	local	56,5 mg/m ³
Consumer DNEL, acute		inhalation	local	226 mg/m ³
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,13 mg/kg bw/day
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 7 of 16

PNEC values

CAS No	Substance	Value
Environmental compartment		
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 8 of 16

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Hydrocarbons, aromatic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		-12 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents:		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,76025 g/cm ³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 9 of 16

Pour point: No data available
No data available
Viscosity / dynamic: No data available
Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent
Nitric acid
Acetic acid
Strong acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles
Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if swallowed.
Harmful in contact with skin.
Harmful if inhaled.

ATEmix calculated

ATE (oral) 641,4 mg/kg; ATE (dermal) 1924 mg/kg; ATE (inhalation vapour) 19,24 mg/l; ATE (inhalation dust/mist) 3,207 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
540-84-1	2,2,4-trimethylpentane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 33,52 mg/l	Rat	Study report (1982)	OECD Guideline 403
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

May cause drowsiness or dizziness. (2,2,4-trimethylpentane; toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 11 of 16

inflammation).

Further information

Irritant, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
540-84-1	2,2,4-trimethylpentane					
	Acute fish toxicity	LC50 mg/l	0,11	96 h	Oncorhynchus mykiss	SIDS Initial Assessment Report For SIAM OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	2,943	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50	0,4 mg/l	48 h	Daphnia magna	Publication (1986) other: As described in: The evaluation o
	Fish toxicity	NOEC mg/l	0,82	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 211
108-88-3	toluene					
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436. Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier Method: other
	Acute crustacea toxicity	EC50 mg/l	11,5	48 h	Daphnia magna	REACH Registration Dossier Method: other
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436. Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier Method: other
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 mg/l	ca. 22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7 OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989) other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research, Calculation performed with ECOSAR
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013) Toxicity of the target chemical is predi

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 13 of 16

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
540-84-1	2,2,4-trimethylpentane	4,08
108-88-3	toluene	2,73
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
540-84-1	2,2,4-trimethylpentane	231	calculated	Other company data (
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.
Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (2,2,4-trimethylpentane, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 14 of 16

Transport category: 2
Hazard No: 336
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1992
14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (2,2,4-trimethylpentane, methanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+6.1
Classification code: FT1
Special Provisions: 274 802
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1992
14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (2,2,4-trimethylpentane, methanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+6.1
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1992
14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (2,2,4-trimethylpentane, methanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+6.1
Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 352
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: 2,2,4-trimethylpentane

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 48, Entry 69, Entry 75
Information according to Directive 2012/18/EU (SEVESO III): H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE
Additional information: P5c, E1

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 15 of 16

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid 4 Reference fluid for fuels with oxygen compound according to DIN ISO 1817:2008

Revision date: 09.02.2024

Product code: 16195

Page 16 of 16

H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)