

according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

UFI: 4PUE-K118-K004-MSH7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone
 number:
 For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,
 Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid

Signal word: Danger

Pictograms:





according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 2 of 15

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

EUH208 Contains nickel dinitrate. May produce an allergic reaction.

2.3. Other hazards

P310

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) N	1272/2008)				
7697-37-2	nitric acid			5 - < 10 %		
	231-714-2	007-030-00-3	01-2119487297-23			
	Ox. Liq. 3, Met. Corr. 1, Acute To	x. 3, Skin Corr. 1A; H272 H290 H331	H314 EUH071			
7664-38-2	phosphoric acid					
	231-633-2	015-011-00-6	01-2119485924-24			
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H290 H302 H314 H318					
13138-45-9	nickel dinitrate		< 0.01 %			
	236-068-5	028-012-00-1	01-2119492333-38			
	Ox. Sol. 2, Carc. 1A, Muta. 2, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H350i H341 H360D H332 H302 H315 H318 H334 H317 H372 H400 H410					

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc. I	Limits, M-factors and ATE					
7697-37-2	231-714-2	231-714-2 nitric acid					
	l l	2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 rr. 1B; H314: >= 5 - < 20					
7664-38-2	231-633-2	phosphoric acid	< 0.01 %				
	oral: ATE = 500 Irrit. 2; H319: >=	0 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye = 10 - < 25					
13138-45-9	236-068-5	nickel dinitrate	< 0.01 %				
	361,9 mg/kg S	•					

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

Causes burns.

Cough

Dyspnoea

Risk of serious damage to eyes.

Vomiting

Methaemoglobinaemia

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 4 of 15

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 5 of 15

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Material, oxygen-rich, Oxidising

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations.

Keep in a cool place.

Further information on storage conditions

Unsuitable container/equipment material: Metal, Light metal

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
7440-50-8	Copper, dusts and mists	-	1		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	
		-	2		STEL (15 min)	



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
7664-38-2	phosphoric acid			
Worker DNEL	, acute	inhalation	local	2 mg/m³
Worker DNEL	., long-term	inhalation	local	2,92 mg/m³
Consumer DN	IEL, long-term	inhalation	systemic	4,57 mg/m³
Consumer DN	IEL, long-term	inhalation	local	0,36 mg/m³
Consumer DN	IEL, long-term	oral	systemic	0,1 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	10,7 mg/m³
13138-45-9	nickel dinitrate			
Consumer DN	IEL, acute	oral	systemic	0,012 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day
Worker DNEL	., acute	inhalation	systemic	104 mg/m³
Worker DNEL	., acute	inhalation	local	1,6 mg/m³
Consumer DN	IEL, acute	inhalation	systemic	8,8 mg/m³
Consumer DN	IEL, acute	inhalation	local	0,1 mg/m³

PNEC values

CAS No	Substance	
Environmenta	ll compartment	Value
13138-45-9	nickel dinitrate	•
Freshwater		0,0071 mg/l
Freshwater (in	ntermittent releases)	0 mg/l
Marine water		0,0086 mg/l
Freshwater se	ediment	109 mg/kg
Marine sedim	Marine sediment	
Secondary poisoning		0,12 mg/kg
Micro-organis	Micro-organisms in sewage treatment plants (STP)	
Soil	Soil	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Face protection shield goggles.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 7 of 15

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range: Flammability:

Lower explosion limits:

Upper explosion limits:

No data available
Plash point:

X
Auto-ignition temperature:

No data available
Decomposition temperature:

No data available
pH-Value:

viscosity / kinematic:

No data available
Water solubility:

No data available

Solubility in other solvents

not determined

No data available Dissolution rate: Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: No data available Relative density: No data available Bulk density: No data available No data available Relative vapour density:

No data available



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains:

Revision date: 02.04.2024 Product code: 16198 Page 8 of 15

No data available

No data available

No data available

Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

Sustaining Combustion.

Self-ignition temperature

Solid:

Gas: Oxidizing properties

Oxidising.

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Danger of explosion:

Acetone, Alcohol, Aniline, Substance, organic, Benzene, Aniline, Amines, Hydrocarbons, halogenated, Diethyl ether, Hydrazine, Dioxane, Acetic acid, Acetic anhydride, Ethanol, Fluorine, Formaldehyde, Rubber articles, Hydrocarbons, Copper, Powdered metals, Methanol, Phosphorus trichloride, Hydrogen phosphides, Gasoline, Reducing agent, titanium, Toluene, Hydrogen peroxide, tin, Xylene, Dichloromethane, carbon black, Potassium chlorate, permanganates, e.g. potassium permanganate

Ignition hazard:

Amines, Ammonia (NH3), Combustible substance, aldehydes, Hydrogen iodide (HI), White/yellow phosphor, Hydrogen sulphide (H2S), Alkali metals, Alkaline earth metal

Violent reaction with:

Nitriles, antimony, arsenic, boron, Alkali (Iye), , Formic acid, sulphuric acid, sulphuric acid, sulphuric acid, selenium

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Cellulose, Metal Keep away from: Metal.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 9 of 15

Keep away from combustible material.

The product develops hydrogen in an aqueous solution in contact with metals. / Nitrogen oxides (NOx)

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
7697-37-2	nitric acid							
	inhalation vapour	ATE 2,6	5 mg/l					
7664-38-2	phosphoric acid							
	oral	ATE mg/kg	500					
13138-45-9	nickel dinitrate							
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425		
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Corrosive to the respiratory tract.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains nickel dinitrate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 10 of 15

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

Irritant — skin irritation and eye damage

Causes burns.

Cough

Dyspnoea

Risk of serious damage to eyes.

Vomiting

Methaemoglobinaemia

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 11 of 15

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
7664-38-2	phosphoric acid						
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2010)	EU Method C.3
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2010)	OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209
13138-45-9	nickel dinitrate						
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
	Acute bacteria toxicity	EC50	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains:

Revision date: 02.04.2024 Product code: 16198 Page 12 of 15

BCF

CAS No	Chemical name	BCF	Species	Source
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

UN 2031

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Do not mix with other wastes.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1. UN number or ID number:

Land transport (ADR/RID)

14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2

Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN	l number	or ID r	•	,	UN 2031
14.2. UN	l proper s	hippin	a na	me:	NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains:

Revision date: 02.04.2024 Product code: 16198 Page 13 of 15

Marine transport (IMDG)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2031 **14.2. UN proper shipping name:** NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A212Limited quantity Passenger:ForbiddenPassenger LQ:ForbiddenExcepted quantity:E0

IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Oxidising substances. strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 27, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 14 of 15

This data sheet contains changes from the previous version in section(s): 1,12.

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H272	May intensity fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
11045	Carrage alsie invitation

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.
H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.
H350i May cause cancer by inhalation.
H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

EUH208 Contains nickel dinitrate. May produce an allergic reaction.



according to Regulation (EC) No 1907/2006

Multielement standard solution 10 elements in nitric acid approx. 1 mol/l 1 Liter contains: 0.2 m

Revision date: 02.04.2024 Product code: 16198 Page 15 of 15

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)