

Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

Product code: 16350

to DI

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Revision date: 12.02.2024

Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according to DI

Substance name:	sulphuric acid
REACH Registration Number:	01-2119458838-20-XXXX
CAS No:	7664-93-9
Index No:	016-020-00-8
EC No:	231-639-5
UFI:	WR8F-G1XM-400C-5P31

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH ACD	
Street: Place:	Stempelstraße 6 D-47167 Duisburg	
Telephone: E-mail:	0203/5194-0 info@analytichem.de	Telefax: 0203/5194-290
Contact person: E-mail: Internet: Responsible Department:	Abteilung Produktsicherheit produktsicherheit@analytichem.de www.analytichem.de Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
<u>1.4. Emergency telephone</u> number:	Exposure, or Accident Call CHEMTF	ous Goods] Incidents Spill, Leak, Fire, REC Day or Night Within USA and Canada: Canada: +1 703-741-5970 (collect calls

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according to DI				
Revision date: 12.02.2024	Product code: 16350	Page 2 of 12		
Pictograms:				
Hazard statements				
H290	May be corrosive to metals.			
H314	Causes severe skin burns and eye damage.			
Precautionary statemen	its			
P280	•			
P301+P330+P331	P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
P305+P351+P338	· ·			
P308	IF exposed or concerned:			
P310	Immediately call a POISON CENTER/doctor.			
2.3. Other hazards				

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula:	H2SO4
Molecular weight:	98,08 g/mol

Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No				
	Classification (Regulation (EC) No 1272/2008)				
7664-93-9	sulphuric acid			95 - < 100 %	
	231-639-5 016-020-00-8 01-2119458838-20-XXXX				
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
7664-93-9	231-639-5	sulphuric acid	95 - < 100 %
oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

to DI

Revision date: 12.02.2024

Product code: 16350

Page 3 of 12

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.
Causes burns.
Irritant
Cough
Dyspnoea
Vomiting
Gastric perforation
Nausea
Abdominal pain

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated: Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

to DI

Page 4 of 12

Revision date: 12.02.2024

Product code: 16350

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Use extractor hood (laboratory). Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according to DI						
Revision date:	: 12.02.2024 Produ	uct code: 16	350			Page 5 of 12
Requirements for storage rooms and vessels Keep container tightly closed. Unsuitable container/equipment material: Metal						
Corros	formation on storage conditions ive to metals. oduct develops hydrogen in an aqueous solution	in contact w	ith metals.			
7.3. Specific e	end use(s)					
Labora	tory chemicals					
SECTION 8:	Exposure controls/personal protection					
8.1. Control p	arameters					
	exposure limits					
CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	
DNEL/DMEL	values		I	I		
CAS No	Substance					
DNEL type		Expo	sure route	Effect	V	′alue
7664-93-9	sulphuric acid					
Worker DNEL,	long-term	inhal	ation	local	0	,05 mg/m³
Worker DNEL,	acute	inhal	ation	local	0	,1 mg/m³
PNEC values	5					
CAS No	Substance					
Environmental compartment Value					alue	
7664-93-9	sulphuric acid					
Freshwater 0,003 mg/l					003 mg/l	
Marine water	Marine water 0 mg/l					mg/l
Freshwater see	Freshwater sediment 0,002 mg/kg					002 mg/kg
Marine sedime	Marine sediment 0,002 mg/kg					
Micro-organism	ns in sewage treatment plants (STP)				8,8	8 mg/l

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles Face protection shield

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

to DI

Revision date: 12.02.2024

Product code: 16350

Page 6 of 12

supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation KCL 890 Vitoject® Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation KCL 720 Camapren® Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		-20 °C
Boiling point or initial boiling point and boiling range:		335 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		Х
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value (at 20 °C):		0,3 (49 g/l)
Viscosity / kinematic:		No data available
Water solubility:		very soluble (Heat)
Solubility in other solvents		
No data available		
Dissolution rate:		No data available



Sulfuric acid solution 95.50 % calib	ration solution for determination of viscosit	y according
Devision data: 12.02.2024	to DI	Dage 7 of 12
Revision date: 12.02.2024	Product code: 16350	Page 7 of 12
Partition coefficient n-octanol/water:	No data available	
Dispersion stability:	No data available	
Vapour pressure:	0,0001 hPa	
(at 20 °C)		
Vapour pressure:	0,004 hPa	
(at 50 °C)		
Density:	No data available	
Bulk density:	No data available	
Relative vapour density:	3,4	
Particle characteristics:	No data available	
9.2. Other information		
Information with regard to physical hazard class	es	
Explosive properties		
No data available		
Sustaining combustion:	No data available	
Self-ignition temperature	NI 17 711	
Solid:	No data available	
Gas:	No data available	
Oxidizing properties No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available	
Sublimation point:	No data available No data available	
Softening point: Pour point:	No data available	
No data available:		
	24 m Da a	
Viscosity / dynamic:	24 mPa⋅s	
(at 20 °C) Flow time:	No data available	
	NU Gata available	
Further Information		
No data available		
SECTION 10: Stability and reactivity		

10.1. Reactivity

Corrosive to metals. Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Water, Alkali metals, Ammonia aldehydes, Alkaline earth metal, Acids Alkali (lye), Metal, Phosphorus oxides, Combustible substance Solvent, Aniline, permanganates, e.g. potassium permanganate Peroxides, Amines, Carbide peroxides, for example hydrogen peroxide , Nitriles



according to Regulation (EC) No 1907/2006 Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

to DI

Page 8 of 12

Revision date: 12.02.2024

Product code: 16350

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal

The product develops hydrogen in an aqueous solution in contact with metals. Cellulose

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Irritation to respiratory tract (Cough, Dyspnoea)

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source	Method	
7664-93-9	sulphuric acid	sulphuric acid					
	oral	LD50 mg/kg	2140	Rat	Am Ind Hyg Assoc 1969 Sep-Oct; 30(

Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage. Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according to DI				
Revision date: 12.02.2024	Product code: 16350	Page 9 of 12		
Practical experience No data available 11.2. Information on other hazards				
Endocrine disrupting properties No data available				
Other information No data available				
Further information Risk of serious damage to eyes. Causes burns. Irritant Cough Dyspnoea Vomiting Gastric perforation Nausea Abdominal pain				

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
7664-93-9	sulphuric acid							
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations



Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

according to Regulation (EC) No 1907/2006

to DI

Revision date: 12.02.2024

Product code: 16350

Page 10 of 12

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not mix with other wastes.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1. UN number or ID number:UN 183014.2. UN proper shipping name:SULPHURIC ACID14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:EInland waterways transport (ADN)
14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
14.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
14.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
Hazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
Limited quantity:1 LExcepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
Excepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
Excepted quantity:E2Transport category:2Hazard No:80Tunnel restriction code:E
Hazard No:80Tunnel restriction code:E
Tunnel restriction code: E
Inland waterways transport (ADN)
14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group:
Hazard label: 8
Classification code: C1
Limited quantity: 1 L
Excepted quantity: E2
Marine transport (IMDG)
14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group:
Hazard label: 8
Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-A, S-B
Air transport (ICAO-TI/IATA-DGR)
14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: SULPHURIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group:
Hazard label: 8
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2



Sulfuric acid solution s	95.50 % calibration solution for determination of viscosi to DI	ty according
Revision date: 12.02.2024	Product code: 16350	Page 11 of 12
IATA-packing instructions - Passe IATA-max. quantity - Passenger: IATA-packing instructions - Cargo IATA-max. quantity - Cargo:	1 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDO	US: No	
14.6. Special precautions for user Warning: strongly corrosive.		
14.7. Maritime transport in bulk acc not applicable	ording to IMO instruments	
SECTION 15: Regulatory information	ation	
15.1. Safety, health and environmen	tal regulations/legislation specific for the substance or mixture	
Acquisition, introduction, poss	precursors (Regulation (EU) 2019/1148): ession or use of this product by the general public is restricted by Regul s transactions, and significant disappearances and thefts should be repo	
National regulatory information		
Employment restrictions: Water hazard class (D):	Observe restrictions to employment for juveniles according to work protection guideline' (94/33/EC). 1 - slightly hazardous to water) the 'juvenile
	r - siightiy hazardous to water	
SECTION 16: Other information		
	ges from the previous version in section(s): 1,12.	
(European Agreement concern IMDG: International Maritime (IATA: International Air Transp GHS: Globally Harmonized Sy	transport des marchandises dangereuses par Route ning the International Carriage of Dangerous Goods by Road) Code for Dangerous Goods ort Association /stem of Classification and Labelling of Chemicals of Existing Commercial Chemical Substances ified Chemical Substances <i>v</i> ice	
Relevant H and EUH statements		
H314 Causes	e corrosive to metals. s severe skin burns and eye damage.	
H318 Causes	s serious eye damage.	
The above information describ	bes exclusively the safety requirements of the product and is based on o nformation is intended to give you advice about the safe handling of the	



Revision date: 12.02.2024

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 95.50 % calibration solution for determination of viscosity according

Product code: 16350

to DI

Page 12 of 12

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The receiver of our product is singularly responsible for adhering to existing laws and regulations.