

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Revision date: 13.02.2024

Product code: 16354

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Substance name: sulphuric acid
REACH Registration Number: 01-2119458838-20-XXXX
CAS No: 7664-93-9
Index No: 016-020-00-8
EC No: 231-639-5
UFI: K29F-H1Q6-C00C-T1E9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals
Industrial uses: Uses of substances as such or in preparations at industrial sites
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol**

Revision date: 13.02.2024

Product code: 16354

Page 2 of 12

Pictograms:



Hazard statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 IF exposed or concerned:
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: H₂SO₄
Molecular weight: 98,08 g/mol

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification (Regulation (EC) No 1272/2008)	
7664-93-9	sulphuric acid	95 - < 100 %
	231-639-5	016-020-00-8
		01-2119458838-20-XXXX
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7664-93-9	231-639-5	sulphuric acid	95 - < 100 %
		oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Revision date: 13.02.2024

Product code: 16354

Page 3 of 12

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Gastric perforation

Nausea

Abdominal pain

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Revision date: 13.02.2024

Product code: 16354

Page 4 of 12

For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff.
- Use personal protection equipment. Use extractor hood (laboratory).
- Provide adequate ventilation.
- Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol)**

Revision date: 13.02.2024

Product code: 16354

Page 5 of 12

Requirements for storage rooms and vessels

Keep container tightly closed.
Unsuitable container/equipment material: Metal

Further information on storage conditions

Corrosive to metals.
The product develops hydrogen in an aqueous solution in contact with metals.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³
Worker DNEL, acute		inhalation	local	0,1 mg/m ³

PNEC values

CAS No	Substance	Value
7664-93-9	sulphuric acid	
Environmental compartment		
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,002 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		8,8 mg/l

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:
goggles
Face protection shield

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol)**

Revision date: 13.02.2024

Product code: 16354

Page 6 of 12

supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®
Recommended material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®
Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm
Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.
Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation
Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	odourless
Odour threshold:	No data available
Melting point/freezing point:	-20 °C
Boiling point or initial boiling point and boiling range:	335 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	X
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value (at 20 °C):	0,3 (49 g/l)
Viscosity / kinematic:	No data available
Water solubility:	very soluble (Heat)
Solubility in other solvents	
No data available	
Dissolution rate:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Revision date: 13.02.2024

Product code: 16354

Page 7 of 12

Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	0,0001 hPa
Vapour pressure: (at 50 °C)	0,004 hPa
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	3,4
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	No data available
Sustaining combustion:	No data available
Self-ignition temperature	No data available
Solid:	No data available
Gas:	No data available
Oxidizing properties	No data available

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic: (at 20 °C)	24 mPa·s
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.
Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with:
Water, Alkali metals, Ammonia
aldehydes, Alkaline earth metal, Acids
Alkali (lye), Metal,
Phosphorus oxides, Combustible substance
Solvent, Aniline, permanganates, e.g. potassium permanganate
Peroxides, Amines, Carbide

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol**

Revision date: 13.02.2024

Product code: 16354

Page 8 of 12

peroxides, for example hydrogen peroxide , Nitriles

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Cellulose

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Irritation to respiratory tract (Cough, Dyspnoea)

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 mg/kg 2140	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol)**

Revision date: 13.02.2024

Product code: 16354

Page 9 of 12

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Risk of serious damage to eyes.

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Gastric perforation

Nausea

Abdominal pain

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodemus subspicatus	Study report (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009) OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977 Groups of sexually mature flagfish

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol)**

Revision date: 13.02.2024

Product code: 16354

Page 10 of 12

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not mix with other wastes.
Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: SULPHURIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Classification code: C1
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Classification code: C1
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: Sulphuric acid
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1830
14.2. UN proper shipping name: SULPHURIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2
IATA-packing instructions - Passenger: 851

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sulfuric acid solution 96.50 % calibration solution for determination of viscosity (plastics/pol)

Revision date: 13.02.2024

Product code: 16354

Page 11 of 12

IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Skin Corr: Skin corrosion

Eye Dam: Eye damage

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Sulfuric acid solution 96.50 % calibration solution for determination of viscosity
(plastics/pol**

Revision date: 13.02.2024

Product code: 16354

Page 12 of 12

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The receiver of our product is singularly responsible for adhering to existing laws and regulations.