

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kerosin Siedebereich: 190 - 250 °C

REACH Registration Number: 01-2119456620-43-XXXX

CAS No: 64742-47-8 Index No: 649-422-00-2 EC No: 926-141-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephoneFor Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,number:Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 2 of 10

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten			100 %
	926-141-6		01-2119456620-43-XXXX	
	Asp. Tox. 1; H304 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
		Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten	100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician immediately.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 3 of 10

Observe risk of aspiration if vomiting occurs.

4.2. Most important symptoms and effects, both acute and delayed

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Carbon dioxide (CO2)

Extinguishing powder

Water

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2) Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 4 of 10

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place.

Keep container tightly closed.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella



according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 5 of 10

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Recommended material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 30 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

-45 °C

Boiling point or initial boiling point and

193-245 °C

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

7 vol. %

Flash point:

77 °C

Auto-ignition temperature:

Decomposition temperature:

No data available



according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 6 of 10

No data available pH-Value: Viscosity / kinematic: 1.97 mm²/s

(at 20 °C)

Water solubility: 0 g/L

Solubility in other solvents

No data available

Dissolution rate: No data available

Partition coefficient n-octanol/water: 6-8.2

Dispersion stability: No data available Vapour pressure: 0.23 hPa

(at 20 °C)

Vapour pressure: No data available Density: 0,787 g/cm³ Relative density: No data available No data available Bulk density: No data available Relative vapour density: No data available Particle characteristics:

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available No data available Gas:

Oxidizing properties No data available

Other safety characteristics

No data available Evaporation rate: Solvent separation test: No data available 100% Solvent content: No data available Solid content: Sublimation point: No data available No data available Softening point: Pour point: No data available No data available Viscosity / dynamic: No data available

Flow time: No data available

Further Information Temperature Class: T3

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent



according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 7 of 10

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

plastics

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose	Species	Source	Method		
	Kohlenwasserstoffe, C1	Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1989)	OECD Guideline 401		
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Has degreasing effect on the skin.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Liver and kidney damage

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available



according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 8 of 10

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method	
	Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten					
	Fish toxicity	NOEC 0,173 mg/l	28 d Oncorhynchus mykiss	1 0	The aquatic toxicity was estimated by a	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten	>= 1,99

BCF

CAS No	Chemical name	BCF	Species	Source
	Kohlenwasserstoffe, C11-C14, n-Alkane, iso-Alkane, cyclische Verbindungen, <2 % Aromaten	>= 7		REACh Registration D

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

No data available

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 9 of 10

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.



according to Regulation (EC) No 1907/2006

Kerosin Siedebereich: 190 - 250 °C

Revision date: 29.03.2023 Product code: 16474 Page 10 of 10

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.