

# Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTF	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls

#### Further Information

This product is a mixture. REACH Registration Number see section 3.

accepted)

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Hazard components for labelling sodium hydroxide

Signal word:

Pictograms:



Danger

### Hazard statements

H290 H314 May be corrosive to metals. Causes severe skin burns and eye damage.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 2 of 11

#### **Precautionary statements**

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308	IF exposed or concerned:
P310	Immediately call a POISON CENTER/doctor.

#### 2.3. Other hazards

No information available.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

#### Hazardous components

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	Classification (Regulation	(EC) No 1272/2008)		
1310-73-2	sodium hydroxide		15 - < 20 %	
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1	A; H290 H314		

### Full text of H and EUH statements: see section 16.

Specific Co	nc. Limits, M-f	actors and ATE	
CAS No	EC No	Chemical name	
	Specific Cond	c. Limits, M-factors and ATE	
1310-73-2	215-185-5	215-185-5 sodium hydroxide	
Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2			

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection!

#### After inhalation

Provide fresh air. Call a physician immediately.

#### After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 3 of 11

Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

#### 4.2. Most important symptoms and effects, both acute and delayed

corrosive Irritant Dyspnoea Cough Circulatory collapse Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Non-flammable.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Avoid contact with skin, eyes and clothes.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Corrosive to metals.

### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 4 of 11

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe vapour/aerosol.

### Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Corrosive to metals. Unsuitable container/equipment material:

Metal, Aluminium, Zinc, tin

#### Further information on storage conditions

Store in a dry place.

Keep container tightly closed.

### 7.3. Specific end use(s)

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	



### Natronlauge 18,0 % 5,39 ± 0,03 mol/I Na2CO3 < 1g/I gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 5 of 11

### **DNEL/DMEL** values

CAS No	Substance	-	_	
DNEL type		Exposure route	Effect	Value
1310-73-2	sodium hydroxide			
Worker DNEL,	long-term	inhalation	local	1 mg/m³
Consumer DNE	EL, long-term	inhalation	local	1 mg/m³

#### 8.2. Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing.

### **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 6 of 11

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

9.1. Information on basic phy	vsical and chemical properties	
Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point		No data available
Boiling point or initial boilin	g point and	No data available
boiling range:		
Flammability:		not applicable
		not applicable
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		Х
Auto-ignition temperature:		not applicable
Decomposition temperatur	e:	not determined
pH-Value:		alkaline
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		
not determined		
Dissolution rate:		No data available
Partition coefficient n-octar	nol/water:	not determined
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		1,197 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		not determined
Particle characteristics:		No data available
9.2. Other information		
Information with regard to	o physical hazard classes	
Explosive properties		
not applicable		
Sustaining combustion:		No data available
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		
Not oxidising.		
Other safety characteristi	cs	
Evaporation rate:		not determined
Solvent separation test:		No data available
Solvent content:		No data available
Solid content:		not determined
Sublimation point:		No data available
Softening point:		No data available
Pour point:		No data available
No data available:		
Viscosity / dynamic:		No data available
Flow time:		No data available



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 7 of 11

#### **Further Information**

Corrosive to metals.

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Corrosive to metals.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

metals, Light metal (Formation of: Hydrogen) Combustible substance, Phenols Acid, Nitriles, Alkaline earth metal (Metal powder)

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Aluminium, Brass metals (including their alloys), Zinc Tin, Light metal Glass, plastics Material, containing silicate

#### 10.6. Hazardous decomposition products

No data available

#### Further information

No data available

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

#### Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage. Risk of serious damage to eyes.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 8 of 11

### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

There are no data available on the mixture itself.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

There are no data available on the mixture itself.

#### Other information

There are no data available on the mixture itself.

Further information corrosive Irritant Dyspnoea Cough Circulatory collapse

#### **SECTION 12: Ecological information**

### 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1310-73-2	sodium hydroxide	-				
	Acute crustacea toxicity	EC50 40,4 mg/l	48 h		Environmental	other: acute 48-h immobilization test ac

### 12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

There are no data available on the mixture itself.

#### 12.7. Other adverse effects

Discharge into the environment must be avoided.

#### **Further information**

Do not allow to enter into surface water or drains.



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 9 of 11

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not allow to enter into surface water or drains. Do not mix with other wastes.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	Ш
Hazard label:	8
Classification code:	C5
Limited quantity:	11
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
	-



## Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Natronlauge 18,0 % 5,39 ± 0,0	)3 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1	982
Revision date: 21.09.2023	Product code: 16575	Page 10 of 11
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	A3 A803 0.5 L Y840 E2 851 1 L 855 30 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for userWarning: strongly corrosive.14.7. Maritime transport in bulk according to not applicable	IMO instruments	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regula	ations/legislation specific for the substance or mixture	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 75 Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)	
National regulatory information		
Employment restrictions: Water hazard class (D):	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC). 1 - slightly hazardous to water	enile
SECTION 16: Other information		

#### \_\_\_\_\_

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Met. Corr: Substance or mixture corrosive to metals Skin Corr: Skin corrosion Eye Dam: Eye damage

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

### Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
------	-----------------------------

Causes severe skin burns and eye damage.

H314



### Natronlauge 18,0 % 5,39 ± 0,03 mol/l Na2CO3 < 1g/l gemäß DIN 54355:1977, ISO 699:1982...

Revision date: 21.09.2023

Product code: 16575

Page 11 of 11

H318

Causes serious eye damage.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)