

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

according to Regulation (EC) No 1907/2006

Revision date: 02.03.2023

Product code: 16776

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Screen cleaning test fluid according to PV 2037, chapter 3.2.3

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTF	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	anada: +1 703-741-5970 (collect calls

#### Further Information

This product is a mixture. REACH Registration Number see section 3.

accepted)

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

Regulation (EC) No 1272/2008

Signal word:

**Pictograms:** 



#### **Hazard statements**

H225 H319

P210

Highly flammable liquid and vapour. Causes serious eye irritation.

#### **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



#### according to Regulation (EC) No 1907/2006

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3 Revision date: 02.03.2023 Product code: 16776 Page 2 of 12 P233 Keep container tightly closed. P280 P280 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P235 Store in a well-ventilated place. Keep cool. 2.3. Other hazards

No information available.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

# Hazardous components

CAS No	Chemical name		Quantity		
	EC No	Index No	REACH No		
	Classification (Regulat				
64-17-5	ethanol			15 - < 20 %	
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2	2; H225 H319			
67-63-0	propan-2-ol; isopropyl	alcohol; isopropanol		5 - < 10 %	
	200-661-7	603-117-00-0			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				

# Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
64-17-5	200-578-6	ethanol	15 - < 20 %
	inhalation: LC5 100	0 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg	

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

# **General information**

No data available

# After inhalation

Provide fresh air. Call a doctor if you feel unwell.

# After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Rinse mouth immediately and drink plenty of water.



according to Regulation (EC) No 1907/2006

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 3 of 12

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant Dizziness The product causes narcotic-like effects. Inebriation Vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

no restriction

## 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Beware of reignition.

#### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases. Avoid contact with skin, eyes and clothes. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

# For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and



# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 4 of 12

basements in higher concentration.

Danger of explosion

# 6.3. Methods and material for containment and cleaning up

# For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. If handled uncovered, arrangements with local exhaust ventilation have to be used. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

#### Further information on storage conditions

Vapours may form explosive mixtures with air. Keep cool. Protect from sunlight.

#### 7.3. Specific end use(s)

Laboratory use Laboratory chemical



according to Regulation (EC) No 1907/2006

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 5 of 12

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	•	End of shift at end of workweek

# **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m³
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³
Worker DNEL,	long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DN	Consumer DNEL, long-term		systemic	319 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	26 mg/kg bw/day



according to Regulation (EC) No 1907/2006

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 6 of 12

PNEC values

CAS No	Substance	
Environment	al compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (	intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Freshwater s	sediment	3,6 mg/kg
Marine sedin	nent	2,9 mg/kg
Secondary p	oisoning	380 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (	intermittent releases)	140,9 mg/l
Marine wate	r	140,9 mg/l
Freshwater s	sediment	552 mg/kg
Marine sediment		552 mg/kg
Secondary p	oisoning	160 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	2251 mg/l
Soil		28 mg/kg

# 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles.

# Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 720 Camapren® Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).



# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 7 of 12

# Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

# Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Danger of explosion

### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and c	chemical properties	
Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Alcohol	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		not applicable
		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		39 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		easily soluble
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,9274 g/cm³
Bulk density:		No data available
Relative vapour density:		not determined
9.2. Other information		
Information with regard to physical h	nazard classes	
Explosive properties		
Vapours can form explosive mixtu	res with air.	
Sustaining combustion:		Sustaining combustion
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		
Not oxidising.		
Other safety characteristics		
Evaporation rate:		not determined
Solvent separation test:		No data available
Solvent content:		No data available
Solid content:		No data available
Sublimation point:		No data available
······································		



# ere also a in a fact flatial as a sudia a fa D) ( 0007, showfor 0

Screen cle	Screen cleaning test fluid according to PV 2037, chapter 3.2.3						
Revision date: 02.03.2023	Product code: 16776	Page 8 of 12					
Softening point:	No data available						
Pour point: No data available:	No data available						
Viscosity / dynamic:	No data available						
Flow time:	No data available						
Further Information							

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

Oxidising agent

# 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

Plastic articles

Rubber articles

## 10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

## Further information

No data available

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name								
	Exposure route	Dose		Species	Source		Method			
64-17-5	ethanol									
	oral	LD50 mg/kg	10470	Rat	Study rep	ort (1976)	OECD Guideline 401			
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study rep	ort (1980)	OECD Guideline 403			

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 9 of 12

#### STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

## 11.2. Information on other hazards

#### Other information

Irritant Dizziness The product causes narcotic-like effects. Inebriation Vomiting

#### **Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

# **SECTION 12: Ecological information**

# 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
64-17-5	ethanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a		
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol								
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203		

# 12.2. Persistence and degradability

There are no data available on the mixture itself.



# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023

Product code: 16776

Page 10 of 12

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

		4
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
64-17-5	ethanol	-0,77
CAS No	Chemical name	Log Pow

#### BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# The product has not been tested.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

There are no data available on the mixture itself.

#### **Further information**

Avoid release to the environment.

Do not empty into drains.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### **Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

_,		
	14.1. UN number or ID number:	UN 1987
	14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (ethanol, propan-2-ol; isopropyl alcohol; isopropanol)
	14.3. Transport hazard class(es):	3
	14.4. Packing group:	III
	Hazard label:	3
	Classification code:	F1
	Special Provisions:	274 601
	Limited quantity:	5 L
	Excepted quantity:	E1
	Transport category:	3
	Hazard No:	30
	Tunnel restriction code:	D/E



# Screen cleaning test fluid according to PV 2037, chapter 3.2.3

Revision date: 02.03.2023	Product code: 16776	j	Page 11 of 12
nland waterways transport (ADN)			
14.1. UN number or ID number:	UN 1987		
14.2. UN proper shipping name:	•	propan-2-ol; isopropyl alcohol; isopro	panol)
14.3. Transport hazard class(es):	3		
14.4. Packing group:	III		
Hazard label:	3		
Classification code:	F1		
Special Provisions:	274 601		
Limited quantity:	5 L		
Excepted quantity:	E1		
Marine transport (IMDG)			
14.1. UN number or ID number:	UN 1987		
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (ethanol,	propan-2-ol)	
14.3. Transport hazard class(es):	3		
14.4. Packing group:	III		
Hazard label:	3		
Special Provisions:	223, 274		
Limited quantity:	5 L		
Excepted quantity:	E1		
EmS:	F-E, S-D		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 1987		
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (ethanol,	propan-2-ol)	
14.3. Transport hazard class(es):	3	,	
14.4. Packing group:	111		
Hazard label:	3		
Special Provisions:	A3 A180		
Limited quantity Passenger:	10 L		
Passenger LQ:	Y344		
Excepted quantity:	E1		
IATA-packing instructions - Passenger:	355		
IATA-max. quantity - Passenger:	60 L		
IATA-packing instructions - Cargo:	366		
IATA-max. quantity - Cargo:	220 L		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user			
Warning: Combustible liquid.			
<b>c</b> .	. INO instruments		
14.7. Maritime transport in bulk according t	<u>o mo instruments</u>		
not applicable			
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regu	lations/legislation specific for t	he substance or mixture	
EU regulatory information			
Restrictions on use (REACH, annex XVII)			
Entry 3, Entry 40			

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS (SEVESO III):

# National regulatory information



Screen cleaning test fluid according to PV 2037, chapter 3.2.3			
Revision date: 02.03.2023	Product code: 16776	Page 12 of 12	
Employment restrictions:	Observe restrictions to employment for juveniles accord work protection guideline' (94/33/EC). Observe employn under the Maternity Protection Directive (92/85/EEC) for nursing mothers.	nent restrictions	
Water hazard class (D):	1 - slightly hazardous to water		

# **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)