

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluoro

Revision date: 05.04.2024

Product code: 17798

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluoro

UFI: W29K-D1DE-M00X-0YVF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Skin Irrit. 2; H315

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Calcium nitrate tetrahydrate

nitric acid

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 2 of 17

Hazard statements

H290 May be corrosive to metals.
H315 Causes skin irritation.
H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P390 Absorb spillage to prevent material damage.

Special labelling of certain mixtures

EUH208 Contains nickel dinitrate. May produce an allergic reaction.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name	EC No	Index No	REACH No	Quantity
		Classification (Regulation (EC) No 1272/2008)			
7697-37-2	nitric acid				1 - < 5 %
		231-714-2	007-030-00-3	01-2119487297-23	
		Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			
13477-34-4	Calcium nitrate tetrahydrate				1 - < 5 %
		233-332-1		01-2119495093-35	
		Ox. Sol. 3, Acute Tox. 4, Eye Dam. 1; H272 H302 H318			
7664-39-3	hydrofluoric acid ... %				< 0.01 %
		231-634-8	009-003-00-1		
		Acute Tox. 1, Acute Tox. 2, Acute Tox. 2, Skin Corr. 1A; H310 H330 H300 H314			
13138-45-9	nickel dinitrate				< 0.01 %
		236-068-5	028-012-00-1	01-2119492333-38	
		Ox. Sol. 2, Carc. 1A, Muta. 2, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H350i H341 H360D H332 H302 H315 H318 H334 H317 H372 H400 H410			
7761-88-8	silver nitrate				< 0.01 %
		231-853-9	047-001-00-2	01-2119513705-43	
		Ox. Sol. 2, Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H290 H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 3 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	1 - < 5 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
13477-34-4	233-332-1	Calcium nitrate tetrahydrate	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 300 - < 2000 mg/kg	
7664-39-3	231-634-8	hydrofluoric acid ... %	< 0.01 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: LC50 = 2240 ppm (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg Skin Corr. 1A; H314: >= 7 - 100 Skin Corr. 1B; H314: >= 1 - < 7 Eye Irrit. 2; H319: >= 0,1 - < 1	
13138-45-9	236-068-5	nickel dinitrate	< 0.01 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 361,9 mg/kg Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; H372: >= 1 - 100 STOT RE 2; H373: >= 0,1 - < 1 Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
7761-88-8	231-853-9	silver nitrate	< 0.01 %
		dermal: LD50 = > 348 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1000 Aquatic Chronic 1; H410: M=100	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.
Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 4 of 17

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 5 of 17

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment.
Provide adequate ventilation.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Further information on storage conditions

Unsuitable container/equipment material: Metal, Glass

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	
		3	2.5		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	
13494-80-9	Tellurium	-	0.1		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
7664-39-3	Hydrogen fluoride	Fluoride	2 mg/L	Urine	Prior to shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 6 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
13477-34-4	Calcium nitrate tetrahydrate			
Consumer DNEL, acute		oral	systemic	10 mg/kg bw/day
10043-35-3	boric acid			
Worker DNEL, long-term		inhalation	systemic	8,3 mg/m ³
Worker DNEL, long-term		dermal	systemic	392 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	4,15 mg/m ³
Consumer DNEL, long-term		dermal	systemic	196 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,98 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,98 mg/kg bw/day
7664-39-3	hydrofluoric acid ... %			
Worker DNEL, long-term		inhalation	systemic	1,5 mg/m ³
Worker DNEL, acute		inhalation	systemic	2,5 mg/m ³
Worker DNEL, long-term		inhalation	local	1,5 mg/m ³
Worker DNEL, acute		inhalation	local	2,5 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,03 mg/m ³
Consumer DNEL, acute		inhalation	systemic	0,03 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,2 mg/m ³
Consumer DNEL, acute		inhalation	local	1,25 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,01 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,01 mg/kg bw/day
13138-45-9	nickel dinitrate			
Consumer DNEL, acute		oral	systemic	0,012 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	104 mg/m ³
Worker DNEL, acute		inhalation	local	1,6 mg/m ³
Consumer DNEL, acute		inhalation	systemic	8,8 mg/m ³
Consumer DNEL, acute		inhalation	local	0,1 mg/m ³
7761-88-8	silver nitrate			
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,016 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,006 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 7 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		Value
13477-34-4	Calcium nitrate tetrahydrate	
Micro-organisms in sewage treatment plants (STP)		18 mg/l
10043-35-3	boric acid	
Freshwater		2,9 mg/l
Freshwater (intermittent releases)		13,7 mg/l
Marine water		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		5,7 mg/kg
7664-39-3	hydrofluoric acid ... %	
Freshwater		0,89 mg/l
Marine water		0,089 mg/l
Freshwater sediment		3,38 mg/kg
Marine sediment		0,338 mg/kg
Micro-organisms in sewage treatment plants (STP)		51 mg/l
Soil		10,6 mg/kg
13138-45-9	nickel dinitrate	
Freshwater		0,0071 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sediment		109 mg/kg
Secondary poisoning		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,33 mg/l
Soil		29,9 mg/kg
7761-88-8	silver nitrate	
Freshwater		0,00004 mg/l
Marine water		0,00086 mg/l
Freshwater sediment		438,13 mg/kg
Marine sediment		438,13 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,025 mg/l
Soil		1,41 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

Face protection shield

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 8 of 17

goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Suitable material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Suitable material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.
Protective clothing acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 9 of 17

Water solubility:	No data available
Solubility in other solvents not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
No data available	

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

Corrosive to metals

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluoro

Revision date: 05.04.2024

Product code: 17798

Page 10 of 17

10.6. Hazardous decomposition products

In case of fire may be liberated:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
13477-34-4	Calcium nitrate tetrahydrate				
	oral	LD50 > 300 - < 2000 mg/kg	Rat	Study report (2010)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402
7664-39-3	hydrofluoric acid ... %				
	oral	ATE 5 mg/kg			
	dermal	ATE 5 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
	inhalation (1 h) gas	LC50 2240 ppm	Rat	Study report (1990)	OECD Guideline 403
13138-45-9	nickel dinitrate				
	oral	LD50 361,9 mg/kg	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
7761-88-8	silver nitrate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 > 348 mg/kg	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434

Irritation and corrosivity

Causes skin irritation.
Causes serious eye damage.

Sensitising effects

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 11 of 17

Based on available data, the classification criteria are not met.
Contains nickel dinitrate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

Irritant

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008) OECD Guideline 209
13477-34-4	Calcium nitrate tetrahydrate					
	Acute fish toxicity	LC50 mg/l	1378	96 h	Poecilia reticulata	Water res. 11(10):927-935 (1977) OECD Guideline 203
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
7664-39-3	hydrofluoric acid ... %					
	Acute fish toxicity	LC50	299 mg/l	96 h	Salmo trutta	REACH Registration Dossier other: U.S Environmental Protection Agen
	Acute algae toxicity	ErC50	43 mg/l	96 h	various algae species	REACH Registration Dossier Methods not detailed in the review.
	Crustacea toxicity	NOEC	3,7 mg/l	21 d	Daphnia magna	REACH Registration Dossier The publication is a review article of v
	Acute bacteria toxicity	EC50 mg/l ()	2930	3 h	Activated sludge	REACH Registration Dossier ISO 8192
13138-45-9	nickel dinitrate					
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003) other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004) other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2 other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990) Chronic exposure to sublethal concentrat

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluoro"

Revision date: 05.04.2024

Product code: 17798

Page 13 of 17

	Acute bacteria toxicity	EC50)	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192
7761-88-8	silver nitrate						
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry.	A guideline was not specified. The test
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	Environmental Science and Technology. 44	eline: U.S. Environmental Protection Agency
	Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry.	The protective effect of reactive sulphur
	Fish toxicity	NOEC > 0,00125 mg/l		73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
	Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days for th
	Crustacea toxicity	NOEC mg/l	0,00031	20 d	Isonychia bicolor	Environmental Toxicology and Chemistry.	20 day sublethal effects on representati

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
7664-39-3	hydrofluoric acid ... %	53 - 58	not specified	REACH Registration D
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 14 of 17

Do not empty into drains.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 15 of 17

IATA-packing instructions - Cargo:

856

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 27, Entry 30, Entry 75

Information according to Directive

Not subject to 2012/18/EU (SEVESO III)

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 16 of 17

Abbreviations and acronyms

Pyr. Sol: Pyrophoric solid
 Water-react: Substance and mixture which, in contact with water, emits flammable gas
 Ox. Liq: Oxidising liquid
 Ox. Sol: Oxidising solid
 Met. Corr: Substance or mixture corrosive to metals
 Flam. Sol: Flammable solid
 Acute Tox: Acute toxicity
 Skin Corr: Skin corrosion
 Skin Irrit: Skin irritation
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 Resp. Sens: Respiratory sensitisation
 Skin Sens: Skin sensitisation
 Muta: Germ cell mutagenicity
 Carc: Carcinogenicity
 Repr: Reproductive toxicity
 STOT SE: Specific target organ toxicity - single exposure
 STOT RE: Specific target organ toxicity - repeated exposure
 Aquatic Acute: Acute aquatic hazard
 Aquatic Chronic: Chronic aquatic hazard
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H272 May intensify fire; oxidiser.
 H290 May be corrosive to metals.
 H300 Fatal if swallowed.
 H302 Harmful if swallowed.
 H310 Fatal in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H330 Fatal if inhaled.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H341 Suspected of causing genetic defects.
 H350i May cause cancer by inhalation.
 H360D May damage the unborn child.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

"Multi element standard solution ""Varian 1"" 25 elements in nitric acid 2 % + 0.1 ml/l of hydrofluo

Revision date: 05.04.2024

Product code: 17798

Page 17 of 17

H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains nickel dinitrate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)