

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt

Revision date: 24.11.2022

Product code: 17908

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Acute Tox. 4; H332

Skin Corr. 1B; H314

Eye Dam. 1; H318

STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

acetic acid

4-methylpentan-2-one

Signal word: Danger

###### Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 2 of 13

**Hazard statements**

- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-19-7	acetic acid			55 - < 60 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A; H226 H314			
108-10-1	4-methylpentan-2-one			40 - < 45 %
	203-550-1	606-004-00-4	01-2119473980-30	
	Flam. Liq. 2, Carc. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H225 H351 H332 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-19-7	200-580-7	acetic acid	55 - < 60 %
	inhalation: LC50 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25		
108-10-1	203-550-1	4-methylpentan-2-one	40 - < 45 %
	inhalation: ATE 11 mg/l (vapours)		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 3 of 13

**General information**

Self-protection of the first aider

**After inhalation**

Provide fresh air.

Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting

Circulatory collapse

Corneal opacity.

Risk of serious damage to eyes.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Acetic acid-vapour

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 4 of 13

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up**

**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 5 of 13

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Further information on storage conditions**

storage temperature +15°C - +25°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	
108-10-1	Methyl isobutyl ketone (MIBK)	20	83		TWA (8 h)	
		50	208		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	Methyl isobutyl ketone (MIBK); 4-methylpentan-2-one)	MIBK	1 mg/L	Urine	End of shift

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 6 of 13

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64-19-7	acetic acid		
Worker DNEL, long-term	inhalation	local	25 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	25 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	25 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	25 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one		
Worker DNEL, long-term	inhalation	systemic	83 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	208 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	83 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	208 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	11,8 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	14,7 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	155,2 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	14,7 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	155,2 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4,2 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
64-19-7	acetic acid	
Freshwater	3,058 mg/l	
Freshwater (intermittent releases)	30,58 mg/l	
Marine water	0,306 mg/l	
Freshwater sediment	11,36 mg/kg	
Marine sediment	1,136 mg/kg	
Micro-organisms in sewage treatment plants (STP)	85 mg/l	
Soil	0,47 mg/kg	
108-10-1	4-methylpentan-2-one	
Freshwater	0,6 mg/l	
Freshwater (intermittent releases)	1,5 mg/l	
Marine water	0,06 mg/l	
Freshwater sediment	8,27 mg/kg	
Marine sediment	0,83 mg/kg	
Micro-organisms in sewage treatment plants (STP)	27,5 mg/l	
Soil	1,3 mg/kg	

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 7 of 13

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

- goggles
- Face protection umbrella

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

- Trade name/designation: KCL 897 Butoject®
- Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm
- Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

- Take off immediately all contaminated clothing and wash it before reuse.
- Wear fire resistant or flame retardant clothing.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Draw up and observe skin protection programme.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**Environmental exposure controls**

- Do not allow to enter into surface water or drains.
- Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
- Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability		
Solid/liquid:		No data available
Gas:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		~40 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 8 of 13

Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,92649 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

**Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

**Self-ignition temperature**

Solid: No data available

Gas: No data available

**Oxidizing properties**

No data available

**Other safety characteristics**

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

: No data available

Viscosity / dynamic: No data available

Flow time: No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

In case of warming: Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent  
peroxides, for example hydrogen peroxide  
permanganates, e.g. potassium permanganate  
Oxidising agent, strong

Metal

iron and steel

Zinc

Alkali (lye)

aldehydes

Alcohols

Nitric acid



**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 9 of 13

**10.4. Conditions to avoid**

storage temperature < 17 °C

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Metal

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Harmful if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

**ATEmix calculated**

ATE (inhalation dust/mist) 3,444 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-19-7	acetic acid				
	oral	LD50 3310 mg/kg	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194)	The sodium salt of acetic acid was admin
	inhalation (4 h) vapour	LC50 11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403
108-10-1	4-methylpentan-2-one				
	inhalation vapour	ATE 11 mg/l			

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 10 of 13

**11.2. Information on other hazards**

**Other information**

Irritant  
corrosive  
Dyspnoea  
Gastrointestinal complaints  
Vomiting  
Circulatory collapse  
Corneal opacity.  
Risk of serious damage to eyes.

**Further information**

kidneys

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-19-7	acetic acid					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (2005) other: SOP E257
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Skeletonema costatum	Study report (2005) ISO 10253
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1990) OECD Guideline 202
108-10-1	4-methylpentan-2-one					
	Acute fish toxicity	LC50 mg/l	> 179	96 h	Danio rerio	Study report (2010) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	> 200	48 h	Daphnia magna	Study report (2009) OECD Guideline 202
	Crustacea toxicity	NOEC	78 mg/l	21 d	Daphnia magna	Grey literature (1988) other: "Vorläufigen Testverfahrensvorsch

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17
108-10-1	4-methylpentan-2-one	1,9

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 11 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.  
There are no data available on the mixture itself.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.  
Avoid release to the environment.

**Further information**

There are no data available on the mixture itself.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2920
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, 4-methylpentan-2-one)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	83
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2920
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, 4-methylpentan-2-one)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 2920
--------------------------------------	---------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Eisessig/Isobutylmethylketon Gemisch zur Analyse volumetrisch 50:50 gemischt**

Revision date: 24.11.2022

Product code: 17908

Page 12 of 13

**14.2. UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, 4-methylpentan-2-one)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
 Hazard label: 8+3  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 2920  
**14.2. UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, 4-methylpentan-2-one)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
 Hazard label: 8+3  
 Limited quantity Passenger: 0.5 L  
 Passenger LQ: Y840  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 851  
 IATA-max. quantity - Passenger: 1 L  
 IATA-packing instructions - Cargo: 855  
 IATA-max. quantity - Cargo: 30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information**

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Eisessig/Isobutylmethyleton Gemisch zur Analyse volumetrisch 50:50 gemischt

Revision date: 24.11.2022

Product code: 17908

Page 13 of 13

H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*