Print date: 24.11.2022



Safety Data Sheet

according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

UFI: G1NM-V1WJ-D00X-FWU0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household). No data available

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephoneFor Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,number:Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word: Warning

Pictograms:



Hazard statements

H290 May be corrosive to metals.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Print date: 24.11.2022



Safety Data Sheet

according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 2 of 10

Precautionary statements

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P390 Absorb spillage to prevent material damage.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP	Regulation)		
1310-73-2	sodium hydroxide			< 1 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
1310-73-2	215-185-5	sodium hydroxide	< 1 %
	Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.

Wash immediately with: Water

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Print date: 24.11.2022



Safety Data Sheet

according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 3 of 10

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

No special environmental measures are necessary.

6.3. Methods and material for containment and cleaning up

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 4 of 10

7.1. Precautions for safe handling

Advice on safe handling

Read label before use.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Unsuitable container/equipment material:

Metal

Aluminium

Tin

Zinc

Hints on joint storage

national regulations

Further information on storage conditions

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1310-73-2	sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m³
Consumer DNEL, long-term		inhalation	local	1 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 5 of 10

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.
Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: P2

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: odourless
Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

No data available

boiling range: Flammability

Solid/liquid: not applicable
Gas: not applicable
Lower explosion limits: not applicable
Upper explosion limits: not applicable



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 6 of 10

Flash point: X

Auto-ignition temperature: not applicable Decomposition temperature: No data available

pH-Value: 12,6
Viscosity / kinematic: No data available

Water solubility: very soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Paluk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not applicable

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

not determined:

Viscosity / dynamic:

No data available

No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Light metal

Ammonia (NH3)

Metal

Acid

10.4. Conditions to avoid

No data available



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 7 of 10

10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	sodium hydroxide					
	Acute crustacea toxicity	EC50 40,4 mg/l	48 1		Environmental	other: acute 48-h immobilization test ac

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Harmful effect due to pH shift.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	JN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es): 8 14.4. Packing group: Ш Hazard label: 8 Classification code: C5 Limited quantity: 5 I Excepted quantity: F1 Transport category: 3 Hazard No: 80 Tunnel restriction code: Ε

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es): 8
14.4. Packing group: | | | |



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 9 of 10

Hazard label: 8
Classification code: C5
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:223Limited quantity:5 LExcepted quantity:E1EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 LPassenger LQ:Y841Excepted quantity:E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to 2012/18/EU

Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): - - non-hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.



according to UK REACH Regulation

Reinigungslösung -regulär- für Silikat-Analysator ABB Typ Navigator 600

Revision date: 24.11.2022 Product code: 18287 Page 10 of 10

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation. H319 Causes serious eye irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)