

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Formaldehyde solution 30 % pure stabilized with methanol

UFI: 4FCN-0125-C004-40WU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Acute Tox. 3; H301

Acute Tox. 3; H311

Acute Tox. 3; H331

Skin Corr. 1B; H314

Eye Dam. 1; H318

Skin Sens. 1; H317

Muta. 2; H341

Carc. 1B; H350

STOT SE 2; H371

STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

formaldehyde

methanol

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 2 of 15

Signal word: Danger

Pictograms:



Hazard statements

- H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H350 May cause cancer.
- H371 May cause damage to organs.

Precautionary statements

- P201 Obtain special instructions before use.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
50-00-0	formaldehyde			30 - < 35 %
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317			
67-56-1	methanol			5 - < 10 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
50-00-0	200-001-8	formaldehyde	30 - < 35 %
		inhalation: LC50 = < 463 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 460 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100	
67-56-1	200-659-6	methanol	5 - < 10 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Allergic reactions

Dyspnoea

Cough

Inebriation

Dizziness

Headache

Dizziness

Agitation

Headache

Spasms

Impairment of vision

Anaesthetic state

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 4 of 15

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO_x)

Carbon dioxide (CO₂) Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 5 of 15

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol.

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Store in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Protect against: Light

Unsuitable container/equipment material: Metal

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed. Keep container dry.

Keep cool. Protect from sunlight.

storage temperature +15°C - +25°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 6 of 15

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
50-00-0	formaldehyde			
Worker DNEL, long-term		inhalation	systemic	9 mg/m ³
Worker DNEL, long-term		inhalation	local	0,375 mg/m ³
Worker DNEL, long-term		dermal	systemic	240 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	3,2 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,1 mg/m ³
Consumer DNEL, long-term		dermal	systemic	102 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,1 mg/kg bw/day
Worker DNEL, acute		inhalation	local	0,75 mg/m ³
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 7 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
50-00-0	formaldehyde	
Freshwater		0,44 mg/l
Freshwater (intermittent releases)		4,44 mg/l
Marine water		0,44 mg/l
Freshwater sediment		2,3 mg/kg
Marine sediment		2,3 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,19 mg/l
Soil		0,2 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles
Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®
Recommended material: FKM (fluoro rubber) 0,7 mm
Wearing time with occasional contact (splashes): > 145 min

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wear fire resistant or flame retardant clothing.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation
Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains.
Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability		
Solid/liquid:		No data available
Gas:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		4,4
Viscosity / kinematic:		No data available
Water solubility:		Soluble in: Water
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,07279 g/cm ³
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

9.2. Other information

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 9 of 15

Information with regard to physical hazard classes

Explosive properties

Danger of dust explosion.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

:

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reducing agent

Danger of polymerisation

In case of warming: Vapours can form explosive mixtures with air.

10.2. Chemical stability

Protect against: Light

Contains as stabilizer(s): Methanol

10.3. Possibility of hazardous reactions

Acids

Phenol

Nitric acid

Hydrogen peroxide

Alkali (lye)

permanganates, e.g. potassium permanganate

Oxidising agent

Hydrochloric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against:

Light

10.5. Incompatible materials

metals

Steel

Copper

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 10 of 15

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

ATEmix calculated

ATE (oral) 251,7 mg/kg; ATE (dermal) 755,1 mg/kg; ATE (inhalation vapour) 7,55 mg/l; ATE (inhalation dust/mist) 1,259 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
50-00-0	formaldehyde				
	oral	LD50 460 mg/kg	Rat	Kefo J Med 24: 19-37 (1975)	OECD Guideline 401
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 < 463 mg/l	Rat	Study report (2015)	OECD Guideline 403
	inhalation dust/mist	ATE 0,5 mg/l			
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Causes tears.

Sensitising effects

May cause an allergic skin reaction. (formaldehyde)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 11 of 15

STOT-single exposure

May cause damage to organs. (methanol)
May cause respiratory irritation. (formaldehyde)
Liver and kidney damage
heart
eyes

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Irritant
corrosive
Allergic reactions
Dyspnoea
Cough
Inebriation
Dizziness
Headache
Dizziness
Agitation
Headache
Spasms
Impairment of vision
Anaesthetic state
Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to UK REACH Regulation

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 12 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
50-00-0	formaldehyde					
	Acute fish toxicity	LC50 mg/l	27,57	96 h	Ictalurus punctatus	Prog.Fish-Cult. 20(1):8-15 (1958) acute toxicity test; "static bioassay"
	Acute algae toxicity	ErC50 mg/l	3,48	72 h	Desmodesmus subspicatus	Ecotoxicol Environ Safety 54: 346-354 (2) OECD Guideline 201
	Acute crustacea toxicity	EC50	5,8 mg/l	48 h	Daphnia pulex	Water, Air and Soil Pollution 97, 315-32 OECD Guideline 202
	Fish toxicity	NOEC mg/l	>= 48	28 d	Oryzias latipes	NTIS (ed.) Compendium of the FY1988 and OECD Guideline 215
	Crustacea toxicity	NOEC mg/l	>= 6,4	21 d	Daphnia magna	Study report (2008) OECD Guideline 211
	Acute bacteria toxicity	(EC50	19 mg/l)	3 h	Activated sludge	Chemosphere 14, 1239-1251 (1985) OECD Guideline 209
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 mg/l	ca. 22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7 OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989) other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research, Calculation performed with ECOSAR
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013) Toxicity of the target chemical is predi

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
50-00-0	formaldehyde	0,35
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
50-00-0	formaldehyde	< 1	Paralichthys olivaceus and Sebastes schlegeli	Aquaculture 194, 253
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 13 of 15

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No data available

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Forms corrosive mixtures with water even if diluted.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2209
14.2. UN proper shipping name:	FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C9
Special Provisions:	533
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2209
14.2. UN proper shipping name:	FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C9
Special Provisions:	533
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2209
14.2. UN proper shipping name:	FORMALDEHYDE SOLUTION

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 14 of 15

14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8
 Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2209
14.2. UN proper shipping name: FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8
 Special Provisions: A803
 Limited quantity Passenger: 1 L
 Passenger LQ: Y841
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 852
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 856
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 69, Entry 75

Information according to 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.

Formaldehyde solution 30 % pure stabilized with methanol

Revision date: 15.09.2022

Product code: 18548

Page 15 of 15

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 2; H371	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H370	Causes damage to organs.
H371	May cause damage to organs.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)