

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Acute Tox. 4; H332 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Carc. 2; H351 STOT RE 2; H373 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Fuels, diesel, No 2

Signal word: Danger

Pictograms:









Print date: 15.03.2023



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 2 of 10

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68476-34-6	Fuels, diesel, No 2			95 - < 100 %
	270-676-1	649-227-00-2	01-2119484664-27	
	Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68476-34-6	270-676-1	Fuels, diesel, No 2	95 - < 100 %
	inhalation: ATE	= 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 3 of 10

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2), Carbon monoxide

Acetic acid vapour

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 4 of 10

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

In case of warming: Vapours may form explosive mixtures with air.

7.3. Specific end use(s)

Laboratory chemicals



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 5 of 10

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L Suitable material: NBR (Nitrile rubber) 0.11 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: light yellow
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

300 °C

boiling range:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 6 of 10

No data available Flammability: Lower explosion limits: No data available Upper explosion limits: No data available Flash point: 60 °C Auto-ignition temperature: 250 °C Decomposition temperature: No data available pH-Value: No data available Viscosity / kinematic: No data available completely miscible Water solubility:

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

0,8284 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available Solid content: No data available No data available Sublimation point: Softening point: No data available Pour point: No data available No data available No data available Viscosity / dynamic: Flow time: No data available

Further Information

May be corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

peroxides, for example hydrogen peroxide



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 7 of 10

permanganates, e.g. potassium permanganate

Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (inhalation vapour) 11,58 mg/l; ATE (inhalation dust/mist) 1,579 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68476-34-6	Fuels, diesel, No 2				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Fuels, diesel, No 2)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking. May cause damage to organs through prolonged or repeated exposure. (Fuels, diesel, No 2)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 8 of 10

Other information

Irritant

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1202
14.2. UN proper shipping name:	DIESEL FUEL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1

Special Provisions: 640K ADR664

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 9 of 10

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 120214.2. UN proper shipping name:DIESEL FUEL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Special Provisions:640KLimited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number:UN 120214.2. UN proper shipping name:DIESEL FUEL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:-Limited quantity:5 LExcepted quantity:E1EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: DIESEL FUEL

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:A3Limited quantity Passenger:10 LPassenger LQ:Y344Excepted quantity:E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Diesel fuel

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU

(SEVESO III):

E2 Hazardous to the Aquatic Environment

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 15.03.2023 Product code: 18747 Page 10 of 10

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Carc. 2; H351	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid	and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)