

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|----------------------------------|------------------------------|
| Company name: | AnalytiChem GmbH | |
| | ACD | |
| Street: | Stempelstraße 6 | |
| Place: | D-47167 Duisburg | |
| Telephone: | 0203/5194-0 | Telefax: 0203/5194-290 |
| E-mail: | info@analytichem.de | |
| Contact person: | Abteilung Produktsicherheit | Telephone: 0203/5194-107/117 |
| E-mail: | produktsicherheit@analytichem.de | |
| Internet: | www.analytichem.de | |
| Responsible Department: | Abteilung Produktsicherheit | |

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Acute Tox. 4; H332

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Carc. 2; H351

STOT RE 2; H373

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Fuels, diesel, No 2

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 2 of 11

Pictograms:



Hazard statements

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------|---|
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |
| P391 | Collect spillage. |

Special labelling of certain mixtures

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|------------|---|--------------|------------------|--------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 68476-34-6 | Fuels, diesel, No 2 | | | 95 - < 100 % |
| | 270-676-1 | 649-227-00-2 | 01-2119484664-27 | |
| | Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|--|---------------------|--------------|
| | Specific Conc. Limits, M-factors and ATE | | |
| 68476-34-6 | 270-676-1 | Fuels, diesel, No 2 | 95 - < 100 % |
| | inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists) | | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 3 of 11

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO₂), Carbon monoxide

Acetic acid vapour

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators,

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 4 of 11

and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 5 of 11

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

In case of warming: Vapours may form explosive mixtures with air.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Suitable material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 6 of 11

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------|
| Physical state: | Liquid |
| Colour: | light yellow |
| Odour: | characteristic |
| Melting point/freezing point: | No data available |
| Boiling point or initial boiling point and boiling range: | 300 °C |
| Flammability: | No data available |
| Lower explosion limits: | No data available |
| Upper explosion limits: | No data available |
| Flash point: | 60 °C |
| Auto-ignition temperature: | 250 °C |
| Decomposition temperature: | No data available |
| pH-Value: | No data available |
| Viscosity / kinematic: | No data available |
| Water solubility: | completely miscible |
| Solubility in other solvents | No data available |
| Partition coefficient n-octanol/water: | No data available |
| Vapour pressure: | No data available |
| Vapour pressure: | No data available |
| Density: | 0,8284 g/cm ³ |
| Bulk density: | No data available |
| Relative vapour density: | No data available |

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

| | |
|--------------------------|-------------------|
| Evaporation rate: | No data available |
| Solvent separation test: | No data available |
| Solvent content: | No data available |
| Solid content: | No data available |
| Sublimation point: | No data available |
| Softening point: | No data available |
| Pour point: | No data available |
| Viscosity / dynamic: | No data available |

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 7 of 11

Flow time:

No data available

Further Information

May be corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent
peroxides, for example hydrogen peroxide
permanganates, e.g. potassium permanganate
Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 11,58 mg/l; ATE (inhalation dust/mist) 1,579 mg/l

| CAS No | Chemical name | | | | |
|------------|----------------------|--------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 68476-34-6 | Fuels, diesel, No 2 | | | | |
| | inhalation vapour | ATE 11 mg/l | | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Fuels, diesel, No 2)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 8 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Fuels, diesel, No 2)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

Irritant

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 9 of 11

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|-------------|
| 14.1. UN number or ID number: | UN 1202 |
| 14.2. UN proper shipping name: | DIESEL FUEL |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3 |
| Classification code: | F1 |
| Special Provisions: | 640K ADR664 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 30 |
| Tunnel restriction code: | D/E |

Inland waterways transport (ADN)

| | |
|--|-------------|
| 14.1. UN number or ID number: | UN 1202 |
| 14.2. UN proper shipping name: | DIESEL FUEL |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3 |
| Classification code: | F1 |
| Special Provisions: | 640K |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |

Marine transport (IMDG)

| | |
|--|-------------|
| 14.1. UN number or ID number: | UN 1202 |
| 14.2. UN proper shipping name: | DIESEL FUEL |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3 |
| Special Provisions: | - |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| EmS: | F-E, S-E |

Air transport (ICAO-TI/IATA-DGR)

| | |
|--|-------------|
| 14.1. UN number or ID number: | UN 1202 |
| 14.2. UN proper shipping name: | DIESEL FUEL |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3 |
| Special Provisions: | A3 |
| Limited quantity Passenger: | 10 L |
| Passenger LQ: | Y344 |
| Excepted quantity: | E1 |
| IATA-packing instructions - Passenger: | 355 |
| IATA-max. quantity - Passenger: | 60 L |
| IATA-packing instructions - Cargo: | 366 |
| IATA-max. quantity - Cargo: | 220 L |

14.5. Environmental hazards

| | |
|-----------------------------|-------------|
| ENVIRONMENTALLY HAZARDOUS: | Yes |
| Danger releasing substance: | Diesel fuel |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 10 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

Additional information:

P5c

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Carc: Carcinogenicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| Acute Tox. 4; H332 | Calculation method |
| Asp. Tox. 1; H304 | Calculation method |
| Skin Irrit. 2; H315 | Calculation method |
| Carc. 2; H351 | Calculation method |
| STOT RE 2; H373 | Calculation method |
| Aquatic Chronic 2; H411 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fuel for diesel engine application according to GMW14914 valid for GM Europe (GME)

Revision date: 05.03.2025

Product code: 18747

Page 11 of 11

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.
The receiver of our product is singularly responsible for adhering to existing laws and regulations.
Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)