

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Butanol 99 - 100 % for analysis

Revision date: 12.07.2023

Product code: 19146

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

2-Butanol 99 - 100 % for analysis

REACH Registration Number: 01-2119475146-36-XXXX  
CAS No: 78-92-2  
Index No: 603-127-00-5  
EC No: 201-158-5

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit  
Telefax: 0203/5194-290  
Telephone: 0203/5194-107/117

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

No data available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 3; H226  
Eye Irrit. 2; H319  
STOT SE 3; H335  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Butanol 99 - 100 % for analysis

Revision date: 12.07.2023

Product code: 19146

Page 2 of 11

#### Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Sum formula:	CH <sub>3</sub> CH(OH)CH <sub>2</sub> CH <sub>3</sub>
Molecular weight:	74,12 g/mol

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
78-92-2	butanol			100 %
	201-158-5	603-127-00-5	01-2119475146-36-	
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, STOT SE 3; H226 H319 H335 H336			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
78-92-2	201-158-5	butanol	100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 2054 mg/kg		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

No data available

##### After inhalation

Provide fresh air.  
Call a doctor if you feel unwell.

##### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Butanol 99 - 100 % for analysis

Revision date: 12.07.2023

Product code: 19146

Page 3 of 11

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.  
Give sodium sulfate as laxative (1 tablespoon in 1 glass of water).

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant  
Cough  
Dyspnoea  
Anaesthetic state  
Vapours may cause drowsiness and dizziness.  
Dizziness

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>)  
Foam  
Extinguishing powder

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
In case of warming:  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Butanol 99 - 100 % for analysis

Revision date: 12.07.2023

Product code: 19146

Page 4 of 11

#### For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
- Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe vapour/aerosol. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- Wash hands and face before breaks and after work and take a shower if necessary.
- When using do not eat or drink.
- Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

#### Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 5 of 11

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.  
Store in a cool dry place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Unsuitable container/equipment material: Light metal

**Further information on storage conditions**

Protect from sunlight.  
minimum storage temperature +5°C  
maximum storage temperature +30°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
78-92-2	Butan-2-ol	100	300		TWA (8 h)	
		150	450		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
78-92-2	butanol			
Worker DNEL, long-term		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	405 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	213 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	203 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	15 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
78-92-2	butanol	
Environmental compartment		
Freshwater		47,1 mg/l
Freshwater (intermittent releases)		47,1 mg/l
Marine water		47,1 mg/l
Freshwater sediment		196,19 mg/kg
Marine sediment		196,19 mg/kg
Secondary poisoning		1000 mg/kg
Micro-organisms in sewage treatment plants (STP)		761 mg/l
Soil		11,58 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 6 of 11

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

- goggles
- Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

- Trade name/designation: KCL 730 Camatril® Velours
- Suitable material: NBR (Nitrile rubber) 0,4 mm
- Wearing time with permanent contact: > 480 min

By short-term hand contact

- Trade name/designation: KCL 720 Camapren®
- Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm
- Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

- Wear fire resistant or flame retardant clothing.
- Take off immediately all contaminated clothing and wash it before reuse.
- Wear suitable protective clothing. Take off immediately all contaminated clothing.
- Wash hands and face before breaks and after work and take a shower if necessary.

**Respiratory protection**

- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Filtering device with filter or ventilator filtering device of type: A

**Environmental exposure controls**

- Do not allow to enter into surface water or drains.
- Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
- Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Alcohol	
Odour threshold:	No data available	
Melting point/freezing point:		-115 °C
Boiling point or initial boiling point and boiling range:		99,5 °C
Flammability:		No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Butanol 99 - 100 % for analysis

Revision date: 12.07.2023

Product code: 19146

Page 7 of 11

Lower explosion limits:	1,4 vol. %
Upper explosion limits:	9,8 vol. %
Flash point:	24 °C
Auto-ignition temperature:	390 °C
Decomposition temperature:	No data available
pH-Value (at 20 °C):	neutral
Viscosity / kinematic:	No data available
Water solubility: (at 20 °C)	125 g/L
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	16,7 hPa
Vapour pressure:	No data available
Density:	0,81 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

###### Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

##### Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

4,21 mPa·s

(at 20 °C)

Flow time:

No data available

##### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 8 of 11

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent  
Alkali metals  
Alkaline earth metal,  
Acid chlorides, inorganic  
Reducing agent  
Aluminium

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-92-2	butanol				
	oral	LD50 mg/kg 2054	Rat	Study report (1986)	OECD Guideline 423
	dermal	LD50 mg/kg > 2000	Rat	Study report (1986)	OECD Guideline 402

**Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (butanol)

May cause drowsiness or dizziness. (butanol)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No data available



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 9 of 11

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

Irritant

Cough

Dyspnoea

Anaesthetic state

Vapours may cause drowsiness and dizziness.

Dizziness

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Further information**

No data available

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
78-92-2	butanol					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	Study report (1998) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	2029	96 h	Pseudokirchneriella subcapitata	Study report (1998) OECD Guideline 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	Study report (1998) OECD Guideline 202

**12.2. Persistence and degradability**

98 %; 5 d

Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
78-92-2	butanol	0,65

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 10 of 11

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1120
<b>14.2. UN proper shipping name:</b>	BUTANOLS
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1120
<b>14.2. UN proper shipping name:</b>	BUTANOLS
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1120
<b>14.2. UN proper shipping name:</b>	BUTANOLS
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Special Provisions:	223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1120
<b>14.2. UN proper shipping name:</b>	BUTANOLS
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**2-Butanol 99 - 100 % for analysis**

Revision date: 12.07.2023

Product code: 19146

Page 11 of 11

<b>14.4. Packing group:</b>	III	
Hazard label:	3	
Special Provisions:	A3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 9,12.

**Abbreviations and acronyms**

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.