

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

UFI: WS8R-F15S-J00R-04XQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household). No data available

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H290 May be corrosive to metals.

Precautionary statements

P234 Keep only in original packaging.
P390 Absorb spillage to prevent material damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 2 of 10

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1310-73-2	sodium hydroxide			< 1 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1310-73-2	215-185-5	sodium hydroxide	< 1 %
	Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.

Wash immediately with: Water

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of eye irritation consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 3 of 10

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Avoid contact with skin, eyes and clothes.

Additional information

Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

No special environmental measures are necessary.

6.3. Methods and material for containment and cleaning up

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use.

Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 4 of 10

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Draw up and observe skin protection programme. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Unsuitable container/equipment material:

Metal

Aluminium

Tin

Zinc

Further information on storage conditions

Store in a dry place.

storage temperature: +15°C - +25°C.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1310-73-2	sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 5 of 10

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		X
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		12,7
Viscosity / kinematic:		not determined
Water solubility:		very soluble
Solubility in other solvents		
not determined		
Dissolution rate:		not determined
Partition coefficient n-octanol/water:		not determined
Dispersion stability:		not determined
Vapour pressure:		not determined
Vapour pressure:		not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 6 of 10

Density:	1,001 g/cm ³
Relative density:	not determined
Bulk density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
not determined:	
Viscosity / dynamic:	not determined
Flow time:	not determined

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal
Aluminium
Tin
Zinc

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 7 of 10

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Based on available data, the classification criteria are not met. slightly irritant but not relevant for classification.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	sodium hydroxide					
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia sp.	Ecotoxicology and Environmental Safety,4 other: acute 48-h immobilization test ac

12.2. Persistence and degradability

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 8 of 10

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1824
<u>14.2. UN proper shipping name:</u>	SODIUM HYDROXIDE SOLUTION
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Classification code:	C5
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1824
<u>14.2. UN proper shipping name:</u>	SODIUM HYDROXIDE SOLUTION
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Classification code:	C5
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 1824
<u>14.2. UN proper shipping name:</u>	SODIUM HYDROXIDE, SOLUTION
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Special Provisions:	223
Limited quantity:	5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 9 of 10

Excepted quantity: E1
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 1 L
Passenger LQ: Y841
Excepted quantity: E1
IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): - - non-hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals
Skin Corr: Skin corrosion
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium hydroxide solution 0.2 % pure suitable for stress cracking tests of PET bottles

Revision date: 15.02.2024

Product code: 19600

Page 10 of 10

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)