

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Product code: 20154 Revision date: 21.03.2024 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Formaldehyde solution 20 % for analysis stabilized with methanol

RATS-U1JQ-700W-F8SF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

AnalytiChem GmbH Company name:

ACD

Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

info@analytichem.de E-mail:

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

produktsicherheit@analvtichem.de E-mail:

www.analytichem.de Internet: Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: number:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302

Acute Tox. 4; H312

Acute Tox. 4; H332

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Skin Sens. 1; H317

Muta. 2; H341

Carc. 1B; H350

STOT SE 2: H371

STOT SE 3: H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

formaldehyde

methanol



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 2 of 15

Signal word: Danger

Pictograms:





Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.

H350 May cause cancer.

H371 May cause damage to organs.

Precautionary statements

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulation (EC)	No 1272/2008)			
50-00-0	formaldehyde	formaldehyde			
	200-001-8	605-001-00-5	01-2119488953-20		
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317				
67-56-1	methanol	methanol			
	200-659-6	603-001-00-X	01-2119433307-44		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370				

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc.	Specific Conc. Limits, M-factors and ATE						
50-00-0	200-001-8	formaldehyde	15 - < 20 %					
	ATE = 300 mg/ H315: >= 5 - <	inhalation: LC50 = < 463 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 460 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100						
67-56-1	200-659-6	methanol	5 - < 10 %					
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10							

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Allergic reactions

Dyspnoea

Cough

Inebriation

Dizziness

Headache

Dizziness

Agitation

Headache Spasms

Impairment of vision

Anaesthetic state

Risk of serious damage to eyes.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 4 of 15

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Carbon dioxide (CO2) Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 5 of 15

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol.

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used. Store in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Protect against: Light

Unsuitable container/equipment material: Metal

Further information on storage conditions

Keep container tightly closed. Keep container dry.

Keep cool. Protect from sunlight. storage temperature +15°C - +25°C

otorage tomperature 10 c

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
50-00-0	Formaldehyde	0.3	0.37		TWA (8 h)	
		0.6	0.738		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 6 of 15

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
50-00-0	formaldehyde				
Worker DNEL,	long-term	inhalation	systemic	9 mg/m³	
Worker DNEL,	long-term	inhalation	local	0,375 mg/m³	
Worker DNEL,	long-term	dermal	systemic	240 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	systemic	3,2 mg/m³	
Consumer DNE	EL, long-term	inhalation	local	0,1 mg/m³	
Consumer DNE	EL, long-term	dermal	systemic	102 mg/kg bw/day	
Consumer DNE	EL, long-term	oral	systemic	4,1 mg/kg bw/day	
Worker DNEL,	acute	inhalation	local	0,75 mg/m³	
67-56-1	methanol				
Consumer DNE	EL, acute	inhalation	systemic	50 mg/m³	
Worker DNEL,	long-term	inhalation	systemic	260 mg/m³	
Worker DNEL,	acute	inhalation	systemic	260 mg/m³	
Worker DNEL,	long-term	inhalation	local	260 mg/m³	
Worker DNEL,	acute	inhalation	local	260 mg/m³	
Worker DNEL,	long-term	dermal	systemic	40 mg/kg bw/day	
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	systemic	50 mg/m³	
Consumer DNEL, long-term		inhalation	local	50 mg/m³	
Consumer DNEL, acute		inhalation	local	50 mg/m³	
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day	
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day	
Consumer DNE	EL, long-term	oral	systemic	8 mg/kg bw/day	
Consumer DNE	EL, acute	oral	systemic	8 mg/kg bw/day	



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 7 of 15

PNEC values

CAS No	Substance		
Environment	Environmental compartment		
50-00-0	formaldehyde		
Freshwater		0,44 mg/l	
Freshwater (intermittent releases)	4,44 mg/l	
Marine wate	r	0,44 mg/l	
Freshwater	sediment	2,3 mg/kg	
Marine sedir	nent	2,3 mg/kg	
Micro-organisms in sewage treatment plants (STP)		0,19 mg/l	
Soil		0,2 mg/kg	
67-56-1	methanol		
Freshwater		20,8 mg/l	
Freshwater (intermittent releases)	1540 mg/l	
Marine wate	Marine water		
Freshwater sediment		77 mg/kg	
Marine sedir	Marine sediment		
Micro-organi	Micro-organisms in sewage treatment plants (STP)		
Soil		100 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 145 min



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: ABEK

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability: No data available Lower explosion limits: No data available Upper explosion limits: No data available Flash point: No data available No data available Auto-ignition temperature: No data available Decomposition temperature: pH-Value: 3.5 Viscosity / kinematic: No data available

Viscosity / kinematic:

Water solubility:

No data available
Soluble in: Water

Solubility in other solvents

No data available

No data available Dissolution rate: Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density: 1,0485 g/cm3 Relative density: No data available Bulk density: No data available Relative vapour density: No data available Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 9 of 15

Explosive properties

Danger of dust explosion.

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available No data available Solid content: Sublimation point: No data available Softening point: No data available No data available Pour point: No data available Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reducing agent

Danger of polymerisation

In case of warming: Vapours can form explosive mixtures with air.

10.2. Chemical stability

Protect against: Light

Contains as stabilizer(s): Methanol

10.3. Possibility of hazardous reactions

Acids

Phenol

Nitric acid

Hydrogen peroxide

Alkali (lye)

permanganates, e.g. potassium permanganate

Oxidising agent Hydrochloric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against:

Light

10.5. Incompatible materials

metals

Steel

Copper

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 10 of 15

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Harmful if swallowed.

Harmful in contact with skin.

Harmful if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

ATEmix calculated

ATE (oral) 377,9 mg/kg; ATE (dermal) 1134 mg/kg; ATE (inhalation vapour) 11,34 mg/l; ATE (inhalation dust/mist) 1,890 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
50-00-0	formaldehyde							
	oral	LD50 mg/kg	460	Rat	Kefo J Med 24: 19-37 (1975)	OECD Guideline 401		
	dermal	ATE mg/kg	300					
	inhalation (4 h) vapour	LC50 mg/l	< 463	Rat	Study report (2015)	OECD Guideline 403		
	inhalation dust/mist	ATE	0,5 mg/l					
67-56-1	methanol	methanol						
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t		
	dermal	ATE mg/kg	300					
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co		
	inhalation dust/mist	ATE	0,5 mg/l					

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Causes tears.

Sensitising effects

May cause an allergic skin reaction. (formaldehyde)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 11 of 15

STOT-single exposure

May cause damage to organs. (methanol)
May cause respiratory irritation. (formaldehyde)
Liver and kidney damage
heart
eyes

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Irritant

corrosive

Allergic reactions

Dyspnoea

Cough

Inebriation

Dizziness

Headache

Dizziness

Agitation Headache

Spasms

Impairment of vision

Anaesthetic state

Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 12 of 15

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method			
50-00-0	formaldehyde									
	Acute fish toxicity	LC50 mg/l	27,57	96 h	Ictalurus punctatus	Prog.Fish-Cult. 20(1):8-15 (1958)	acute toxicity test; "static bioassay"			
	Acute algae toxicity	ErC50 mg/l	3,48	72 h	Desmodesmus subspicatus	Ecotoxicol Environ Safety 54: 346-354 (2	OECD Guideline 201			
	Acute crustacea toxicity	EC50	5,8 mg/l	48 h	Daphnia pulex	Water, Air and Soil Pollution 97, 315-32	OECD Guideline 202			
	Fish toxicity	NOEC mg/l	>= 48	28 d	Oryzias latipes	NTIS (ed.) Compendium of the FY1988 and	OECD Guideline 215			
	Crustacea toxicity	NOEC mg/l	>= 6,4	21 d	Daphnia magna	Study report (2008)	OECD Guideline 211			
	Acute bacteria toxicity	EC50)	19 mg/l (3 h	Activated sludge	Chemosphere 14, 1239-1251 (1985)	OECD Guideline 209			
67-56-1	methanol	methanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975			
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11			
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR			
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi			

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
50-00-0	formaldehyde	0,35
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
50-00-0	formaldehyde		Paralichthys olivaceus and Sebastes schlegeli	Aquaculture 194, 253
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 13 of 15

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land	trans	port (A	ADR/RID)
------	-------	---------	---------	---

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



according to Regulation (EC) No 1907/2006

Formaldehyde solution 20 % for analysis stabilized with methanol

Revision date: 21.03.2024 Product code: 20154 Page 14 of 15

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 69, Entry 75

Information according to Directive

Not subject to 2012/18/EU (SEVESO III)

2012/18/EU (SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,6,8,9,12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 2; H371	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225 High	y flammable liquid and vapour.
-----------	--------------------------------

H301 Toxic if swallowed. H302 Harmful if swallowed.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H331 Toxic if inhaled.
H332 Harmful if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 21.03.2024 Product code: 20154 Page 15 of 15

H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.
H371 May cause damage to organs.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)