

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

REACH Registration Number: 01-2119486761-29-XXXX

CAS No: 71-23-8
Index No: 603-003-00-0
EC No: 200-746-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

e-mail: info@analytichem.de

O man. Abt.: I man Do. dultable b

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephoneFor Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,number:Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 2 of 11

H318 Causes serious eye damage.H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P240 Ground and bond container and receiving equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: C3H8O

Molecular weight: 60,1 g/mol

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulation (EC) N	ion (Regulation (EC) No 1272/2008)			
71-23-8	propan-1-ol				
	200-746-9	603-003-00-0	01-2119486761-29-XXXX		
	Flam. Liq. 2, Eye Dam. 1, STOT	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. L	pecific Conc. Limits, M-factors and ATE			
71-23-8	200-746-9	9 propan-1-ol			
	dermal: LD50 = 4032 mg/kg; oral: LD50 = ca. 8000 mg/kg				

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 3 of 11

apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Cough, Dyspnoea

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 4 of 11

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 5 of 11

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Protect from sunlight. minimum storage temperature +5°C maximum storage temperature +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
71-23-8	n-Propyl alcohol; (n-Propanol)	100	-		TWA (8 h)	

DNEL/DMEL values

	_						
CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
71-23-8	propan-1-ol						
Worker DNEL	, long-term	inhalation	systemic	268 mg/m³			
Worker DNEL	, acute	inhalation	systemic	1723 mg/m³			
Worker DNEL	, long-term	dermal	systemic	136 mg/kg bw/day			
Consumer DN	IEL, long-term	inhalation	systemic	80 mg/m³			
Consumer DNEL, acute		inhalation	systemic	1036 mg/m³			
Consumer DN	IEL, long-term	dermal	systemic	81 mg/kg bw/day			
Consumer DN	IEL, long-term	oral	systemic	61 mg/kg bw/day			

PNEC values

CAS No	Substance				
Environmental compartment Value					
71-23-8	propan-1-ol				
Freshwater 6,83 mg/l					
Freshwater (intermittent releases) 10 mg/l					
Marine water		0,683 mg/l			
Freshwater sediment 2					
Marine sedime	2,75 mg/kg				
Micro-organism	96 mg/l				
Soil	1,49 mg/kg				

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Product code: 20167 Revision date: 23.02.2023 Page 6 of 11

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: >480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): >120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liauid Colour: colourless like: Alcohol Odour.

Melting point/freezing point: -127 °C Boiling point or initial boiling point and 96,5-98 °C

boiling range:

No data available Flammability: Lower explosion limits: 2,1 vol. % 19.2 vol. % Upper explosion limits: 15 °C Flash point: Auto-ignition temperature: 360 °C



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 7 of 11

Decomposition temperature:

pH-Value (at 20 °C):

Viscosity / kinematic:

No data available

No data available

No data available

very soluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: log Pow: 1,6
Vapour pressure: 19 hPa

(at 20 °C)

Vapour pressure:No data availableDensity (at 20 °C):0,8 g/cm³Bulk density:No data availableRelative vapour density:No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available No data available Solvent content: Solid content: No data available No data available Sublimation point: Softening point: No data available Pour point: No data available No data available 2.3 mPa·s Viscosity / dynamic:

(at 20 °C)

Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkaline earth metal

Alkali metals

Oxidising agent, strong

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 8 of 11

10.5. Incompatible materials

Rubber articles Plastic articles

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
71-23-8	propan-1-ol						
	oral	LD50 mg/kg	ca. 8000	Rat	Study report (1975)	OECD Guideline 401	
	dermal	LD50 mg/kg	4032	Rabbit	Arch. ind. hyg. occupat. med. 10, 61-68.	OECD Guideline 402	

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-1-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 9 of 11

Further information

Irritant

Cough, Dyspnoea

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
71-23-8	propan-1-ol							
	Acute fish toxicity	LC50 mg/l	4555	96 h	Pimephales promelas	Vol. 1, pp 3, 5-16, 65-68. Center for La	OECD Guideline 203	
	Acute crustacea toxicity	EC50 mg/l	3644	48 h	Daphnia magna	Water Res 23: 495-499 (1989)	other: DIN 38412 Part 11, Daphnia- Short	
	Crustacea toxicity	NOEC mg/l	> 100	21 d	Daphnia magna	Study report (1997)	OECD Guideline 211	

12.2. Persistence and degradability

75 %; 20 d; aerob

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
71-23-8	propan-1-ol	1,6

BCF

CAS No	Chemical name	BCF	Species	Source
71-23-8	propan-1-ol	0,88		Unpublished calculat

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 10 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1274

14.2. UN proper shipping name: n-PROPANOL (PROPYL ALCOHOL, NORMAL)

14.3. Transport hazard class(es): 14.4. Packing group: П Hazard label: 3 Classification code: F1 Limited quantity: 1 I Excepted quantity: F2 Transport category: Hazard No: 33 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1274

14.2. UN proper shipping name: n-PROPANOL (PROPYL ALCOHOL, NORMAL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1274

14.2. UN proper shipping name: n-PROPANOL (PROPYL ALCOHOL, NORMAL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 127414.2. UN proper shipping name:n-PROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3



according to Regulation (EC) No 1907/2006

1-Propanol > 99.5 % (n-propyl alcohol) for analysis

Revision date: 23.02.2023 Product code: 20167 Page 11 of 11

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU

(SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.