

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

REACH Registration Number: 01-2119475103-46-XXXX  
CAS No: 141-78-6  
Index No: 607-022-00-5  
EC No: 205-500-4

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemical  
Industrial uses: Uses of substances as such or in preparations at industrial sites  
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit  
Telefax: 0203/5194-290  
Telephone: 0203/5194-107/117

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

No data available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Eye Irrit. 2; H319  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 2 of 12

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P280  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.

#### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Sum formula: CH<sub>3</sub>COOC<sub>2</sub>H<sub>5</sub>  
Molecular weight: 88,11 g/mol

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
141-78-6	ethyl acetate			100 %
	205-500-4	607-022-00-5	01-2119475103-46-XXXX	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
141-78-6	205-500-4	ethyl acetate	100 %
	dermal: LD50 = > 20000 mg/kg; oral: LD50 = 4934 mg/kg		

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

No data available

##### After inhalation

Provide fresh air.  
Call a physician immediately.

##### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 3 of 12

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Respiratory complaints

Dizziness

The product causes narcotic-like effects.

Gastrointestinal complaints

Vomiting

Headache

Vapours may cause drowsiness and dizziness.

Dizziness

Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

#### 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 4 of 12

#### For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
- Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

- Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis**

Revision date: 26.07.2023

Product code: 20198

Page 5 of 12

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed and dry.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

storage temperature +2°C - +25°C  
Protect against: Light

**7.3. Specific end use(s)**

Laboratory use Laboratory chemical

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	734 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	367 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	734 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 6 of 12

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Freshwater (intermittent releases)		1,65 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		200 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation KCL 898 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <,) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

##### Environmental exposure controls

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Liquid

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis**

Revision date: 26.07.2023

Product code: 20198

Page 7 of 12

Colour:	colourless
Odour:	fruity
Odour threshold:	No data available
Melting point/freezing point:	-83 °C
Boiling point or initial boiling point and boiling range:	77 °C
Flammability:	not applicable
Lower explosion limits:	2,2 vol. %
Upper explosion limits:	11,5 vol. %
Flash point:	-4 °C
Auto-ignition temperature:	460 °C
Decomposition temperature:	not determined
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility: (at 20 °C)	85,3 g/L
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 0,73
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	103 hPa
Vapour pressure:	No data available
Density:	0,9 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate:

not determined

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

not determined

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

0,44 mPa·s

(at 20 °C)

Flow time:

No data available

**Further Information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis**

Revision date: 26.07.2023

Product code: 20198

Page 8 of 12

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.  
Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

Protect against:  
Light  
Air

**10.3. Possibility of hazardous reactions**

Fluorine  
Oxidising agent  
Alkali metals  
Alkaline earth metal  
Strong acid  
Strong alkali

**10.4. Conditions to avoid**

Light  
Air  
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.  
Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

plastic

**10.6. Hazardous decomposition products**

Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 4934 mg/kg	Rabbit	Ind. Med. Vol. 41, No.4, 31 - 33 (1972)	OECD Guideline 401
	dermal	LD50 > 20000 mg/kg	Rabbit	Am Ind Hyg Ass J, 23, 95 (1962)	Similar to one day cuff method of Draize

**Irritation and corrosivity**

Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis**

Revision date: 26.07.2023

Product code: 20198

Page 9 of 12

Based on available data, the classification criteria are not met.  
May cause sensitisation especially in sensitive humans.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (ethyl acetate)

**STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

**Aspiration hazard**

Based on available data, the classification criteria are not met.  
Observe risk of aspiration if vomiting occurs.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

Irritant  
Respiratory complaints  
Dizziness  
The product causes narcotic-like effects.  
Gastrointestinal complaints  
Vomiting  
Headache  
Vapours may cause drowsiness and dizziness.  
Dizziness

**Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas	Publication (1984)	other: US EPA method E03-05
	Fish toxicity	NOEC < 9,65 mg/l	32 d	Pimephales promelas	http://www.epa.gov/ecotox (1992)	OECD Guideline 210
	Crustacea toxicity	NOEC 2,4 mg/l	21 d	Daphnia magna	Water Research 23: 501-510. (1989)	other: see principles of method below

**12.2. Persistence and degradability**

100 %; 28 d  
OECD 301D

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 10 of 12

Readily biodegradable (according to OECD criteria).

#### **12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,68

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus melanotus	Chemosphere 14, 1589

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

#### **12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

#### **12.7. Other adverse effects**

Do not empty into drains.

#### **Further information**

Avoid release to the environment.

## SECTION 13: Disposal considerations

### **13.1. Waste treatment methods**

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Do not allow to enter into surface water or drains.

Send to a physico-chemical treatment facility under observation of official regulations.

#### **Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1173
<b>14.2. UN proper shipping name:</b>	ETHYL ACETATE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

### **Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1173
<b>14.2. UN proper shipping name:</b>	ETHYL ACETATE
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 11 of 12

**14.4. Packing group:** II  
**Hazard label:** 3  
**Classification code:** F1  
**Limited quantity:** 1 L  
**Excepted quantity:** E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
**Hazard label:** 3  
**Special Provisions:** -  
**Limited quantity:** 1 L  
**Excepted quantity:** E2  
**EmS:** F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
**Hazard label:** 3  
**Limited quantity Passenger:** 1 L  
**Passenger LQ:** Y341  
**Excepted quantity:** E2  
**IATA-packing instructions - Passenger:** 353  
**IATA-max. quantity - Passenger:** 5 L  
**IATA-packing instructions - Cargo:** 364  
**IATA-max. quantity - Cargo:** 60 L

#### 14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

#### 14.6. Special precautions for user

Warning: Combustible liquid.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Ethyl acetate > 99.5 % (acetic acid ethylester) for analysis

Revision date: 26.07.2023

Product code: 20198

Page 12 of 12

#### Changes

This data sheet contains changes from the previous version in section(s): 9,12.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.