



#### an analyti**chem** brand

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Potassium methylate solution approx. 25 % for synthesis in methanol

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMT	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls

#### Further Information

This product is a mixture. REACH Registration Number see section 3.

accepted)

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

## Regulation (EC) No 1272/2008

Hazard components for labelling methanol potassium methanolate

Signal word: Danger





#### Special labelling of certain mixtures

EUH014

Reacts violently with water.

#### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)					
67-56-1	methanol					
	200-659-6	603-001-00-X	01-2119433307-44			
	Flam. Liq. 2, Acute To:	. 3, Acute Tox. 3, Acute Tox. 3, STOT	SE 1; H225 H331 H311 H301 H370			
865-33-8	potassium methanolate	9		25 - < 30 %		
	212-736-1	603-040-00-2				
	Self-heat. 1, Skin Corr. 1B; H251 H314 EUH014					

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
67-56-1	200-659-6	methanol	75 - < 80 %		
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10				

## **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



# Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 3 of 13

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

## **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

#### After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

#### After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

## After ingestion

Provide fresh air. Call a physician immediately. (Induce vomiting when the affected person is not unconscious.) Notes for the doctor : Methanol Do not allow a neutralisation agent to be drunk.

#### 4.2. Most important symptoms and effects, both acute and delayed

corrosive, Cough, Dyspnoea Irritant, Dizziness Dizziness, Anaesthetic state Agitation, Spasms Inebriation, Vomiting Headache, Impairment of vision Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder

#### Unsuitable extinguishing media

Water Foam

## 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Do not allow contact with water.



## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 4 of 13

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear full chemical protective clothing. In case of fire and/or explosion do not breathe fumes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

## For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

For containment

#### Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**



an analyti**chem** brand

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 5 of 13

## 7.1. Precautions for safe handling

#### Advice on safe handling

#### Do not allow contact with water.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container dry.
Keep container tightly closed.
Keep locked up.
Store in a place accessible by authorized persons only.
Provide adequate ventilation as well as local exhaustion at critical locations.
Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Do not allow contact with water.

#### Further information on storage conditions

Keep cool. Protect from sunlight. storage temperature: < +30°C

## 7.3. Specific end use(s)

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection** 

#### 8.1. Control parameters

#### **Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	

### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift



# Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 6 of 13

## **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-56-1	methanol			
Consumer D	NEL, acute	inhalation	systemic	50 mg/m³
Worker DNE	EL, long-term	inhalation	systemic	260 mg/m³
Worker DNE	L, acute	inhalation	systemic	260 mg/m³
Worker DNE	EL, long-term	inhalation	local	260 mg/m <sup>3</sup>
Worker DNE	L, acute	inhalation	local	260 mg/m <sup>3</sup>
Worker DNE	EL, long-term	dermal	systemic	40 mg/kg bw/day
Worker DNE	L, acute	dermal	systemic	40 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	50 mg/m³
Consumer D	NEL, long-term	inhalation	local	50 mg/m³
Consumer D	NEL, acute	inhalation	local	50 mg/m³
Consumer D	NEL, long-term	dermal	systemic	8 mg/kg bw/day
Consumer D	NEL, acute	dermal	systemic	8 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	8 mg/kg bw/day
Consumer D	NEL, acute	oral	systemic	8 mg/kg bw/day

## **PNEC** values

CAS No	Substance					
Environmental compartment Value						
67-56-1	methanol					
Freshwater	20,8 mg/l					
Freshwater	Freshwater (intermittent releases) 1540 mg/l					
Marine wate	r	2,08 mg/l				
Freshwater sediment		77 mg/kg				
Marine sedi	ment	7,7 mg/kg				
Micro-organ	isms in sewage treatment plants (STP)	100 mg/l				
Soil		100 mg/kg				

#### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

## Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 7 of 13

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

Trade name/designation: KCL 898 Butoject® Recommended material: Butyl caoutchouc (butyl rubber) 0,7 mm Wearing time with permanent contact: > 480 min

Trade name/designation: KCL 890 Vitoject® Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme.

## **Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Filtering device with filter or ventilator filtering device of type: AX

## Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	Liquid colourless like: Methanol No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		5,5 vol. %
Upper explosion limits:		36,5 vol. %
Flash point:		>23 °C
Auto-ignition temperature:		415 °C
Decomposition temperature:		not determined
pH-Value:		No data available
Viscosity / kinematic:		not determined
Water solubility: (at 20 °C)		Reacts violently with water.
Solubility in other solvents		
not determined		
Dissolution rate:		No data available



Potassium methylate solu	ution approx. 25 % for synthesis in n	nethanol
Revision date: 16.08.2023	Product code: 20432	Page 8 of 13
Partition coefficient n-octanol/water:	not determined	
Dispersion stability:	No data available	
Vapour pressure:	No data available	
Vapour pressure:	No data available	
Density:	0,9537 g/cm³	
Relative density:	No data available	
Bulk density:	not applicable	
Relative vapour density:	not determined	
Particle characteristics:	No data available	
9.2. Other information		
Information with regard to physical hazard classe	S	
Explosive properties		
Vapours can form explosive mixtures with air.		
Sustaining combustion:	Sustaining combustion	
Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Oxidizing properties		
not determined		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	No data available	
Solid content:	No data available	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point: No data available:	No data available	
	<b>N N N N</b>	
Viscosity / dynamic:	No data available	
Flow time:	not determined	
Further Information		
not determined		
SECTION 10: Stability and reactivity		

### 10.1. Reactivity

In case of warming: Vapours can form explosive mixtures with air. Reacts violently with water.

## 10.2. Chemical stability

Protect against: Humidity

## 10.3. Possibility of hazardous reactions

Oxidising agent Acid Water

## 10.4. Conditions to avoid

Humidity Heat

## 10.5. Incompatible materials

No data available

## 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures



## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 9 of 13

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

#### ATEmix calculated

.....

ATE (oral) 153,8 mg/kg; ATE (dermal) 461,5 mg/kg; ATE (inhalation vapour) 4,620 mg/l; ATE (inhalation dust/mist) 0,7690 mg/l

CAS No	Chemical name	Chemical name							
	Exposure route	Dose		Species	Source	Method			
67-56-1	methanol	nethanol							
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t			
	dermal	ATE mg/kg	300						
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co			
	inhalation dust/mist	ATE	0,5 mg/l						

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Risk of serious damage to eyes.

## Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Causes damage to organs. (methanol) (eyes)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

There are no data available on the mixture itself.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

## Additional information on tests

There are no data available on the mixture itself.



# Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 10 of 13

Practical experience There are no data available on the mixture itself.

# 11.2. Information on other hazards

# Endocrine disrupting properties

There are no data available on the mixture itself.

# Other information

There are no data available on the mixture itself.

# Further information

corrosive, Cough, Dyspnoea Irritant, Dizziness Dizziness, Anaesthetic state Agitation, Spasms Inebriation, Vomiting Headache, Impairment of vision Risk of serious damage to eyes.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
67-56-1	methanol	methanol							
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR		
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi		

## 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No Chemical name						
67-56-1	5-1 methanol					
BCF						
CAS No	Chemical name	BCF	Species	Source		
67-56-1	methanol	1	Cyprinus carpio	Comparativ	e Biochemi	

## 12.4. Mobility in soil

There are no data available on the mixture itself.



## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 11 of 13

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

There are no data available on the mixture itself.

### Further information

Do not allow to enter into surface water or drains. Avoid release to the environment.

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not mix with other wastes. Do not empty into drains.

#### **Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium methanolate,
	methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	ll
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	83
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium methanolate,
	methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	ll
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Marine transport (IMDG)	



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

Potassium methylate solution approx. 25 % for synthesis in methanol		
Revision date: 16.08.2023	Product code: 20432	Page 12 of 13
14.1. UN number or ID number:	UN 2920	
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium methanolate, methanol)	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
Hazard label:	8+3	
Special Provisions:	274	
Limited quantity:	1 L	
Excepted quantity:	E2	
EmS:	F-E, S-C	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 2920	
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium methanolate, methanol)	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
Hazard label:	8+3	
Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:	851	
IATA-max. quantity - Passenger:	1 L	
IATA-packing instructions - Cargo:	855	
IATA-max. quantity - Cargo:	30 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
<u>14.6. Special precautions for user</u> Warning: Combustible liquid. Toxic.		
14.7. Maritime transport in bulk according to	MO instruments	
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII):		
Entry 3, Entry 40, Entry 69, Entry 75		
Information according to 2012/18/EU	H2 ACUTE TOXIC	
(SEVESO III):		
Additional information:	P5c, O1	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juver	hile
	work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or	
	nursing mothers.	
Water hazard class (D):	2 - obviously hazardous to water	
Skin resorption/Sensitization:	Permeates easily through outer skin and causes poisoning.	
15.2. Chemical safety assessment		
For this substance a chemical safety as	esessment has not been carried out	
i ui uno ouvolanue a unennual dalely de		

# SECTION 16: Other information



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Potassium methylate solution approx. 25 % for synthesis in methanol

Revision date: 16.08.2023

Product code: 20432

Page 13 of 13

## Changes

This data sheet contains changes from the previous version in section(s): 9,12.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Self-heat: Self-heating substance or mixture Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage STOT SE: Specific target organ toxicity - single exposure

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H251	Self-heating: may catch fire.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs.
EUH014	Reacts violently with water.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)