



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

UFI: 60RT-W139-J006-D9E0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0

info Ob a madium find a

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone
 number:
 For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,
 Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 2 of 13

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P243 Take action to prevent static discharges.

P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	ndex No REACH No		
	Classification (GB CLP Regulation)				
64-17-5	ethanol				
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319				
78-93-3	butanone	butanone			
	201-159-0	606-002-00-3	606-002-00-3 01-2119457290-43		
_	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

opecine cone	pecific done: Elimits, M-lactors and ATE				
CAS No	EC No	EC No Chemical name			
	Specific Conc. Limits, M-factors and ATE				
64-17-5	200-578-6	ethanol	95 - < 100 %		
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100				

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.





according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 3 of 13

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

Aspiration hazard

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Beware of reignition.

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert



Fa. Bernd Kraft GmbH

according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 4 of 13

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 5 of 13

national regulations

Further information on storage conditions

Vapours may form explosive mixtures with air.

7.3. Specific end use(s)

Laboratory use Laboratory chemical

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
64-17-5	ethanol			
Worker DNE	L, long-term	inhalation	systemic	950 mg/m³
Worker DNE	L, long-term	dermal	systemic	343 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	114 mg/m³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	87 mg/kg bw/day
78-93-3	butanone			
Worker DNE	L, long-term	inhalation	systemic	600 mg/m³
Worker DNE	L, long-term	dermal	systemic	1161 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	106 mg/m³
Consumer DNEL, long-term		dermal	systemic	412 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	31 mg/kg bw/day



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 6 of 13

PNEC values

CAS No Substance		
3.13.13		
Environmental compartment	Value	
64-17-5 ethanol		
Freshwater	0,96 mg/l	
Freshwater (intermittent releases)	2,75 mg/l	
Marine water	0,79 mg/l	
Freshwater sediment	3,6 mg/kg	
Marine sediment	2,9 mg/kg	
Secondary poisoning	380 mg/kg	
Micro-organisms in sewage treatment plants (STP)	580 mg/l	
Soil	0,63 mg/kg	
78-93-3 butanone		
Freshwater	55,8 mg/l	
Freshwater (intermittent releases)	55,8 mg/l	
Marine water	55,8 mg/l	
Freshwater sediment	284,74 mg/kg	
Marine sediment 284,7		
Secondary poisoning 1000 m		
Micro-organisms in sewage treatment plants (STP) 709 mg/l		
Soil	22,5 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 7 of 13

(e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Thermal hazards

No data available

Environmental exposure controls

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Alcohol
Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

-114,5 °C

Boiling point or initial boiling point and

78 °C

boiling range:

Sublimation point:

Softening point:

No data available

No data available

Pour point:

No data available

No data available

No data available:

Flash point: 12 °C

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: 3,1 vol. %
Upper explosion limits: 27,7 vol. %
Auto-ignition temperature: 425 °C

Self-ignition temperature

Solid: not applicable Gas: not applicable not applicable not applicable Pecomposition temperature: not determined pH-Value (at 20 °C): 7 (10g/l) Viscosity / dynamic: 1,2 mPa·s

(at 20 °C)

Viscosity / kinematic:

Flow time:

No data available

No data available

Water solubility:

Soluble in: Water





according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 8 of 13

Solubility in other solvents

not determined

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

Vapour pressure:

No data available

Vapour pressure:

59 hPa

(at 50 °C)

Vapour pressure:

Density:

O,79000 g/cm³
Relative density:

No data available
Bulk density:

No data available
Relative vapour density:

not determined
Particle characteristics:

No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: Sustaining combustion

Oxidizing properties Not oxidising.

Other safety characteristics

Solvent separation test:

Solvent content:

No data available

Solid content:

No data available

Evaporation rate:

No data available

not determined

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Plastic articles

Rubber articles

10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Further information

No data available



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 9 of 13

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64-17-5	ethanol					
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Irritant

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

Further information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 10 of 13

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
64-17-5	ethanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a		
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th		
78-93-3	butanone								
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	Study report (1998)	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	2029	96 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201		
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77
78-93-3	butanone	0,3

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 11 of 13

12.7. Other adverse effects

Do not empty into drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Do not allow to enter into surface water or drains.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

I and	transport	(ADR/RID)
∟anu	uansport	

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 F1 Classification code: **Special Provisions:** 144 601 Limited quantity: 1 L E2 Excepted quantity: 2 Transport category: 33 Hazard No: Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)


14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:144 601Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:144Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D





according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 12 of 13

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)

14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 100 %

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%





according to UK REACH Regulation

Ethanol absolut mind. 99,7 % zur Analyse sulfatfrei - mit MEK vergällt

Revision date: 14.06.2022 Product code: 20488 Page 13 of 13

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)