

## Safety Data Sheet

according to UK REACH Regulation

### Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol

Revision date: 23.11.2022

Product code: 20492

Page 1 of 15

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol

#### Further trade names

Formaldehyda - solutie min. 37%, fara acid, stabilizata cu ~ 10%  
metanol si carbonat de calciu, pentru histologie

UFI: PCRT-W1UV-S005-1NR8

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals  
Industrial uses: Uses of substances as such or in preparations at industrial sites  
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

inapplicable, this product is a mixture REACH registration number see section 3

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Acute Tox. 3; H301  
Acute Tox. 3; H311  
Acute Tox. 3; H331  
Skin Corr. 1B; H314  
Eye Dam. 1; H318  
Skin Sens. 1; H317  
Muta. 2; H341  
Carc. 1B; H350  
STOT SE 1; H370  
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### GB CLP Regulation

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 2 of 15

**Hazard components for labelling**

formaldehyde  
methanol

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H341 Suspected of causing genetic defects.  
H350 May cause cancer.  
H370 Causes damage to organs.

**Precautionary statements**

P201 Obtain special instructions before use.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

**Special labelling of certain mixtures**

Restricted to professional users.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
50-00-0	formaldehyde			35 - < 40 %
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317			
67-56-1	methanol			10 - < 15 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 3 of 15

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
50-00-0	200-001-8	formaldehyde	35 - < 40 %
		inhalation: LC50 = < 463 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 460 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100	
67-56-1	200-659-6	methanol	10 - < 15 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Self-protection of the first aider

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Rinse mouth immediately and drink plenty of water.  
Call a physician immediately.  
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant  
corrosive  
Allergic reactions  
Dyspnoea  
Cough  
Inebriation  
Dizziness  
Headache  
Dizziness  
Agitation  
Headache  
Spasms  
Impairment of vision  
Anaesthetic state  
Risk of serious damage to eyes.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 4 of 15

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO<sub>x</sub>)

Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

Danger of explosion

**6.3. Methods and material for containment and cleaning up**

**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 5 of 15

**Other information**

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

- Avoid exposure - obtain special instructions before use.
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe vapour/aerosol.
- Provide adequate ventilation.

**Advice on protection against fire and explosion**

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

**Advice on general occupational hygiene**

- Keep away from food, drink and animal feedingstuffs.

**Further information on handling**

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Store in a place accessible by authorized persons only.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

- Keep in a cool, well-ventilated place.
- Protect against: Light
- Unsuitable container/equipment material: Metal

**Hints on joint storage**

- national regulations

**Further information on storage conditions**

- Keep container tightly closed. Keep container dry.
- Keep cool. Protect from sunlight.
- storage temperature +15°C - +25°C

**7.3. Specific end use(s)**

- Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 6 of 15

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
50-00-0	formaldehyde			
Worker DNEL, long-term		inhalation	systemic	9 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	0,375 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	240 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	3,2 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	0,1 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	102 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,1 mg/kg bw/day
Worker DNEL, acute		inhalation	local	0,75 mg/m <sup>3</sup>
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 7 of 15

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
50-00-0	formaldehyde	
Freshwater		0,44 mg/l
Freshwater (intermittent releases)		4,44 mg/l
Marine water		0,44 mg/l
Freshwater sediment		2,3 mg/kg
Marine sediment		2,3 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,19 mg/l
Soil		0,2 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles  
Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®  
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm  
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®  
Recommended material: FKM (fluoro rubber) 0,7 mm  
Wearing time with occasional contact (splashes): > 145 min

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Draw up and observe skin protection programme.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation  
Filtering device with filter or ventilator filtering device of type: ABEK

**Environmental exposure controls**

Do not allow to enter into surface water or drains.  
Danger of explosion

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	stinging
Odour threshold:	No data available
Melting point/freezing point:	< -15 °C
Boiling point or initial boiling point and boiling range:	93-96 °C
Flammability	
Solid/liquid:	No data available
Gas:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	62 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value (at 20 °C):	2,8 - 4
Viscosity / kinematic:	No data available
Water solubility:	Soluble in: Water
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,09 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**



**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 9 of 15

**Explosive properties**

Danger of dust explosion.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

:

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Reducing agent

Danger of polymerisation

In case of warming: Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

Protect against: Light

Contains as stabilizer(s): Methanol

**10.3. Possibility of hazardous reactions**

Acids

Phenol

Nitric acid

Hydrogen peroxide

Alkali (lye)

permanganates, e.g. potassium permanganate

Oxidising agent

Hydrochloric acid

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against:

Light

**10.5. Incompatible materials**

metals

Steel

Copper

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 10 of 15

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

**Acute toxicity**

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

**ATEmix calculated**

ATE (oral) 222,2 mg/kg; ATE (dermal) 666,7 mg/kg; ATE (inhalation vapour) 6,67 mg/l; ATE (inhalation dust/mist) 1,111 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
50-00-0	formaldehyde				
	oral	LD50 mg/kg 460	Rat	Kefo J Med 24: 19-37 (1975)	OECD Guideline 401
	dermal	ATE mg/kg 300			
	inhalation (4 h) vapour	LC50 mg/l < 463	Rat	Study report (2015)	OECD Guideline 403
	inhalation dust/mist	ATE 0,5 mg/l			
67-56-1	methanol				
	oral	LD50 mg/kg 6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE mg/kg 300			
	inhalation (4 h) vapour	LC50 mg/l 128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

Causes serious eye damage.

Causes tears.

**Sensitising effects**

May cause an allergic skin reaction. (formaldehyde)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing genetic defects. (formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 11 of 15

**STOT-single exposure**

Causes damage to organs. (methanol)  
May cause respiratory irritation. (formaldehyde)  
Liver and kidney damage  
heart  
eyes

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

No data available

**Further information**

Irritant  
corrosive  
Allergic reactions  
Dyspnoea  
Cough  
Inebriation  
Dizziness  
Headache  
Dizziness  
Agitation  
Headache  
Spasms  
Impairment of vision  
Anaesthetic state  
Risk of serious damage to eyes.

**SECTION 12: Ecological information**

**12.1. Toxicity**

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 12 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
50-00-0	formaldehyde					
	Acute fish toxicity	LC50 mg/l	27,57	96 h	Ictalurus punctatus	Prog.Fish-Cult. 20(1):8-15 (1958) acute toxicity test; "static bioassay"
	Acute algae toxicity	ErC50 mg/l	3,48	72 h	Desmodesmus subspicatus	Ecotoxicol Environ Safety 54: 346-354 (2) OECD Guideline 201
	Acute crustacea toxicity	EC50	5,8 mg/l	48 h	Daphnia pulex	Water, Air and Soil Pollution 97, 315-32 OECD Guideline 202
	Fish toxicity	NOEC mg/l	>= 48	28 d	Oryzias latipes	NTIS (ed.) Compendium of the FY1988 and OECD Guideline 215
	Crustacea toxicity	NOEC mg/l	>= 6,4	21 d	Daphnia magna	Study report (2008) OECD Guideline 211
	Acute bacteria toxicity	(EC50	19 mg/l)	3 h	Activated sludge	Chemosphere 14, 1239-1251 (1985) OECD Guideline 209
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 mg/l	ca. 22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7 OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989) other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research, Calculation performed with ECOSAR
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013) Toxicity of the target chemical is predi

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
50-00-0	formaldehyde	0,35
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
50-00-0	formaldehyde	< 1	Paralichthys olivaceus and Sebastes schlegeli	Aquaculture 194, 253
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 13 of 15

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.  
Forms corrosive mixtures with water even if diluted.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2209
<b>14.2. UN proper shipping name:</b>	FORMALDEHYDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	533
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2209
<b>14.2. UN proper shipping name:</b>	FORMALDEHYDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	533
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 2209
<b>14.2. UN proper shipping name:</b>	FORMALDEHYDE SOLUTION
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	-

**Safety Data Sheet**

according to UK REACH Regulation

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 14 of 15

Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 2209  
**14.2. UN proper shipping name:** FORMALDEHYDE SOLUTION  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** III  
 Hazard label: 8  
 Special Provisions: A803  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y841  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 852  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 856  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 28, Entry 40, Entry 69, Entry 75  
 Information according to 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Water hazard class (D): 3 - highly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,9,12.

**Formaldehyde solution 37 % for analysis, ACS, Reag. Ph. Eur. stabilized with methanol**

Revision date: 23.11.2022

Product code: 20492

Page 15 of 15

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H335	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H370	Causes damage to organs.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*