

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

UFI: T15U-U10N-300E-X5YT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290
Flam. Liq. 3; H226
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetic acid

Signal word: Danger

Pictograms:



Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 2 of 12

Hazard statements

H226 Flammable liquid and vapour.
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-19-7	acetic acid			95 - < 100 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A; H226 H314			
576-26-1	2,6-xylenol			< 1 %
	209-400-1	604-006-00-X		
	Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Aquatic Chronic 2; H311 H301 H314 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-19-7	200-580-7	acetic acid	95 - < 100 %
	inhalation: LC50 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25		
576-26-1	209-400-1	2,6-xylenol	< 1 %
	dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 3 of 12

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.
Do not allow a neutralisation agent to be drunk.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
corrosive
Dyspnoea
Gastrointestinal complaints
Vomiting
Circulatory collapse
Corneal opacity.
Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂) Carbon monoxide
Acetic acid vapour
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 4 of 12

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 5 of 12

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	WEL
		20	50		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-19-7	acetic acid			
Worker DNEL, long-term		inhalation	local	25 mg/m ³
Worker DNEL, acute		inhalation	local	25 mg/m ³
Consumer DNEL, long-term		inhalation	local	25 mg/m ³
Consumer DNEL, acute		inhalation	local	25 mg/m ³

PNEC values

CAS No	Substance	Value
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 6 of 12

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability		
Solid/liquid:		No data available
Gas:		No data available
Lower explosion limits:		No data available

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 7 of 12

Upper explosion limits:	No data available
Flash point:	40 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	0,7
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,05 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

: No data available

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 8 of 12

peroxides, for example hydrogen peroxide
permanganates, e.g. potassium permanganate
Oxidising agent, strong
Metal
iron and steel
Zinc
Alkali (lye)
aldehydes
Alcohols
Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Symptoms may be delayed.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-19-7	acetic acid				
	oral	LD50 3310 mg/kg	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194)	The sodium salt of acetic acid was admin
	inhalation (4 h) vapour	LC50 11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403
576-26-1	2,6-xylenol				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 9 of 12

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.
Observe risk of aspiration if vomiting occurs.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Irritant
corrosive
Dyspnoea
Gastrointestinal complaints
Vomiting
Circulatory collapse
Corneal opacity.
Risk of serious damage to eyes.

Further information

May cause damage to organs.
(kidneys)

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-19-7	acetic acid					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 10 of 12

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.
Harmful effect due to pH shift.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2789
14.2. UN proper shipping name:	Acetic acid, glacial
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Classification code:	CF1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	83
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2789
14.2. UN proper shipping name:	Acetic acid, glacial
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Classification code:	CF1
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 11 of 12

14.1. UN number or ID number: UN 2789
14.2. UN proper shipping name: Acetic acid, glacial
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8+3
Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2789
14.2. UN proper shipping name: Acetic acid, glacial
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8+3
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2
IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 3; H226	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Safety Data Sheet

according to UK REACH Regulation

Dimethylphenol solution 1.2 g/l in acetic acid 100% according to DIN 38405-9:2011, DEV D9

Revision date: 19.12.2022

Product code: 20640

Page 12 of 12

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)