



according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung 6 Elemente je 1 g/l

UFI: UXRU-51UY-G009-G960

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290 Acute Tox. 2; H330 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1B; H350i STOT RE 2: H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

nitric acid

Signal word: Danger

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H350i May cause cancer by inhalation.



according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 2 of 9

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.

P260

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Re	gulation)	·		
7697-37-2	nitric acid				
	231-714-2	007-030-00-3	01-2119487297-23		
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071				
13597-99-4	beryllium nitrate				
	237-062-5	004-002-00-2			
	Carc. 1B, Acute Tox. 2, Acute Tox. 3, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, STOT RE 1, Aquatic Chronic 2; H350i H330 H301 H315 H319 H317 H335 H372 H411				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

			
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
	inhalation: ATE 2,65 mg/kg (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20		
13597-99-4	237-062-5	beryllium nitrate	1 - < 5 %
	inhalation: ATE 100 mg/kg	E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE =	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Call a physician immediately.





according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 3 of 9

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eves and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

No special environmental measures are necessary. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).





according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 4 of 9

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Unsuitable container/equipment material: Metal.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Fa. Bernd Kraft GmbH



Safety Data Sheet

according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 5 of 9

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: odourless

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and ?

boiling range:

Flash point: X

Flammability

Solid/liquid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined
pH-Value: <1

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: <=1100 hPa

(at 50 °C)

Density: 1,06000 g/cm³
Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.



according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 6 of 9

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Keep away from: Metal.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Fatal if inhaled.

CAS No	Chemical name							
	Exposure route	Dose	Species	Source	Method			
7697-37-2	nitric acid							
	inhalation vapour	ATE 2,65 mg/kg						
13597-99-4	beryllium nitrate							
	oral	ATE 100 mg/kg						
	inhalation vapour	ATE 0,5 mg/l						
	inhalation dust/mist	ATE 0,05 mg/l						

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (beryllium nitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (beryllium nitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (beryllium nitrate)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.





according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 7 of 9

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
7697-37-2	nitric acid							
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26	
	Fish toxicity	NOEC	268 mg/l		juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical	
	Algae toxicity	NOEC mg/l	> 419	_	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:274



according to UK REACH Regulation

Multielement-Standardlösung 6 Elen	nente je 1 g/l
------------------------------------	----------------

Revision date: 07.06.2022 Product code: 20860 Page 8 of 9

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-BSegregation group:1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



according to UK REACH Regulation

Multielement-Standardlösung 6 Elemente je 1 g/l

Revision date: 07.06.2022 Product code: 20860 Page 9 of 9

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350i	May cause cancer by inhalation.
H372	Causes damage to organs through prolonged or repeate
H373	May cause damage to organs through prolonged or repe
	H290 H301 H314 H315 H317 H318 H319 H330 H331 H335 H350i H372

ed exposure. peated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)