

according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

## Further Information

This product is a mixture. REACH Registration Number see section 3.

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## Regulation (EC) No 1272/2008

### Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





### **Hazard statements**

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 2 of 11

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves and eve/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			95 - < 100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
77-09-8	phenolphthalein			
	201-004-7	604-076-00-1	01-2119498295-24	
	Carc. 1B, Muta. 2, Repr. 2; H350 H341 H361f			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

Opcomo con	opcomo cono: Eminto, in lactoro ana 711					
CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Specific Conc. Limits, M-factors and ATE				
77-09-8	201-004-7	phenolphthalein	< 1 %			
	Carc. 1B; H350: >= 1 - 100					

#### **Further Information**

No data available

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

No data available

## After inhalation

Provide fresh air.

Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 3 of 11

### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Cough, Dyspnoea

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.



according to Regulation (EC) No 1907/2006

# Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 4 of 11

Remove persons to safety.

**Emergency procedures** 

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Print date: 02.01.2023



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 5 of 11

## Further information on storage conditions

Protect from sunlight.

## 7.3. Specific end use(s)

Laboratory chemicals

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	_	End of shift at end of workweek

### **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³	
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³	
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day	

## PNEC values

CAS No	Substance		
Environmen	tal compartment	Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Freshwater		140,9 mg/l	
Freshwater (intermittent releases)		140,9 mg/l	
Marine water		140,9 mg/l	
Freshwater sediment		552 mg/kg	
Marine sediment		552 mg/kg	
Secondary poisoning		160 mg/kg	
Micro-organisms in sewage treatment plants (STP)		2251 mg/l	
Soil		28 mg/kg	

## 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment

If handled uncovered, arrangements with local exhaust ventilation have to be used.

# Individual protection measures, such as personal protective equipment



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 6 of 11

### Eye/face protection

goggles

Face protection umbrella

#### Hand protection

4When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: >480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): >120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

## **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Alcohol
Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available
82 °C

boiling range: Flammability



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 7 of 11

Upper explosion limits:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

No data available

No data available

PH-Value:

No data available

Viscosity / kinematic:

No data available

Water solubility:

very soluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

Vapour pressure:

No data available

Relative vapour density:

No data available

No data available

### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

## Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available Solid content: Sublimation point: No data available Softening point: No data available Pour point: No data available No data available Viscosity / dynamic: No data available Flow time: No data available

# **Further Information**

No data available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Vapours may form explosive mixtures with air.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Alkaline earth metal

Alkali metals

Oxidising agent, strong

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 8 of 11

### 10.5. Incompatible materials

Rubber articles Plastic articles

### 10.6. Hazardous decomposition products

In case of fire may be liberated:

Carbon dioxide (CO2)

Carbon monoxide

### **Further information**

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Specific effects in experiment on an animal

There are no data available on the mixture itself.

### Additional information on tests

There are no data available on the mixture itself.

### **Practical experience**

There are no data available on the mixture itself.

# 11.2. Information on other hazards

### Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

# **Further information**

Irritant

Cough, Dyspnoea

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Print date: 02.01.2023



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 9 of 11

Risk of serious damage to eyes.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
77-09-8	phenolphthalein						
	Acute algae toxicity	ErC50	8,9 mg/l		Desmodesmus subspicatus		OECD Guideline 201

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
77-09-8	phenolphthalein	0,9

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

Avoid release to the environment.

### **Further information**

Do not allow to enter into surface water or drains.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

# Land transport (ADR/RID)



according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 10 of 11

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 Special Provisions: 601 Limited quantity: 1 I Excepted quantity: E2 Transport category: 2 Hazard No: 33

Inland waterways transport (ADN)

Tunnel restriction code:

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

D/E

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:601Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A180Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

Print date: 02.01.2023



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Phenolphtalein-Indikatorlösung 0,3% in iso-Propanol

Revision date: 02.01.2023 Product code: 20993 Page 11 of 11

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

phenolphthalein

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Information according to 2012/18/EU

P5c FLAMMABLE LIQUIDS

(SEVESO III):

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

### **SECTION 16: Other information**

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.

H350 May cause cancer.

H361f Suspected of damaging fertility.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)