

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

UFI: 298V-S1E1-900V-VDGJ

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

inapplicable, this product is a mixture REACH registration number see section 3

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GB CLP Regulation

Skin Corr. 1B; H314

Eye Dam. 1; H318

STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### GB CLP Regulation

###### Hazard components for labelling

2-dimethylaminoethanol

Signal word: Danger

###### Pictograms:



###### Hazard statements

H314

Causes severe skin burns and eye damage.

**Safety Data Sheet**

according to UK REACH Regulation

**Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC**

Revision date: 16.10.2023

Product code: 21039

Page 2 of 11

H335 May cause respiratory irritation.

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves and eye/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
108-01-0	2-dimethylaminoethanol			5 - < 10 %
	203-542-8	603-047-00-0	01-2119492298-24	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, STOT SE 3; H226 H331 H312 H302 H314 H335			
1336-21-6	Ammonia			< 1 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-01-0	203-542-8	2-dimethylaminoethanol	5 - < 10 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg STOT SE 3; H335: >= 5 - 100	
1336-21-6	215-647-6	Ammonia	< 1 %
		inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!

**After inhalation**

Provide fresh air.  
 Call a physician immediately.

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 3 of 11

#### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water.  
Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns.  
Irritant  
Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

##### Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Hazardous combustion products  
In case of fire may be liberated:  
Nitrogen oxides (NO<sub>x</sub>)

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 4 of 11

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

##### **Advice on protection against fire and explosion**

Usual measures for fire prevention.

##### **Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

##### **Further information on handling**

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed.

##### **Hints on joint storage**

national regulations

##### **Further information on storage conditions**

Store in a cool dry place.

#### **7.3. Specific end use(s)**

Laboratory chemicals

## **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 5 of 11

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-01-0	2-Dimethylaminoethanol	2	7.4		TWA (8 h)	WEL
		6	22		STEL (15 min)	WEL
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1336-21-6	Ammonia			
Worker DNEL, long-term		inhalation	systemic	47,6 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	47,6 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	14 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	36 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	6,8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	6,8 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	23,8 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	23,8 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	2,8 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	7,2 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	6,8 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
1336-21-6	Ammonia	
Environmental compartment		
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,007 mg/l
Marine water		0,001 mg/l

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

goggles

Wear eye/face protection.

##### Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 6 of 11

By long-term hand contact

Recommended glove articles: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 730 Camatril® Velours

Recommended material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 240 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		10,6
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 7 of 11

#### Explosive properties

No data available

#### Sustaining combustion:

No data available

#### Self-ignition temperature

Solid:

No data available

Gas:

No data available

#### Oxidizing properties

Oxidizing

#### Other safety characteristics

##### Evaporation rate:

No data available

##### Solvent separation test:

No data available

##### Solvent content:

0

##### Solid content:

0

##### Sublimation point:

No data available

##### Softening point:

No data available

##### Pour point:

No data available

##### No data available:

##### Viscosity / dynamic:

No data available

##### Flow time:

No data available

#### Further Information

Corrosive to metals.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

#### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC**

Revision date: 16.10.2023

Product code: 21039

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-01-0	2-dimethylaminoethanol				
	oral	ATE 500 mg/kg			
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			
1336-21-6	Ammonia				
	oral	LD50 350 mg/kg	Rat	Journal of Industrial Hygiene and Toxicology	OECD Guideline 401
	inhalation (1 h) vapour	LC50 4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity

**Irritation and corrosivity**

Causes severe skin burns and eye damage.  
Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (2-dimethylaminoethanol)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

There are no data available on the preparation/mixture itself.

**Additional information on tests**

There are no data available on the preparation/mixture itself.

**Practical experience**

There are no data available on the preparation/mixture itself.

**11.2. Information on other hazards**

**Other information**

There are no data available on the preparation/mixture itself.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.



## Safety Data Sheet

according to UK REACH Regulation

## Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 9 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 0,75 - 3,4 mg/l	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210

**12.2. Persistence and degradability**

The methods for determining the biological degradability are not applicable to inorganic substances.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

There are no data available on the mixture itself.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3267

**14.2. UN proper shipping name:**CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(2-dimethylaminoethanol)

## Safety Data Sheet

according to UK REACH Regulation

### Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC

Revision date: 16.10.2023

Product code: 21039

Page 10 of 11

<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

#### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 3267
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-dimethylaminoethanol)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

#### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 3267
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-dimethylaminoethanol)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 3267
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-dimethylaminoethanol)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Safety Data Sheet**

according to UK REACH Regulation

**Verdünnungs-Reagenz "PAR Postcolumn" zur Detektion von Übergangsmetallen in der IC**

Revision date: 16.10.2023

Product code: 21039

Page 11 of 11

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 3,9.

**Abbreviations and acronyms**

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Eye Dam: Eye damage

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method

**Relevant H and EUH statements (number and full text)**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*