

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 1 of 15

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Acute Tox. 3; H301  
Acute Tox. 3; H311  
Acute Tox. 3; H331  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Repr. 2; H361d  
STOT SE 1; H370  
STOT SE 3; H336  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

toluene  
methanol

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 2 of 15

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H225	Highly flammable liquid and vapour.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			50 - < 55 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
67-56-1	methanol			45 - < 50 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 3 of 15

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-88-3	203-625-9	toluene	50 - < 55 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
67-56-1	200-659-6	methanol	45 - < 50 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

First aider: Pay attention to self-protection!

**After inhalation**

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

**After contact with skin**

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

**After contact with eyes**

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Consult an ophthalmologist.

**After ingestion**

Provide fresh air.  
Call a physician immediately.  
Notes for the doctor : Methanol

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant, Dizziness  
Dizziness, Anaesthetic state  
Agitation, Spasms  
Inebriation, Vomiting  
Headache, Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

no restriction

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 4 of 15

#### **5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Highly flammable.  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide, Carbon monoxide  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Beware of reignition.  
Heating causes rise in pressure with risk of bursting.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
Wear full chemical protective clothing.  
In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion  
Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 5 of 15

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Avoid exposure - obtain special instructions before use.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.  
Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe vapour/aerosol. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.  
Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 6 of 15

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

**DNEL/DMEL values**

CAS No	Substance	DNEL type	Exposure route	Effect	Value
108-88-3	toluene				
		Worker DNEL, long-term	inhalation	systemic	192 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	systemic	384 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	local	192 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	local	384 mg/m <sup>3</sup>
		Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m <sup>3</sup>
		Consumer DNEL, acute	inhalation	systemic	226 mg/m <sup>3</sup>
		Consumer DNEL, long-term	inhalation	local	56,5 mg/m <sup>3</sup>
		Consumer DNEL, acute	inhalation	local	226 mg/m <sup>3</sup>
		Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
67-56-1	methanol				
		Consumer DNEL, acute	inhalation	systemic	50 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	systemic	260 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	local	260 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>
		Worker DNEL, long-term	dermal	systemic	40 mg/kg bw/day
		Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	50 mg/m <sup>3</sup>
		Consumer DNEL, long-term	inhalation	local	50 mg/m <sup>3</sup>
		Consumer DNEL, acute	inhalation	local	50 mg/m <sup>3</sup>
		Consumer DNEL, long-term	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	8 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	8 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	8 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 7 of 15

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet <(>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 8 of 15

and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing  
Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### Environmental exposure controls

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>35 °C
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

Vapours can form explosive mixtures with air.

##### Sustaining combustion:

Sustaining combustion

##### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

##### Oxidizing properties

No data available



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 9 of 15

**Other safety characteristics**

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	100%
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic: (at 20 °C)	No data available
Flow time:	No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Highly flammable.  
Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent, Nitrogen oxides (NOx), Potassium chlorate, peroxides, for example hydrogen peroxide, Nitric acid, sulphuric acid, , Acid halogen, Acetic anhydride, Maleic anhydride, Reducing agent, Acid, Bromine, Chlorine, Chloroform, Fluorine, Alkali metals, Alkaline earth metal;

**10.4. Conditions to avoid**

Vapours can form explosive mixtures with air.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles  
Zinc

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

**Acute toxicity**

Toxic if swallowed.  
Toxic in contact with skin.  
Toxic if inhaled.  
Irritation to respiratory tract

**ATEmix calculated**

ATE (oral) 209,9 mg/kg; ATE (dermal) 629,6 mg/kg; ATE (inhalation vapour) 6,300 mg/l; ATE (inhalation dust/mist) 1,049 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 10 of 15

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
67-56-1	methanol					
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE mg/kg	300			
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE	0,5 mg/l			

**Irritation and corrosivity**

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Has degreasing effect on the skin.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Causes damage to organs. (methanol)

May cause drowsiness or dizziness. (toluene)

(eyes)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (toluene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Other information**

Irritation to respiratory tract

Repeated exposure may cause skin dryness or cracking.

Causes damage to organs.

Organs affected:

Liver and kidney damage

eyes

heart

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 11 of 15

**Further information**

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache, Impairment of vision  
Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l > 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 mg/l 11,5	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l 1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l > 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l 0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l 15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l 446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 12 of 15

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1992
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, toluene)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	336
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1992
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, toluene)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 13 of 15

**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3+6.1  
 Classification code: FT1  
 Special Provisions: 274 802  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, toluene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3+6.1  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, toluene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3+6.1  
 Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 352  
 IATA-max. quantity - Passenger: 1 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. Toxic.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 69

Information according to Directive 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Additional information: P5c

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt**

Revision date: 09.02.2024

Product code: 21381

Page 14 of 15

Water hazard class (D): 3 - highly hazardous to water  
Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,12.

**Abbreviations and acronyms**

Flam. Liq: Flammable liquid  
Acute Tox: Acute toxicity  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Repr: Reproductive toxicity  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
H301 Toxic if swallowed.  
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H331 Toxic if inhaled.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Methanol / Toluol-Gemisch zur Analyse volumetrisch 1:1 gemischt

Revision date: 09.02.2024

Product code: 21381

Page 15 of 15

H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*