

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2-Propanol min. 99,8%

REACH Registration Number: 01-2119457558-25-XXXX

CAS No: 67-63-0
Index No: 603-117-00-0
EC No: 200-661-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

e-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephoneFor Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,number:Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 2 of 11

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P240 Ground and bond container and receiving equipment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: CH3CH(OH)CH3
Molecular weight: 60,1 g/mol

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REAC	H No	
	Classification (Regulation (EC) No 1272/2008)				
67-63-0	propan-2-ol; isopropyl alcohol;	propan-2-ol; isopropyl alcohol; isopropanol			100 %
	200-661-7	603-117-00-0			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				

Full text of H and EUH statements: see section 16.

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 3 of 11

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 4 of 11

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Protect from sunlight.

Protect against: Light

minimum storage temperature +5°C

maximum storage temperature +30°C



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 5 of 11

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	_	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³		
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³		
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day		

PNEC values

CAS No	Substance			
Environmen	Environmental compartment			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Freshwater	140,9 mg/l			
Freshwater (intermittent releases) 140,9 r				
Marine water		140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment		552 mg/kg		
Secondary poisoning		160 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil				

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 6 of 11

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Alcohol

Melting point/freezing point:

-89,5 °C

Boiling point or initial boiling point and

82,5 °C

boiling range: Flammability

Solid/liquid:
Gas:
No data available
No data available
No data available
Lower explosion limits:
2 vol. %
Upper explosion limits:
13 vol. %
Flash point:
11,7 °C



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 7 of 11

Auto-ignition temperature: 425 °C
Decomposition temperature: No data available
pH-Value (at 20 °C): neutral
Viscosity / kinematic: No data available
Water solubility: easily soluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: log Pow: 0,05 Vapour pressure: 44 hPa

(at 20 °C)

Vapour pressure: 76 hPa hPa

(at 50 °C)

Density: 0,786 g/cm³
Bulk density: No data available
Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available No data available Solvent separation test: No data available Solvent content: Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point: No data available No data available 2.2 mPa·s Viscosity / dynamic:

(at 20 °C)

Flow time: No data available

Further Information No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

Formation of: Peroxides

10.2. Chemical stability

Protect against:

Light

Air

10.3. Possibility of hazardous reactions

Oxidising agent, Alkali metals, Alkaline earth metal,

, Nitric acid, aldehydes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 8 of 11

Amines, Aluminium, Chlorine (CI2)

Phosphorus trichloride, Strong acid, Phosgene Hydrogen peroxide, Nitrogen oxides (NOx), Iron.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Light Air

10.5. Incompatible materials

Rubber articles

Plastic articles

10.6. Hazardous decomposition products

Peroxides

In case of fire:

SECTION 5: Firefighting measures

Further information

Peroxides

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

Further information

No data available



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 9 of 11

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity Dose [h] [d] Species Source Method						
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 10000 mg/l	96 h Pimepha	lles promelas	` ,	OECD Guideline 203	

12.2. Persistence and degradability

95 %; 21 d; aerob

OECD-301E

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1



Safety Data Sheet

according to Regulation (EC) No 1907/2006

	according to resignation (25) no 1557/2555				
2-Propanol min. 99,8%					
Revision date: 11.01.2023	Product code: 21496	Page 10 of 11			
Special Provisions:	601				
Limited quantity:	1L				
Excepted quantity:	E2				
Transport category:	2				
Hazard No:	33				
Tunnel restriction code:	D/E				
Inland waterways transport (ADN)					
14.1. UN number or ID number:	UN 1219				
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)				
14.3. Transport hazard class(es):	3				
14.4. Packing group:	II				
Hazard label:	3				
Classification code:	F1				
Special Provisions:	601				
Limited quantity:	1 L				
Excepted quantity:	E2				
Marine transport (IMDG)					
14.1. UN number or ID number:	UN 1219				
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)				
14.3. Transport hazard class(es):	3				
14.4. Packing group:	II				
Hazard label:	3				
Special Provisions:	-				
Limited quantity:	1L				
Excepted quantity:	E2				
EmS:	F-E, S-D				
Air transport (ICAO-TI/IATA-DGR)					
14.1. UN number or ID number:	UN 1219				
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)				
14.3. Transport hazard class(es):	3				
14.4. Packing group:	II				
Hazard label:	3				
Special Provisions:	A180				
Limited quantity Passenger:	1L				
Passenger LQ:	Y341				
Excepted quantity:	E2				
IATA may quantity Passanger:	353 5 L				
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	364				
IATA-packing instituctions - Cargo:	60 L				
14.5. Environmental hazards	00 L				
14.5. Environmental hazarus					

SECTION 15: Regulatory information

ENVIRONMENTALLY HAZARDOUS:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU

(SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol min. 99,8%

Revision date: 11.01.2023 Product code: 21496 Page 11 of 11

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.