

according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

UFI: 75UW-S14W-K00F-8N28

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: Fa. Bernd Kraft GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

e-mail: info@berndkraft.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@berndkraft.de

Internet: www.berndkraft.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Ammonia

Signal word: Danger



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 2 of 14

Pictograms:







Hazard statements

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation	Classification (GB CLP Regulation)			
1336-21-6	Ammonia		10 - < 15 %		
	215-647-6	007-001-01-2	01-2119488876-14		
	Skin Corr. 1B, Aquatic Acute 1, Ac	uatic Chronic 2; H314 H400 H411			
12125-02-9	ammonium chloride		5 - < 10 %		
	235-186-4	017-014-00-8	01-2119487950-27		
	Acute Tox. 4, Eye Irrit. 2; H302 H319				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
1336-21-6	215-647-6	Ammonia	10 - < 15 %
	inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 M acute; H400: M=10		
12125-02-9	235-186-4	ammonium chloride	5 - < 10 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1410 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 3 of 14

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

Avoid contact with skin, eyes and clothes.

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Corrosion

Cough

Dyspnoea

Gastrointestinal complaints

gastric perforation

Unconsciousness

Vomiting

Circulatory collapse

Spasms

Pulmonary oedema

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction



Safety Data Sheet

according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 4 of 14

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 5 of 14

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour/aerosol.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Corrosive to metals.

Unsuitable container/equipment material: Metal

Hints on joint storage

national regulations

Further information on storage conditions

Keep away from heat.

Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	WEL
		-	20		STEL (15 min)	WEL



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1336-21-6	Ammonia			
Worker DNEL	, long-term	inhalation	systemic	47,6 mg/m³
Worker DNEL	, acute	inhalation	systemic	47,6 mg/m³
Worker DNEL	, long-term	inhalation	local	14 mg/m³
Worker DNEL	, acute	inhalation	local	36 mg/m³
Worker DNEL	, long-term	dermal	systemic	6,8 mg/kg bw/day
Worker DNEL	, acute	dermal	systemic	6,8 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	23,8 mg/m³
Consumer DN	EL, acute	inhalation	systemic	23,8 mg/m³
Consumer DNEL, long-term		inhalation	local	2,8 mg/m³
Consumer DNEL, acute		inhalation	local	7,2 mg/m³
Consumer DN	EL, long-term	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	6,8 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	6,8 mg/kg bw/day
12125-02-9	ammonium chloride			
Consumer DN	EL, long-term	inhalation	systemic	9,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	114 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11,4 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	33,5 mg/m³
Worker DNEL	, long-term	dermal	systemic	190 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment Value			
1336-21-6	Ammonia		
Freshwater		0,001 mg/l	
Freshwater (intermittent releases) 0,007 mg/l		0,007 mg/l	
Marine water 0,001 mg/l		0,001 mg/l	
12125-02-9	ammonium chloride		
Freshwater 1,2 mg/l		1,2 mg/l	
Freshwater (intermittent releases) 1,2 mg/l		1,2 mg/l	
Marine water 11,2 mg/l		11,2 mg/l	
Micro-organisms in sewage treatment plants (STP) 16,2 mg/l			
Soil 0,163 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 7 of 14

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 730 Camatril® Velours
Recommended material: NBR (Nitrile rubber) 0,4 mm
Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range: Flammability

Solid/liquid: No data available



Safety Data Sheet

according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 8 of 14

Gas No data available No data available Lower explosion limits: No data available Upper explosion limits: Flash point: No data available Auto-ignition temperature: No data available No data available Decomposition temperature: 10.6 pH-Value: Viscosity / kinematic: No data available completely miscible Water solubility:

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

(at 20 °C)

Vapour pressure:No data availableDensity:0,9647 g/cm³Bulk density:No data availableRelative vapour density:No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available UN Test L.2

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

Keep cool. Protect from sunlight.

10.3. Possibility of hazardous reactions



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 9 of 14

Oxidising agent, mercury (Hg)., Oxygen, Hydrogen peroxide, Acid, Chlorine, Heavy metals, Nitric acid, Bromine, Hydrogen bromide (HBr), Hydrochloric gas, Nitrogen oxides (NOx), Hydrogen fluoride, Carbon dioxide.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source	Method	
1336-21-6	Ammonia						
	oral	LD50 mg/kg	350	Rat	Journal of Industrial Hygiene and Toxico	OECD Guideline 401	
	inhalation (1 h) vapour	LC50 mg/l	4230	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity	
12125-02-9	ammonium chloride						
	oral	LD50 mg/kg	1410	Rat	Other company data (1983)	other: not mentioned	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2010)	EU Method B.3	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Ammonia)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 10 of 14

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

Irritant

Corrosion

Cough

Dyspnoea

Gastrointestinal complaints

gastric perforation

Unconsciousness

Vomiting

Circulatory collapse

Spasms

Pulmonary oedema

Further information

Risk of serious damage to eyes.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 11 of 14

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
1336-21-6	Ammonia						
	Acute fish toxicity	LC50 3,4 mg/l	0,75 -	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986	other: ASTM E729-80
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210
12125-02-9	ammonium chloride						
	Acute fish toxicity	LC50	209 mg/l	96 h	Cyprinus carpio	Indian J. Environ. Health, 17, 140-146,	other: E03-05:APHA, AWWA & WPCF
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: ASTM E729-80
	Fish toxicity	NOEC mg/l	11,8	28 d	Pimephales promelas	Env.Tox. Chem. 5, 437-442 (1986) (1986)	other: - American Society for Testing an
	Algae toxicity	NOEC mg/l	26,8	10 d	Navicula sp.	Mar. Biol. 43(4), 307-315, (1977) (1977)	no data
	Crustacea toxicity	NOEC mg/l	14,6	21 d	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: not mentioned
	Acute bacteria toxicity	(EC50 mg/l)	1618	0,5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.



Safety Data Sheet

according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 12 of 14

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2672
-------------------------------	---------

14.2. UN proper shipping name: Ammonia solution

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 8 C5 Classification code: 543 Special Provisions: 5 L Limited quantity: Excepted quantity: E1 Transport category: 3 Hazard No: 80 F Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2672

14.2. UN proper shipping name: Ammonia solution

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C5Special Provisions:543Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 2672

14.2. UN proper shipping name: Ammonia solution

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Marine pollutant:PSpecial Provisions:-Limited quantity:5 LExcepted quantity:E1



according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 13 of 14

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2672

14.2. UN proper shipping name: Ammonia solution

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8

Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A64 A803

1 L

Y841

Excepted quantity:

E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Ammonia

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU

E1 Hazardous to the Aquatic Environment

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,14.

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.



Safety Data Sheet

according to UK REACH Regulation

Buffer solution pH 10.0 for determination of Ca and Mg complexometric procedure DIN 38406:2002, DEV

Revision date: 28.09.2022 Product code: 21608 Page 14 of 14

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)