

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

info@analytichem.de e-mail:

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

e-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de Abteilung Produktsicherheit Responsible Department:

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: number:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Paraffins (petroleum), normal C5-20

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 2 of 9

Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|---|----------|-------------|----------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 64771-72-8 | Paraffins (petroleum), normal C5-20 | | 75 - < 80 % | |
| | 265-233-4 | | | |
| | Asp. Tox. 1; H304 EUH066 | | | |
| 90-12-0 | 1-methylnaphthalene | | 15 - < 20 % | |
| | 201-966-8 | | | |
| | Acute Tox. 4, Aquatic Chronic 2; H302 H411 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|---------|--|---------------------|-------------|
| | Specific Conc. Limits, M-factors and ATE | | |
| 90-12-0 | 201-966-8 | 1-methylnaphthalene | 15 - < 20 % |
| | oral: ATE = 500 mg/kg | | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Carbon dioxide (CO2)

Extinguishing powder

Water

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2), Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.



according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 4 of 9

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment.

Do not breathe vapour/aerosol.

Provide adequate ventilation.

Advice on protection against fire and explosion

Usual measures for fire prevention.

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place.

Keep container tightly closed.

Hints on joint storage

No data available

Further information on storage conditions

Keep cool. Protect from sunlight. storage temperature +15°C - +25°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|---------|---------------------|-----|-------|---------|-----------|--------|
| 90-12-0 | 1-Methylnaphthalene | 0.5 | - | | TWA (8 h) | |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.



according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 5 of 9

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

aoaales

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: light yellow
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

No data available Flammability: Lower explosion limits: No data available No data available Upper explosion limits: Flash point: No data available No data available Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: Viscosity / kinematic: No data available Water solubility: No data available



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 6 of 9

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

0,8241 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available Solid content: No data available No data available Sublimation point: Softening point: No data available No data available Pour point: No data available Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures



according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 7 of 9

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|---------|---------------------|------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 90-12-0 | 1-methylnaphthalene | | | | |
| | | ATE 500 mg/kg | | | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

No data available

Further information

Gastrointestinal complaints

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 8 of 9

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

| Land transp | ort (AD | R/RID) |
|-------------|---------|--------|
|-------------|---------|--------|

| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

| , , , | |
|-----------------------------------|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Test fluid group 3a for diesel fuels (DIN EN 590:2004-03) containing max. 5 vol. % biodiesel (includ

Revision date: 15.03.2023 Product code: 21869 Page 9 of 9

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU

Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Asp. Tox. 1; H304 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)