



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Acetone for analysis solvent for METROHM

REACH Registration Number:	01-2119471330-49-XXXX
CAS No:	67-64-1
Index No:	606-001-00-8
EC No:	200-662-2

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

Laboratory chemical Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

.3. Details of the supplier of the safety data shee	t
---	---

1.3. Details of the supplier of the sa	fety data sheet	
Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
<u>1.4. Emergency telephone</u> number:	For Hazardous Materials [or Dangerous Exposure, or Accident Call CHEMTREC 1-800-424-9300 Outside USA and Cana accepted)	Day or Night Within USA and Canada:

## **Further Information**

No data available

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

**Pictograms:** 

H225



Hazard statements

Highly flammable liquid and vapour.



# according to Regulation (EC) No 1907/2006

Acetone	for	analysis	solvent	for	METROHM
Acelone	101	allalysis	SOIVEIIL	101	

	Acetone for analysis solvent for METROTIM	
Revision date: 08.11.2023	Product code: 22044	Page 2 of 12
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
Precautionary statemer	nts	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P240	Ground and bond container and receiving equipment.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
Special labelling of cert	ain mixtures	
EUH066	Repeated exposure may cause skin dryness or cracking.	
2.3. Other hazards		

## No information available.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Sum formula:	C3H6O
Molecular weight:	58,08 g/mol

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone			100 %
	200-662-2 606-001-00-8 01-2119471330-49-XXXX			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	C No Chemical name	
	Specific Conc. Limits, M-factors and ATE		
67-64-1	200-662-2 acetone		100 %
dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg			

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

No data available

## After inhalation

Provide fresh air. Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 3 of 12

ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Anaesthetic state Vomiting, Headache, Dizziness Gastrointestinal complaints, Corneal opacity. Has degreasing effect on the skin. Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2). Foam.

Extinguishing powder

## Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquid. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide Beware of reignition.

## 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases. Avoid contact with skin, eyes and clothes. In case of fire: Wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## Additional information

Danger of bursting container. Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice


Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Take action to prevent static discharges.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.





according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 4 of 12

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

## For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

## For containment

Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe vapour/aerosol. Provide adequate ventilation.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### Advice on general occupational hygiene

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Keep away from food, drink and animal feedingstuffs. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

## Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary.

## 7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 5 of 12

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. storage temperature:  $+5^{\circ}C - +30^{\circ}C$ 

#### Further information on storage conditions

Keep cool. Protect from sunlight.

Protect against: Light

## 7.3. Specific end use(s)

Laboratory chemicals

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	

#### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

## **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone			
Worker DNEL,	long-term	inhalation	systemic	1210 mg/m³
Worker DNEL,	acute	inhalation	local	2420 mg/m³
Worker DNEL,	long-term	dermal	systemic	186 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	200 mg/m³
Consumer DN	EL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	62 mg/kg bw/day

**PNEC** values

CAS No	Substance			
Environmental compartment Value				
67-64-1	acetone			
Freshwater		10,6 mg/l		
Freshwater (intermittent releases) 21 mg/l				
Marine water 1,06 mg/l				
Freshwater sediment 30,4 mg/kg				
Marine sediment 3,04 mg/kg				
Micro-organisms in sewage treatment plants (STP)		100 mg/l		
Soil		29,5 mg/kg		

#### 8.2. Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 6 of 12

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour/aerosol.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles. Face protection umbrella

#### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation: KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

## Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Take off immediately all contaminated clothing. Wash hands before breaks and after work. Draw up and observe skin protection programme.

#### **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: AX

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	fruity	
Odour threshold:	No data available	
Melting point/freezing point:		-95,4 °C
Boiling point or initial boiling point and		56,2 °C
boiling range:		
Flammability:		No data available
Lower explosion limits:		2,15 vol. %



according to Regulation (EC) No 1907/2006

Upper explosion limits: Flash point: Auto-ignition temperature: Decomposition temperature: pH-Value (at 20 °C):	ode: 22044 13 vol. % <-20 °C 465 °C No data available 5-6 (395 g/l) No data available very soluble	Page 7 of 12
Flash point: Auto-ignition temperature: Decomposition temperature: pH-Value (at 20 °C):	<-20 °C 465 °C No data available 5-6 (395 g/l) No data available	
Auto-ignition temperature: Decomposition temperature: pH-Value (at 20 °C):	465 °C No data available 5-6 (395 g/l) No data available	
Decomposition temperature: pH-Value (at 20 °C):	No data available 5-6 (395 g/l) No data available	
pH-Value (at 20 °C):	5-6 (395 g/l) No data available	
	No data available	
	No data available	
Viscosity / kinematic:	very soluble	
Water solubility:	-	
Solubility in other solvents		
No data available		
Dissolution rate:	No data available	
Partition coefficient n-octanol/water:	log Pow: -0,23	
Dispersion stability:	No data available	
Vapour pressure:	240 hPa	
(at 20 °C)		
Vapour pressure:	No data available	
Density:	0,79 g/cm³	
Relative density:	No data available	
Bulk density:	No data available	
Relative vapour density:	No data available	
Particle characteristics:	No data available	
9.2. Other information		
Information with regard to physical hazard classes		
Explosive properties		
Vapours can form explosive mixtures with air.		
Sustaining combustion:	Sustaining combustion	
Self-ignition temperature	Sustaining combustion	
Solid:	not applicable	
Gas:	not applicable	
Oxidizing properties		
No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	100%	
Solid content:	No data available	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point:	No data available	
No data available:		
Viscosity / dynamic:	0,32 mPa·s	
(at 20 °C)	0,32 m a s	
Flow time:	No data available	
Further Information		
No data available		
SECTION 10: Stability and reactivity		

## 10.1. Reactivity

Highly flammable. Vapours can form explosive mixtures with air.

## 10.2. Chemical stability

Protect against:



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 8 of 12

Light Air

## 10.3. Possibility of hazardous reactions

Ignition hazard: Fluorine, Oxidising agent, strong; Reducing agent, strong; Nitric acid Danger of explosion: Chloroform, peroxides, for example hydrogen peroxide Exothermic reaction with: Bromine, Alkali metals Hydrogen halide, Sulphur dichloride

## 10.4. Conditions to avoid

Heat Light Air

#### 10.5. Incompatible materials

Rubber articles Plastic articles

#### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### **Further information**

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

No data available

## Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-64-1	acetone			-		
	oral	LD50 mg/kg	5800	Rat	J Toxicol Environ Health 15: 609-621 (19	Undiluted acetone applied to female rats
	dermal	LD50 mg/kg	> 7426	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965	other: Code of federal regulations: 21 C

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Has degreasing effect on the skin.

Repeated exposure may cause skin dryness or cracking.

## Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 9 of 12

#### STOT-single exposure

May cause drowsiness or dizziness. (acetone)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure No data available

No data avaliable

## Specific effects in experiment on an animal

No data available

## Additional information on tests

No data available

#### Practical experience No data available

No data avaliable

## 11.2. Information on other hazards

Endocrine disrupting properties No data available

## Other information

No data available

## **Further information**

Irritant, Dizziness, Anaesthetic state Vomiting, Headache, Dizziness Gastrointestinal complaints, Corneal opacity. Has degreasing effect on the skin. Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-64-1	acetone						
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984)	OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978)	The toxicity of acetone towards daphnids
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310	Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	EC50 mg/l()	61150	,	activated sludge of a predominantly domestic sewag	Water Res 26: 887-892 (1992)	ISO 8192

## 12.2. Persistence and degradability

91 %; 28 d

## 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 10 of 12

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,23
BCF		

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone	3		Unpublished calculat

#### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

#### 12.7. Other adverse effects

Avoid release to the environment.

#### Further information

Do not allow to enter into surface water or drains.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

#### **Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	ACETONE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	ACETONE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L



## according to Regulation (EC) No 1907/2006

Ace	tone for analysis solvent for METROHM	
Revision date: 08.11.2023	Product code: 22044	Page 11 of 2
Excepted quantity:	E2	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1090	
14.2. UN proper shipping name:	ACETONE	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Special Provisions:	-	
Limited quantity:	1 L	
Excepted quantity:	E2	
EmS:	 F-E, S-D	
	,	
Air transport (ICAO-TI/IATA-DGR) 14.1. UN number or ID number:	UN 1090	
	ACETONE	
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Limited quantity Passenger:	1L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:	353	
IATA-max. quantity - Passenger:	5 L	
IATA-packing instructions - Cargo:	364	
IATA-max. quantity - Cargo:	60 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user Warning: Combustible liquid.		
<b>.</b> .		
14.7. Maritime transport in bulk according	to IMO instruments	
not applicable		
SECTION 15: Regulatory information		
5.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII)	:	
Entry 3, Entry 40		
Information according to Directive 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS	
Marketing and use of explosives precurso	rs (Regulation (EU) 2019/1148):	
	n (EU) 2019/1148: all suspicious transactions, and significant	
1 0 0	reported to the relevant national contact point.	
Additional information		
	nces of very high concern according to Regulation (EC) No 1907/2006 tive regulatory concentration limit of = 0.1 % (w/w).	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'j	uvenile
Water hazard class (D):	work protection guideline' (94/33/EC). 1 - slightly hazardous to water	

## SECTION 16: Other information



according to Regulation (EC) No 1907/2006

## Acetone for analysis solvent for METROHM

Revision date: 08.11.2023

Product code: 22044

Page 12 of 12

## Changes

This data sheet contains changes from the previous version in section(s): 9,12.

## Abbreviations and acronyms

- Flam. Liq: Flammable liquid
- Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.