

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

2-Propanol for analysis solvent for METROHM

REACH Registration Number: 01-2119457558-25-XXXX  
CAS No: 67-63-0  
Index No: 603-117-00-0  
EC No: 200-661-7

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH  
Street: Stempelstraße 6  
Place: D-47167 Duisburg  
Telephone: 0203/5194-0  
E-mail: info@analytichem.de  
Contact person: Abteilung Produktsicherheit  
E-mail: produktsicherheit@analytichem.de  
Internet: www.analytichem.de  
Responsible Department: Abteilung Produktsicherheit  
Telefax: 0203/5194-290  
Telephone: 0203/5194-107/117

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

No data available

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Eye Irrit. 2; H319  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



###### Hazard statements

H225 Highly flammable liquid and vapour.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 2 of 11

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Sum formula: CH<sub>3</sub>CH(OH)CH<sub>3</sub>  
Molecular weight: 60,1 g/mol

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

No data available

##### After inhalation

Provide fresh air.  
Call a physician immediately.

##### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Observe risk of aspiration if vomiting occurs.  
Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 3 of 11

Respiratory complaints  
Headache  
Dizziness  
Dizziness  
Inebriation  
Anaesthetic state  
Unconsciousness  
Repeated exposure may cause skin dryness or cracking.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

##### **Unsuitable extinguishing media**

no restriction

#### **5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

##### **For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 4 of 11

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

##### **Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### **Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

##### **Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### **Further information on storage conditions**

Protect from sunlight.

Protect against: Light

minimum storage temperature +5°C

maximum storage temperature +30°C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Propanol for analysis solvent for METROHM**

Revision date: 22.11.2023

Product code: 22045

Page 5 of 11

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

goggles

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**2-Propanol for analysis solvent for METROHM**

Revision date: 22.11.2023

Product code: 22045

Page 6 of 11

Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: &gt; 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): &gt; 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Alcohol
Odour threshold:	No data available
Melting point/freezing point:	-89,5 °C
Boiling point or initial boiling point and boiling range:	82,5 °C
Flammability:	No data available
Lower explosion limits:	2 vol. %
Upper explosion limits:	13 vol. %
Flash point:	11,7 °C
Auto-ignition temperature:	425 °C

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 7 of 11

Decomposition temperature:	No data available
pH-Value (at 20 °C):	neutral
Viscosity / kinematic:	No data available
Water solubility:	easily soluble
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 0,05
Dispersion stability:	No data available
Vapour pressure:	44 hPa
(at 20 °C)	
Vapour pressure:	76 hPa hPa
(at 50 °C)	
Density:	0,786 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

###### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

###### Sustaining combustion:

Sustaining combustion

###### Self-ignition temperature

Solid:

No data available

Gas:

No data available

###### Oxidizing properties

No data available

##### Other safety characteristics

###### Evaporation rate:

No data available

###### Solvent separation test:

No data available

###### Solvent content:

No data available

###### Solid content:

No data available

###### Sublimation point:

No data available

###### Softening point:

No data available

###### Pour point:

No data available

###### Viscosity / dynamic:

2,2 mPa·s

    (at 20 °C)

###### Flow time:

No data available

##### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours may form explosive mixtures with air.

Formation of: Peroxides

### 10.2. Chemical stability

Protect against:

Light

Air

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 8 of 11

#### **10.3. Possibility of hazardous reactions**

Oxidising agent, Alkali metals, Alkaline earth metal,  
, Nitric acid, aldehydes  
Amines, Aluminium, Chlorine (Cl<sub>2</sub>)  
Phosphorus trichloride, Strong acid, Phosgene  
Hydrogen peroxide, Nitrogen oxides (NO<sub>x</sub>), Iron.

#### **10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Light  
Air

#### **10.5. Incompatible materials**

Rubber articles  
Plastic articles

#### **10.6. Hazardous decomposition products**

Peroxides  
In case of fire:  
SECTION 5: Firefighting measures

#### **Further information**

Peroxides

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

##### **Toxicokinetics, metabolism and distribution**

No data available

##### **Acute toxicity**

Based on available data, the classification criteria are not met.

##### **Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

##### **Sensitising effects**

Based on available data, the classification criteria are not met.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

##### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

##### **Aspiration hazard**

Based on available data, the classification criteria are not met.

##### **Information on likely routes of exposure**

No data available

##### **Specific effects in experiment on an animal**

No data available

##### **Additional information on tests**

No data available

##### **Practical experience**

No data available

#### **11.2. Information on other hazards**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Propanol for analysis solvent for METROHM**

Revision date: 22.11.2023

Product code: 22045

Page 9 of 11

**Endocrine disrupting properties**

No data available

**Other information**

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia  
Repeated exposure may cause skin dryness or cracking.

**Further information**

No data available

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203

**12.2. Persistence and degradability**

95 %; 21 d; aerob  
OECD-301E  
Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2-Propanol for analysis solvent for METROHM**

Revision date: 22.11.2023

Product code: 22045

Page 10 of 11

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Classification code: F1  
 Special Provisions: 601  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Classification code: F1  
 Special Provisions: 601  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3  
 Special Provisions: A180  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2-Propanol for analysis solvent for METROHM

Revision date: 22.11.2023

Product code: 22045

Page 11 of 11

#### SECTION 15: Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

###### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive  
2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

###### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

#### SECTION 16: Other information

##### Changes

This data sheet contains changes from the previous version in section(s): 12.

##### Abbreviations and acronyms

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

##### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

##### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.