

# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

UFI:

### HW3Y-31QQ-D00K-JPV4

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

#### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMT	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and 0	Canada: +1 703-741-5970 (collect calls
	accepted)	

#### **Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1A; H350i Repr. 1B; H360D STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### **GB CLP Regulation**

Hazard components for labelling nitric acid nickel dinitrate

Signal word:

Danger



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

**Pictograms:** 

Product code: 22071

Page 2 of 13



# Hazard statements

H290	May be corrosive to metals.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

Obtain special instructions before use.
Wear protective gloves/protective clothing/eye protection/face protection/hearing
protection.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
present and easy to do. Continue rinsing.
IF exposed or concerned:
Immediately call a POISON CENTER/doctor.

### Special labelling of certain mixtures

Restricted to professional users.

#### 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

#### Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation					
7697-37-2	nitric acid			1 - < 5 %		
	231-714-2	01-2119487297-23				
	Ox. Liq. 3, Met. Corr. 1, Acute Tox	. 3, Skin Corr. 1A; H272 H290 H331	H314 EUH071			
13138-45-9	nickel dinitrate			< 1 %		
	236-068-5	028-012-00-1				
	Ox. Sol. 2, Carc. 1A, Muta. 2, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H350i H341 H360D H332 H302 H315 H318 H334 H317 H372 H400 H410					

Full text of H and EUH statements: see section 16.



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

. . ..

....

. . \_\_\_

Product code: 22071

Page 3 of 13

	nc. Limits, M-fac		
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	1 - < 5 %
		E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 rr. 1B; H314: >= 5 - < 20	
13138-45-9	236-068-5	nickel dinitrate	< 1 %
	361,9 mg/kg S	,	

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### General information

No data available

### After inhalation

Provide fresh air. Call a physician immediately.

#### After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

# After ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Allergic reactions

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated:



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 4 of 13

Hydrochloric gas Metal oxide smoke, toxic

# 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Provide adequate ventilation. Avoid contact with skin, eyes and clothes.



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 5 of 13

### Advice on protection against fire and explosion

Usual measures for fire prevention.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

Take on infinediately all contaminated clothing and wash it before reus

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

# Hints on joint storage

national regulations

# Further information on storage conditions

Unsuitable container/equipment material: Metal

### 7.3. Specific end use(s)

Laboratory chemicals

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL

#### **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
13138-45-9	nickel dinitrate		-				
Consumer DN	EL, acute	oral	systemic	0,012 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day			
Worker DNEL,	acute	inhalation	systemic	104 mg/m³			
Worker DNEL, acute		inhalation	local	1,6 mg/m³			
Consumer DNEL, acute		inhalation	systemic	8,8 mg/m³			
Consumer DNEL, acute		inhalation	local	0,1 mg/m³			



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 6 of 13

### **PNEC** values

CAS No	Substance					
Environmenta	Environmental compartment Value					
13138-45-9	nickel dinitrate					
Freshwater		0,0071 mg/l				
Freshwater (intermittent releases) 0 mg/l						
Marine water 0,00						
Freshwater sediment 109 mg/kg						
Marine sedim	109 mg/kg					
Secondary po	0,12 mg/kg					
Micro-organis	0,33 mg/l					
Soil	29,9 mg/kg					

### 8.2. Exposure controls

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: Face protection shield goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

### Skin protection

Wear suitable protective clothing.



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 7 of 13

### Protective clothing acid-resistant

# **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and ch	lemical properties	
Physical state:	Liquid	
Colour:	light green	
Odour:	odourless	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		No data available
boiling range:		
Flammability:		not applicable
		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		Х
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		0,7
Viscosity / kinematic:		No data available
Water solubility:		easily soluble
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,0173 g/cm³
Bulk density:		No data available
Relative vapour density:		No data available
9.2. Other information		
Information with regard to physical ha	azard classes	
Explosive properties		
No data available		
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		
No data available		
Other safety characteristics		
Evaporation rate:		No data available
Solvent separation test:		No data available
Solvent content:		No data available
Solid content:		No data available
Sublimation point:		No data available
Softening point:		No data available
Pour point:		No data available
No data available:		
Viscosity / dynamic:		No data available



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023 Product code: 22071		Page 8 of 13
Flow time:	No data available	

## **Further Information**

Corrosive to metals

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

# Further information

No data available

### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
7697-37-2	nitric acid									
	inhalation vapour	ATE 2,65 I	mg/l							
13138-45-9	nickel dinitrate									
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425				
	inhalation vapour	ATE	11 mg/l							
	inhalation dust/mist	ATE	1,5 mg/l							

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (nickel dinitrate)

### Carcinogenic/mutagenic/toxic effects for reproduction



### an analyti**chem** brand

# Safety Data Sheet

according to UK REACH Regulation

# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 9 of 13

May cause cancer by inhalation. (nickel dinitrate) May damage the unborn child. (nickel dinitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (nickel dinitrate)

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### Practical experience

There are no data available on the mixture itself.

### 11.2. Information on other hazards

### Other information

There are no data available on the mixture itself.

### **Further information**

Irritant

### **SECTION 12: Ecological information**

### 12.1. Toxicity

There are no data available on the mixture itself.



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 10 of 13

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method			
7697-37-2	nitric acid	nitric acid								
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26			
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical			
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso			
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209			
13138-45-9	nickel dinitrate									
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported			
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m			
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729			
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported			
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat			
	Acute bacteria toxicity	(EC50	33 mg/l)	0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192			

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en

### 12.4. Mobility in soil

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. There are no data available on the mixture itself.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 11 of 13

# 12.7. Other adverse effects

Discharge into the environment must be avoided. Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted.

### Further information

Do not empty into drains.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations.

# Contaminated packaging

This material and its container must be disposed of as hazardous waste.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u>	UN 3264
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023	Product code: 22071	Page 12 of 13
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 3264	
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid)	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
Hazard label:	8	
Special Provisions:	A3 A803	
Limited quantity Passenger:	1L	
Passenger LQ:	Y841	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:	852	
IATA-max. quantity - Passenger:	5 L	
IATA-packing instructions - Cargo:	856	
IATA-max. quantity - Cargo:	60 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII):		
Entry 3, Entry 27		
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	

# **SECTION 16: Other information**

# Changes

This data sheet contains changes from the previous version in section(s): 9.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%



# Nickel standard solution 1 g/l in diluted nitric acid standard solution for METROHM

Revision date: 09.03.2023

Product code: 22071

Page 13 of 13

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 1A; H350i	Calculation method
Repr. 1B; H360D	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)