

according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Phenol / methanol mixture for analysis mixed 68: 32 volumetrically optically clear, completely co

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Corr. 1B; H314 Eye Dam. 1; H318 Muta. 2; H341 STOT SE 1; H370 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

phenol methanol

Signal word: Danger



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 2 of 15

Pictograms:









Hazard statements

H225 Highly flammable liquid and vapour.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
H314 Causes severe skin burns and eye damage.
H341 Suspected of causing genetic defects.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	ndex No REACH No		
	Classification (Regulation (EC) No 1272/2008)				
108-95-2	phenol			65 - < 70 %	
	203-632-7	604-001-00-2	604-001-00-2 01-2119471329-32		
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H373 H411				
67-56-1	methanol			30 - < 35 %	
	200-659-6	603-001-00-X	01-2119433307-44		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. I					
108-95-2	203-632-7	203-632-7 phenol				
	850 mg/kg; oral	= 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = : LD50 = 530 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - 2; H319: >= 1 - < 3				
67-56-1	200-659-6	methanol	30 - < 35 %			
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10					



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 3 of 15

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

After ingestion

Provide fresh air.

Rinse mouth immediately and drink plenty of water.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

corrosive, Irritant, Cough

Dyspnoea, Cardiac arrhythmias, Circulatory collapse

Dizziness, Risk of serious damage to eyes.

Dizziness, Anaesthetic state

Agitation, Spasms

Inebriation, Vomiting

Headache, Impairment of vision

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Highly flammable.

Hazardous combustion products

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 4 of 15

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 5 of 15

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep locked up.

Store in a place accessible by authorized persons only.

Provide adequate ventilation as well as local exhaustion at critical locations.

Further information on storage conditions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect against: Light

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
108-95-2	Phenol	2	8		TWA (8 h)	
		4	16		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-95-2	Phenol	Phenol	120 mg/g	Creatinine	End of shift
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 6 of 15

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
108-95-2	phenol					
Worker DNEL,	long-term	inhalation	systemic	8 mg/m³		
Worker DNEL,	acute	inhalation	local	16 mg/m³		
Worker DNEL,	long-term	dermal	systemic	1,23 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	1,32 mg/m³		
Consumer DNI	EL, long-term	dermal	systemic	0,4 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	0,4 mg/kg bw/day		
67-56-1	methanol					
Consumer DNI	EL, acute	inhalation	systemic	50 mg/m³		
Worker DNEL,	long-term	inhalation	systemic	260 mg/m³		
Worker DNEL,	acute	inhalation	systemic	260 mg/m³		
Worker DNEL,	long-term	inhalation	local	260 mg/m³		
Worker DNEL,	acute	inhalation	local	260 mg/m³		
Worker DNEL,	long-term	dermal	systemic	40 mg/kg bw/day		
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	50 mg/m³		
Consumer DNI	EL, long-term	inhalation	local	50 mg/m³		
Consumer DNEL, acute		inhalation	local	50 mg/m³		
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day		
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	8 mg/kg bw/day		
Consumer DNI	EL, acute	oral	systemic	8 mg/kg bw/day		



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 7 of 15

PNEC values

CAS No	Substance			
Environmental	Environmental compartment			
108-95-2	phenol			
Freshwater		0,008 mg/l		
Freshwater (in	termittent releases)	0,031 mg/l		
Marine water		0,001 mg/l		
Freshwater se	diment	0,091 mg/kg		
Marine sediment		0,009 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2,1 mg/l		
Soil		0,136 mg/kg		
67-56-1	methanol			
Freshwater		20,8 mg/l		
Freshwater (in	termittent releases)	1540 mg/l		
Marine water		2,08 mg/l		
Freshwater sediment 77		77 mg/kg		
Marine sediment 7,7 mg		7,7 mg/kg		
Micro-organisms in sewage treatment plants (STP)		100 mg/l		
Soil		100 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 120 min



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing, gloves and eye/face protection.

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

>35 °C

boiling range:

Flammability: No data available Lower explosion limits: No data available Upper explosion limits: No data available Flash point: <21 °C No data available Auto-ignition temperature: No data available Decomposition temperature: pH-Value: not determined Viscosity / kinematic: No data available Water solubility: No data available

Solubility in other solvents

not determined

No data available Dissolution rate: Partition coefficient n-octanol/water: No data available Dispersion stability: No data available No data available Vapour pressure: Vapour pressure: No data available Density: No data available Relative density: No data available Bulk density: No data available Relative vapour density: No data available Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 9 of 15

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available
No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

Protect against: Light

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal

Plastic articles

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 10 of 15

ATEmix calculated

ATE (oral) 100,0 mg/kg; ATE (dermal) 535,7 mg/kg; ATE (inhalation vapour) 3,000 mg/l; ATE (inhalation dust/mist) 0,5000 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
108-95-2	phenol							
	oral	LD50 mg/kg	530	Rat	J Pharmacol Exp Ther 80: 233-240 (1944)	OECD Guideline 401		
	dermal	LD50 mg/kg	850	Rabbit	Am Ind Hyg Assoc J 37: 596-606 (1976)	OECD Guideline 402		
	inhalation vapour	ATE	3 mg/l					
	inhalation dust/mist	ATE	0,5 mg/l					
67-56-1	methanol							
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t		
	dermal	ATE mg/kg	300					
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co		
	inhalation dust/mist	ATE	0,5 mg/l					

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (phenol)

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (phenol) (liver, kidneys, heart)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 11 of 15

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

corrosive, Irritant, Cough

Dyspnoea, Cardiac arrhythmias, Circulatory collapse

Dizziness, Risk of serious damage to eyes.

Dizziness, Anaesthetic state

Agitation, Spasms Inebriation, Vomiting

Headache, Impairment of vision

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
108-95-2	phenol								
	Acute fish toxicity	LC50	8,9 mg/l	96 h	Oncorhynchus mykiss	Publication (1980)	other:		
	Acute algae toxicity	ErC50 mg/l	61,1	96 h	Pseudokirchneriella subcapitata	Environ. Toxicol. Water Qual. 7: 35-48 (other: US EPA		
	Acute crustacea toxicity	EC50	3,1 mg/l	48 h	Ceriodaphnia dubia	Publication (1991)	Test performance in compliance with EPA		
	Fish toxicity	NOEC mg/l	0,077	60 d	Cirrhina mrigala	Publication (1984)	Method: other		
	Crustacea toxicity	NOEC mg/l	0,16	16 d	Daphnia magna	Ecotoxicol. Envir. Saf. 15: 72-77 (1988)	other: NEN 6502		
67-56-1	methanol	methanol							
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975		
	Acute algae toxicity	ErC50 22000 mg/	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11		
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR		
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-95-2	phenol	1,47
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
108-95-2	phenol	17,5	Danio rerio	Publication (1985)
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not allow to enter into surface water or drains.

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, phenol)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3+6.1Classification code: FT1 Special Provisions: 274 Limited quantity: 1 L Excepted quantity: F2 Transport category: 2 Hazard No: 336 Tunnel restriction code: D/E



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 13 of 15

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, phenol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Classification code:FT1Special Provisions:274 802Limited quantity:1 L

Excepted quantity:

Marine transport (IMDG)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, phenol)

E2

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E. S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, phenol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 69, Entry 75

Information according to 2012/18/EU H2 ACUTE TOXIC

(SEVESO III):

Additional information: P5c



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 14 of 15

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage Muta: Germ cell mutagenicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Muta. 2; H341	Calculation method
STOT SE 1; H370	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H331 Toxic if inhaled.



according to Regulation (EC) No 1907/2006

Phenol / methanol mixture for analysis mixed 68 : 32 volumetrically optically clear, completely co

Revision date: 24.08.2023 Product code: 22113 Page 15 of 15

H341 Suspected of causing genetic defects.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)