

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Xylene substitute petroleum benzene dearomatized

REACH Registration Number: 01-2119471843-32-XXXX

EC No: 927-241-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

STOT SE 3; H336

Asp. Tox. 1; H304

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 2 of 11

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten			100 %
	927-241-2		01-2119471843-32-XXXX	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	927-241-2	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten	100 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 15000 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 3 of 11

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Unconsciousness

Dizziness

Spasms

Irritant

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration hazard

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 4 of 11

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 5 of 11

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 6 of 11

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Gasoline	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		110-190 °C
Flammability:		No data available
Lower explosion limits:		0,6 vol. %
Upper explosion limits:		7 vol. %
Flash point:		>23 °C
Auto-ignition temperature:		>200 °C
Decomposition temperature:		No data available
pH-Value:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		5 hPa
(at 20 °C)		
Vapour pressure:		No data available
Density:		0,76 g/cm ³
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: No data available

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: 100%

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzine dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 7 of 11

Pour point: No data available
 No data available
 Viscosity / dynamic: No data available
 Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten				
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)	OECD Guideline 423
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.
 slightly irritant but not relevant for classification.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 8 of 11

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Headache

Dizziness

Unconsciousness

Dizziness

Spasms

Irritant

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten						
	Fish toxicity	NOEC mg/l	0,182	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	0,317	21 d	Daphnia magna	Company report (2010)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

Readily biodegradable (according to OECD criteria).
(MSDS)

12.3. Bioaccumulative potential

No data available

BCF

CAS No	Chemical name	BCF	Species	Source
	Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclene, < 2% Aromaten	144,3	calculated	Other company data (

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 9 of 11

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzene dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 10 of 11

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3295
14.2. UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	A3 A324
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Asp. Tox: Aspiration hazard

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Xylene substitute petroleum benzine dearomatized

Revision date: 22.09.2023

Product code: 22781

Page 11 of 11