

| an analyti chem company | according to Regulation (EC) No 1907/2006 | | | |
|---|--|--|--------------|--|
| Lösemittelgemisch 3-M | Gemisch HH Solvesso 100 gemischt | / Butylglykol gravimetrisch 1200 + | 575 | |
| Revision date: 30.11.2022 | Product code: 23 | 382 | Page 1 of 13 | |
| SECTION 1: Identification of the se | ubstance/mixture and of the co | mpany/undertaking | | |
| 1.1. Product identifier Lösemittelgemisch 3-M Gemisch | n HH_Solvesso 100 / Butylglykol gra | vimetrisch 1200 + 575 gemischt | | |
| 1.2. Relevant identified uses of the su | bstance or mixture and uses advis | sed against | | |
| Use of the substance/mixture Laboratory chemicals Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen) | | | | |
| Uses advised against Do not use for private purposes | (household) | | | |
| 1.3. Details of the supplier of the safe | , , | | | |
| Company name: Street: Place: | Fa. Bernd Kraft GmbH Stempelstraße 6 D-47167 Duisburg | | | |
| Telephone: | 0203/5194-0 | Telefax: 0203/5194-290 | | |
| e-mail: Contact person: e-mail: Internet: Responsible Department: | info@berndkraft.de Abteilung Produktsicherheit produktsicherheit@berndkraft.de www.berndkraft.de Abteilung Produktsicherheit | Telephone: 0203/5194-107/117 | | |
| <u>1.4. Emergency telephone</u> number: | Exposure, or Accident Call CHEM | erous Goods] Incidents Spill, Leak, Fire, TREC Day or Night Within USA and Canada Canada: +1 703-741-5970 (collect calls | | |
| Further Information This product is a mixture. REACH Registration Number see section 3. | | | | |
| SECTION 2: Hazards identification | | | | |

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Acute Tox. 3; H331 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C9, aromatics (solvesso 100) 2-butoxyethanol Signal word: Danger

Revision No: 1,02 - Replaces version: 1,01



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

Revision date: 30.11.2022

Pictograms:

gemischt

Page 2 of 13



Hazard statements

| 6 | Flammable liquid and vapour. |
|-----------------------|---|
| 1 | May be fatal if swallowed and enters airways. |
| 5 | Causes skin irritation. |
| 9 | Causes serious eye irritation. |
| 1 | Toxic if inhaled. |
| 5 | May cause respiratory irritation. |
| 6 | May cause drowsiness or dizziness. |
| 1 | Toxic to aquatic life with long lasting effects. |
| 5 9 1 5 6 | Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. |

Precautionary statements

| · · · · · · · · · · · · · · · · · · · | |
|---------------------------------------|---|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No |
| | smoking. |
| P273 | Avoid release to the environment. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |
| P391 | Collect spillage. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| | |

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | Chemical name | | |
|----------|--|---------------------------------|---------------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No | o 1272/2008) | · | |
| | Hydrocarbons, C9, aromatics (solvesso 100) | | | |
| | | | 01-2119455851-35 | |
| | Flam. Liq. 3, STOT SE 3, STOT S H411 EUH066 | E 3, Asp. Tox. 1, Aquatic Chror | ic 2; H226 H335 H336 H304 | |
| 111-76-2 | 2-butoxyethanol | | | 30 - < 35 % |
| | 203-905-0 | 603-014-00-0 | 01-2119475108-36 | |
| | Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-----------------------------|--|---|-------------|
| | Specific Conc. Limits, M-factors and ATE | | |
| | | Hydrocarbons, C9, aromatics (solvesso 100) | 65 - < 70 % |
| dermal: LD50 = > 3160 mg/kg | | | |
| 111-76-2 | 203-905-0 | 2-butoxyethanol | 30 - < 35 % |
| | inhalation: ATE | 3 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: ATE 1200 mg/kg | |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Revision date: 30.11.2022

Product code: 23382

Page 3 of 13

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Do not breathe vapour/aerosol. Self-protection of the first aider

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Observe risk of aspiration if vomiting occurs.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575 gemischt

Revision date: 30.11.2022

Product code: 23382

Page 4 of 13

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Revision date: 30.11.2022

Product code: 23382

Page 5 of 13

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep cool. Protect from sunlight.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|----------|------------------------|-----|-------|---------|---------------|--------|
| 111-76-2 | 2-Butoxyethanol (EGBE) | 20 | 98 | | TWA (8 h) | |
| | | 50 | 246 | | STEL (15 min) | |

Biological limit values

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|----------|-----------------|-----------|----------|---------------|---------------|
| 111-76-2 | 2-Butoxyethanol | ВАА | 200 mg/g | Creatinine | End of shift |



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

Revision date: 30.11.2022

gemischt Product code: 23382

Page 6 of 13

DNEL/DMEL values

| CAS No | Substance | | | | |
|----------------------|---|----------------|----------|-----------------------|--|
| DNEL type | | Exposure route | Effect | Value | |
| | Hydrocarbons, C9, aromatics (solvesso 100 |) | | | |
| Worker DNE | L, long-term | dermal | systemic | 25 mg/kg bw/day | |
| Consumer D | NEL, long-term | inhalation | systemic | 32 mg/m³ | |
| Consumer D | NEL, long-term | dermal | systemic | 11 mg/kg bw/day | |
| Consumer D | NEL, long-term | oral | systemic | 11 mg/kg bw/day | |
| Worker DNE | L, long-term | inhalation | systemic | 150 mg/m³ | |
| 111-76-2 | 2-butoxyethanol | | | | |
| Consumer D | NEL, acute | oral | systemic | 26,7 mg/kg bw/day | |
| Consumer D | NEL, long-term | oral | systemic | 6,3 mg/kg bw/day | |
| Worker DNE | L, long-term | inhalation | systemic | 98 mg/m³ | |
| Worker DNE | L, acute | inhalation | systemic | 1091 mg/m³ | |
| Worker DNE | L, acute | inhalation | local | 246 mg/m ³ | |
| Worker DNE | L, long-term | dermal | systemic | 125 mg/kg bw/day | |
| Worker DNE | L, acute | dermal | systemic | 89 mg/kg bw/day | |
| Consumer D | NEL, long-term | inhalation | systemic | 59 mg/m³ | |
| Consumer D | NEL, acute | inhalation | systemic | 426 mg/m ³ | |
| Consumer D | NEL, acute | inhalation | local | 147 mg/m³ | |
| Consumer D | NEL, long-term | dermal | systemic | 75 mg/kg bw/day | |
| Consumer DNEL, acute | | dermal | systemic | 89 mg/kg bw/day | |

PNEC values

| CAS No | Substance | | |
|--|---------------------------------|------------|--|
| Environmenta | Environmental compartment Value | | |
| 111-76-2 | 2-butoxyethanol | | |
| Freshwater | | 8,8 mg/l | |
| Freshwater (intermittent releases) 26,4 mg/l | | 26,4 mg/l | |
| Marine water 0,88 mg/l | | 0,88 mg/l | |
| Freshwater sediment 34,6 mg/kg | | 34,6 mg/kg | |
| Marine sediment 3,46 m | | 3,46 mg/kg | |
| Secondary poisoning 20 mg/kg | | 20 mg/kg | |
| Micro-organisms in sewage treatment plants (STP) | | 463 mg/l | |
| Soil | | 2,33 mg/kg | |

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Revision date: 30.11.2022

Product code: 23382

Page 7 of 13

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact KCL 741 Dermatril® L NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact KCL 741 Dermatril® L NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse. Wear fire resistant or flame retardant clothing. Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | Liquid | |
|--|-------------------|-------------------|
| Colour: | clear | |
| Odour threshold: | No data available | |
| Melting point/freezing point: | | No data available |
| Boiling point or initial boiling point and | | ? |
| boiling range: | | |
| Flammability | | |
| Solid/liquid: | | not applicable |
| Gas: | | not applicable |



| Lösemittelgemisch 3-M Gemisch HH | I Solvesso 100 / Butylglykol gravimetrisch gemischt | 1200 + 575 |
|---|--|--------------|
| Revision date: 30.11.2022 | Product code: 23382 | Page 8 of 13 |
| Lower explosion limits: | No data available | |
| Upper explosion limits: | No data available | |
| Flash point: | >23 °C | |
| Auto-ignition temperature: | No data available | |
| Decomposition temperature: | No data available | |
| pH-Value: | No data available | |
| Viscosity / kinematic: | No data available | |
| Water solubility: | No | |
| Solubility in other solvents not determined | | |
| Dissolution rate: | No data available | |
| Partition coefficient n-octanol/water: | No data available | |
| Dispersion stability: | No data available | |
| Vapour pressure: | No data available | |
| Vapour pressure: | No data available | |
| Density: | 0,8815 g/cm³ | |
| Relative density: | No data available | |
| Bulk density: | No data available | |
| Relative vapour density: | No data available | |
| Particle characteristics: | No data available | |
| 9.2. Other information | | |
| Information with regard to physical hazard classe Explosive properties | | |
| Vapours are heavier than air, spread along floors | s and form explosive mixtures with air. No data available | |
| Sustaining combustion: Self-ignition temperature | | |
| Solid: | No data available | |
| Gas: | No data available | |
| Oxidizing properties | | |
| Not oxidising. | | |
| Other safety characteristics | | |
| Evaporation rate: | No data available | |
| Solvent separation test: | No data available | |
| Solvent content: | No data available | |
| Solid content: | No data available | |
| Sublimation point: | No data available | |
| Softening point: | No data available | |
| Pour point: | No data available No data available | |
| Viscosity / dynamic: | No data available | |
| Flow time: | No data available | |
| Further Information | | |
| No data available | | |
| SECTION 10: Stability and reactivity | | |

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.



| Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575 gemischt | | | | |
|--|---|--------------|--|--|
| Revision date: 30.11.2022 | Product code: 23382 | Page 9 of 13 | | |
| 10.3. Possibility of hazardous reactions | | | | |
| Oxidising agent | | | | |
| 10.4. Conditions to avoid Keep away from sources of heat (e.g mixtures with air. | . hot surfaces), sparks and open flames. Vapours can fo | rm explosive | | |
| <u>10.5. Incompatible materials</u> No data available | | | | |
| 10.6. Hazardous decomposition products SECTION 5: Firefighting measures | | | | |
| Further information No data available | | | | |
| SECTION 11: Toxicological information | | | | |
| 11.1. Information on hazard classes as def | fined in Regulation (EC) No 1272/2008 | | | |
| Toxicocinetics, metabolism and distribution | | | | |

There are no data available on the mixture itself.

Acute toxicity

Toxic if inhaled.

ATEmix calculated

ATE (oral) 3704,8 mg/kg; ATE (inhalation vapour) 9,26 mg/l

| CAS No | Chemical name | | | | | |
|----------|--|--|---------|---------------------|--------------------|--|
| | Exposure route | Dose | Species | Source | Method | |
| | Hydrocarbons, C9, aromatics (solvesso 100) | | | | | |
| | dermal | LD50 > 3160 mg/kg | Rabbit | Study report (1984) | OECD Guideline 402 | |
| 111-76-2 | 2-butoxyethanol | | | | | |
| | | | | | | |
| | oral | ATE 1200 mg/kg | | | | |
| | oral dermal | ATE 1200 mg/kg LD50 > 2000 mg/kg | Rat | Study report (1993) | OECD Guideline 402 | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Hydrocarbons, C9, aromatics (solvesso 100)) May cause drowsiness or dizziness. (Hydrocarbons, C9, aromatics (solvesso 100))

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

There are no data available on the mixture itself.



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Product code: 23382

Page 10 of 13

Revision date: 30.11.2022

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

| CAS No | Chemical name | | | | | | |
|----------|--|--------------|----------|-----------|------------------------------------|---|---|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| | Hydrocarbons, C9, aromatics (solvesso 100) | | | | | | |
| | Acute algae toxicity | ErC50 | 7,9 mg/l | 72 h | Pseudokirchneriella subcapitata | Study report (2006) | OECD Guideline 201 |
| | Acute crustacea toxicity | EC50 | 3,2 mg/l | 48 h | Daphnia magna | Study report (1994) | OECD Guideline 202 |
| | Fish toxicity | NOEC mg/l | 1,228 | 28 d | Oncorhynchus mykiss | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| | Crustacea toxicity | NOEC mg/l | 2,144 | 21 d | Daphnia magna | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 111-76-2 | 2-butoxyethanol | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 1474 | 96 h | Oncorhynchus mykiss | Toxicol Mech Meth 12, 255-63 (2002) | OECD Guideline 203 |
| | Acute algae toxicity | ErC50 | 911 mg/l | 72 h | Pseudokirchneriella subcapitata | Toxicol Mech Meth 12, 255-63 (2002) | OECD Guideline 201 |
| | Acute crustacea toxicity | EC50 mg/l | 1550 | 48 h | Daphnia magna | Toxicol Mech Meth 12, 255-63 (2002) | OECD Guideline 202 |
| | Fish toxicity | NOEC mg/l | > 100 | 21 d | Danio rerio | Toxicol Mech Meth 12, 255-63 (2002) | OECD Guideline 204 |
| | Crustacea toxicity | NOEC | 100 mg/l | 21 d | Daphnia magna | Toxicol Mech Meth 12, 255-63 (2002) | OECD Guideline 211 |

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|-----------------|---------|
| 111-76-2 | 2-butoxyethanol | 0,81 |



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Revision date: 30.11.2022

Product code: 23382

Page 11 of 13

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into soil/subsoil.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

| <u>14.1. UN number or ID number:</u> | UN 1992 |
|--------------------------------------|---|
| 14.2. UN proper shipping name: | FLAMMABLE LIQUID, TOXIC, N.O.S. (Hydrocarbons, C9, aromatics (solvesso 100), 2-butoxyethanol) |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3+6.1 |
| Classification code: | FT1 |
| Special Provisions: | 274 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 36 |
| Tunnel restriction code: | D/E |
| Inland waterways transport (ADN) | |
| 14.1. UN number or ID number: | UN 1992 |
| 14.2. UN proper shipping name: | FLAMMABLE LIQUID, TOXIC, N.O.S. (Hydrocarbons, C9, aromatics |
| | (solvesso 100), 2-butoxyethanol) |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | III |
| Hazard label: | 3+6.1 |
| Classification code: | FT1 |
| Special Provisions: | 274 802 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| | |



| Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575 gemischt | | | |
|--|---|---------------|--|
| Revision date: 30.11.2022 | Product code: 23382 | Page 12 of 13 | |
| Marine transport (IMDG) | | | |
| 14.1. UN number or ID number: | UN 1992 | | |
| 14.2. UN proper shipping name: | FLAMMABLE LIQUID, TOXIC, N.O.S. (Hydrocarbons, C9, aromatics (solvesso 100), 2-butoxyethanol) | | |
| 14.3. Transport hazard class(es): | 3 | | |
| 14.4. Packing group: | III | | |
| Hazard label: | 3+6.1 | | |
| Special Provisions: | 223, 274 | | |
| Limited quantity: | 5 L | | |
| Excepted quantity: | E1 | | |
| EmS: | F-E, S-D | | |
| Air transport (ICAO-TI/IATA-DGR) | | | |
| 14.1. UN number or ID number: | UN 1992 | | |
| 14.2. UN proper shipping name: | FLAMMABLE LIQUID, TOXIC, N.O.S. (Hydrocarbons, C9, aromatics | | |
| | (solvesso 100), 2-butoxyethanol) | | |
| 14.3. Transport hazard class(es): | 3 | | |
| 14.4. Packing group: | III | | |
| Hazard label: | 3+6.1 | | |
| Special Provisions: | A3 | | |
| Limited quantity Passenger: | 2 L | | |
| Passenger LQ: | Y343 | | |
| Excepted quantity: | E1 | | |
| IATA-packing instructions - Passenger: | 355 | | |
| IATA-max. quantity - Passenger: | 60 L | | |
| IATA-packing instructions - Cargo: | 366 | | |
| IATA-max. quantity - Cargo: | 220 L | | |
| 14.5. Environmental hazards | | | |
| ENVIRONMENTALLY HAZARDOUS: | Yes | | |
| Danger releasing substance: | Kohlenwasserstoffe, C9, Aromaten (Solvesso 100) | | |
| 14.6. Special precautions for user | | | |
| Warning: Combustible liquid. Toxic. | | | |
| 14.7. Maritime transport in bulk according to | IMO instruments | | |
| not applicable | | | |
| SECTION 15: Regulatory information | | | |
| 15.1. Safety, health and environmental regul | ations/legislation specific for the substance or mixture | | |
| | | | |
| EU regulatory information | | | |
| Restrictions on use (REACH, annex XVII): | | | |
| Entry 3, Entry 40 | | | |
| Information according to 2012/18/EU | H2 ACUTE TOXIC | | |
| (SEVESO III): | | | |
| Additional information: | P5c, E2 | | |
| National regulatory information | | | |
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juve | nile | |
| ······································ | work protection guideline' (94/33/EC). Observe employment restriction | | |
| | under the Maternity Protection Directive (92/85/EEC) for expectant or | | |
| | nursing mothers. | | |
| Water hazard class (D): | 2 - obviously hazardous to water | | |
| Skin resorption/Sensitization: | Permeates easily through outer skin and causes poisoning. | | |
| | | | |



Lösemittelgemisch 3-M Gemisch HH Solvesso 100 / Butylglykol gravimetrisch 1200 + 575

gemischt

Page 13 of 13

Revision date: 30.11.2022

Product code: 23382

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,7,8,9,11,12,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| Acute Tox. 3; H331 | Calculation method |
| Asp. Tox. 1; H304 | Calculation method |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |
| STOT SE 3; H335 | Calculation method |
| STOT SE 3; H336 | Calculation method |
| Aquatic Chronic 2; H411 | Calculation method |

Relevant H and EUH statements (number and full text)

| H226 | Flammable liquid and vapour. |
|--------|--|
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |
| FUH066 | Repeated exposure may cause skin dryness or crac |

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)